FED. SUP CLASS 6115

MS33631 SHALL BE USED AS A DESIGN GUIDE EXCEPT TERMINALS SHALL BE 5/16 X 24 STUDS, LOAD TERMINALS IN AREA "A" ALL OTHER TERMINALS IN AREA "AA"

RECEPTACLE MS-3112E-18-11S OR EQUIV.

BENDIX-SCINTILLA RECEPTACLE PT02E-20-16P OR EQUIV.

MOUNTING FLANGE AND COUPLING IN ACCORDANCE WITH AS 472 TYPE XXI-A AND AS 474

FLANGE & CLEARANCE SUITABLE FOR MOUNTING MS25159 OR MS25160

CONNECTOR CENTER SHALL REMAIN WITHIN THIS AREA

GENERATOR

REGULATOR

MS25262 SHALL BE USED AS A DESIGN GUIDE EXCEPT TERMINALS SHALL BE 5/16 X24 STUDS.

RECEPTACLES MS-3112E-14-19P & MS-3112E-20-16P OR EQUIV.

CONNECTOR CENTERS SHALL REMAIN WITHIN THIS AREA

RECEPT MS-3112E-18-11P OR EQUIV.

CONNECTOR MTG. SURFACE

.203 DIA. DRILL THRU 6 MOUNTING HOLES

CANCELLED (A)

CANCELLED (B) AFTER 28 April 1966 NO SUPERSEDING STANDARD

.203 DIA. DRILL THRU 4 MOUNTING HOLES

STATIC EXCITER

SUPERVISORY PANEL

GENERATOR DATA	
RATED VOLTAGE	120/208 V
RATED OUTPUT	20 KVA
PHASE	3
SPEED RANGE	7600-8400 RPM
MAX SPEED FOR REGULATION	8800 RPM
OVERSPEED	10,500 RPM
RATED POWER FACTOR	0.75 LAGGING TO 1.0
EFFICIENCY MIN. AT RATED LOAD	80%
MAX. WEIGHT	39 LB.
OVERHUNG MOMENT, MAX	160 IN. LB.
FREQUENCY	380-420 CPS
CLASS	C
SHEAR	1200 IN. LB. ±10%

REGULATOR DATA	
REGULATOR WEIGHT-MAXIMUM	4 LB
SUPERVISORY PANEL DATA	
SUPERVISORY PANEL WEIGHT-MAXIMUM	6 LB
STATIC EXCITER DATA	
STATIC EXCITER WEIGHT-MAXIMUM	12 LB
SYSTEMS DATA	

TYPE	GENERATOR ROTATION	REGULATOR AND SUPERVISORY PANEL
MS25363-1	CLOCKWISE	AS REQUIRED
MS25363-2	COUNTERCLOCKWISE	

THIS IS A DESIGN STANDARD. NOT TO BE USED AS A PART NUMBER.

REVISED - (A) 28 April 1966

APPROVED 7/20/59

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Department of the Navy and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. BUREAU OF AERONAUTICS
Other Cust

TITLE
GENERATOR SYSTEM, ALTERNATING CURRENT, STATICALLY EXCITED, 20 KVA

PROCUREMENT SPECIFICATION
MIL-G-21480 (AER)

SUPERSEDES:

MILITARY STANDARD
MS25363 (AER)
SHEET 1 OF 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:09Z
Check the source to verify that this is the current version before use.

DD FORM 1 SEP 57 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.