


REVIEWER EA,GL,IS,MI,SH
USER AV,MC,ME,PA,WV

FED SUP CLASS
5340



NOT SWAGED, FOR FULL SURFACE APPLICATION





SWAGED, FOR MORTISE APPLICATION

NOMINAL SIZE							
	A LENGTH	+ .00 -.02	2.00	2.00	2.00	2.50	3.00
	B WIDTH	±.02	1.50	2.00	2.50	2.50	2.00
	C	±.005	1.375	1.375	1.375	.938	1.185
	D	±.005	.312	.312	.312	.312	.312
	E	±.005	.250	.312	.312	.320	.312
	F	±.005				.516	.312
	T THICKNESS	±.005	.082	.082	.082	.089	.092
NUMBER OF SCREW HOLES			4	4	4	6	6
* SIZE OF SCREWS		MIN	#8 32 x 1/2	#8 32 x 1/2	#8 32 x 1/2	#8 32 x 1/2	#10 24 x 1/2
TYPES			DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER	DASH NUMBER
FAST PIN, NOT SWAGED			2	4	6	8	
FAST PIN, SWAGED			22	24	26	28	30

NOMINAL SIZE								
	A LENGTH	-.00 -.02	3.00	3.00	3.00	3.50		4.00
	B WIDTH	±.02	2.50	3.00	4.00	3.00		4.00
	C	±.005	1.188	1.188	1.188	1.395		1.004
	D	±.005	.312	.312	.312	.355		.512
	E	±.005	.312	.312	.312	.360	.667	.750
	F	±.005	.360	.360	.360	.667	.360	.375
	T THICKNESS	±.005	.092	.092	.092	.123		.130
NUMBER OF SCREW HOLES			6	6	6	6		8
* SIZE OF SCREWS		MIN	#10 24 x 1/2	#10 24 x 1/2	#10 24 x 1/2	#10 24 x 1/2		#12 24 x 1/2
TYPES			DASH NUMBER	DASH NUMBER	DASH NUMBER	(A) ** DASH NUMBER	DASH NUMBER	DASH NUMBER
FAST PIN, NOT SWAGED			12	14	16	**18	18	20
FAST PIN, SWAGED			32	34	36	**38	38	40

NOTES

(A) 1. MATERIAL Body Brass, in accordance with ASTM-B121 (any alloy) annealed
Pin Corrosion resisting steel, in accordance with FED. STD. No 66, number 302, 303, 304, or 305.

(1) 2. PROTECTIVE COATING Satin nickel plated, in accordance with QQ-N-290, Class 1, grade G.

(1) 3. *SCREWS Hinges are furnished with flat undercut-head UNC-2A brass screws in accordance with FF-S-92.
Brass in accordance with QQ-B-637.

4 SIZE The width dimension of not swaged hinges will be slightly narrower than shown in table.

5. DIMENSIONS All dimensions are in inches unless otherwise specified.

6 PART NUMBER The MS part number consists of the MS number, plus the dash number.
Example MS27958-6.

7 Reference documents shall be of the issue in effect on date of invitations for bid.

8 For design feature purposes, this standard takes precedence over procurement documents referenced herein.

(A)** INACTIVE FOR NEW DESIGN AFTER 30 OCT 1975

(B) Revised "C" Dim. on 2.50 Length from .928 to .938

APPROVED 24 FEB 1961 REVISED (A) 30 OCT 1975 (B) 1 NOV 1977

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

P.A. AR Other Cust YD 99	TITLE HINGE, BUTT, NARROW AND BROAD, TEMPLATE, BRASS	MILITARY STANDARD MS27958
PROCUREMENT SPECIFICATION MIL-H-1237	SUPERSEDES	SHEET 1 OF 1

DD FORM 1426 672-1 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:53Z
Check the source to verify that this is the current version before use.