

FED SUP CLASS
5306





SECTION THRU THREAD PROFILE



OPTIONAL SHAPE OF HEAD

TABLE I DASH NUMBERS AND DIMENSIONS

DASH NO.	L	K +.000 -.060	APPROX WEIGHT LB/100
-03	.312	1/	.451
-04	.375	1/	.482
-05	.438	1/	.513
-06	.500	1/	.543
-07	.562	1/	.573
-08	.625	1/	.604
-09	.688	1/	.634
-10	.750	.125	.664
-11	.812	.188	.695
-12	.875	.250	.725
-13	.938	.312	.756
-14	1.000	.375	.786
-15	1.062	.438	.816
-16	1.125	.500	.847

DASH NO.	L	K +.000 -.060	APPROX WEIGHT LB/100
-17	1.188	.562	.878
-18	1.250	.625	.908
-19	1.312	.688	.938
-20	1.375	.750	.969
-21	1.438	.812	.999
-22	1.500	.875	1.029
-23	1.562	.938	1.060
-24	1.625	1.000	1.090
-25	1.688	1.062	1.121
-26	1.750	1.125	1.151
-27	1.875	1.250	1.212
-28	2.000	1.375	1.273

1/ THREAD TO HEAD. MAXIMUM TWO IMPERFECT THREADS.

REQUIREMENTS:

1. MATERIAL: STEEL AMS 6322 (UNS G87400).
2. HARDNESS: 26-32 HRC
3. FINISH: CADMIUM PLATE PER AMS 2400. DIMENSIONS SPECIFIED ARE AFTER PLATING.
4. THREADS: THREADS IN ACCORDANCE WITH MIL-S-7742. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
6. WEIGHING CONFIGURATION: WEIGHING CONFIGURATION IN ACCORDANCE WITH AS 870.
7. SURFACE TEXTURE: SURFACE TEXTURE, UNLESS OTHERWISE SPECIFIED SHALL BE 125 MICROINCHES EXCEPT UPSET HEAD.
8. MAGNETIC PARTICLE INSPECTION: MAGNETIC PARTICLE INSPECTION PER AMS 2640.
9. TOLERANCE: UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS ±.010 , ANGULAR DIMENSIONS ±5° .
10. EDGES: BREAK SHARP EDGES .003 - .015 UNLESS OTHERWISE SPECIFIED.

INACTIVE FOR NEW DESIGN AFTER 26 OCT 72

Ⓑ ENTIRE STANDARD REVISED

APPROVED 31 MAR 68 REVISED Ⓑ 13 JUL 87

P.A. NAVY-AS / Other Cust AIR FORCE-11	INTERNATIONAL INTEREST	TITLE BOLT-MACHINE, STEEL, 12 POINT HEAD, J64(NO. 8)-36, CADMIUM PLATE	MILITARY STANDARD MS9186
PROCUREMENT SPECIFICATION AMS 7452	SUPERSEDES:		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1173

REVIEW ACTIVITIES: DLA-IS

USER ACTIVITIES:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Reference for all new engineering and design applications and for reprintive use shall be made from this document when applicable.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:12Z
Check the source to verify that this is the current version before use.

11. PART NUMBER: THE PART SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9186-03
- DASH NUMBER
- BASIC MS NUMBER

MS9186-03 INDICATES: BOLT-MACHINE, STEEL, 12 POINT HEAD, .164-36, CADMIUM PLATE, .312 LONG.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DoDISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS.

APPROVED 31 MAR 58 REVISED (B) FOR CHANGES SEE PAGES 1 AND 2

USER ACTIVITIES:
REVIEWER ACTIVITIES:
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. NAVY-AS / Other Cust AIR FORCE-11	INTERNATIONAL INTEREST	TITLE: BOLT-MACHINE, STEEL, 12 POINT HEAD, .164 (NO. 8)-36, CADMIUM PLATE	MILITARY STANDARD MS9186
PROCUREMENT SPECIFICATION: AMS 7452	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T13:12Z
Check the source to verify that this is the current version before use.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1988 505-033/90226