
AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

REVIEWER ACTIVITIES: ARMY - ME
NAVY - OS
AIR FORCE - 82

USER ACTIVITIES: ARMY - MD, EM
NAVY - MS

FED. SUP CLASS
6640



PART NUMBER	COPPER TUBE O.D. LENGTH mm (in)	GLASS TUBE OD mm
MS51421-1		6
MS51421-2		10
MS51421-3		12
MS51421-4		16
MS51421-5		19
MS51421-6		22
MS51421-7		26
MS51421-8		28
MS51421-9		35
MS51421-10		41
MS51421-11		48
MS51421-12		57
MS51421-13	(2.25)	64
MS51421-14	64 (2.50)	70
MS51421-15	70 (2.75)	75
MS51421-16	76 (3.00)	80
MS51421-17	83 (3.25)	90
MS51421-18	89 (3.50)	95
MS51421-19	101 (4.00)	110

CANCELLED
CANCELLED AFTER 20 AUG 1991
NO SUPERSEDING STANDARD

MATERIAL: Borosilicate glass and copper tubing.

DESIGN: The borosilicate glass tubing shall be fused to the copper tubing to form a seal suitable for low temperature applications. The assembly shall be oven-annealed and thermal shock tested by immersion in liquid nitrogen. Each assembly shall be vacuum tight to at least 5×10^{-9} torr or 6.666×10^{-7} Pa. The overall length shall be 229 ± 10 mm.

NOTES:
1. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.
2. FSCM: 07736.

(A) CANCELLATION

APPROVED 20 JUL 1983 REVISED (A) 20 AUG 1991

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
EA		SEAL, GRADED, BOROSILICATE GLASS TO COPPER TUBING	MS51421
Other Cust MS 99			
Procurement Specifications NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

CANCELLATION

Project Number 6640-1725-04

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:01Z
Check the source to verify that this is the current version before use.