MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6J5WGT 1/

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Triode, medium-mu

Outline	---	9-12 (EIA)
Base	---	B8-28 (metal sleeve, low-loss phenolic insert)
Envelope	---	T9
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	5	7	8
Element	---	Base sleeve	h	a	g	h	k

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	Pp	Ik	(B) Ehk	(B) Alt
Unit:	V	Vdc	Vdc	W	Adc	v	ft
Maximum:	6.3	330	---	2.75	20	100	(See note 2)
Minimum:	5.7	---	---	---	---	---	---
TEST CONDITIONS:	6.3	250	-8	---	---	---	---

GENERAL:

Qualification - Required

1/ See note 1

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.

	METHOD	REQUIREMENT OR TEST	CONDITIONS	NO. SPECIMENS INSPECTED	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
		Qualification inspection							
	1051	Variable-frequency vibration	R_p = 2,000 ohms	---	---	E_p	---	150	mVac
	---	Mechanical resonance	See note 3	---	---	---	---	---	---
S	1216	Base material insulating quality		---	---	---	---	---	---
		Quality conformance inspection, part 1							
	1308	Total grid current	See note 4	0.65	K	I_c	0	-1.5	μAdc
	1356	Electrode current (1) (anode)		0.65	K	I_b	5.5	12.5	mAdc
	1406	Transconductance (1)		0.65	K	g_m	2,975	3,125	μmhos
	1046	Audio frequency noise	E_{sig} = 300 mVac; R_p = 10,000 ohms	0.65	K	N_R	---	17	ms
	1321	Emission	E_b = E_c = 30 Vdc (see note 4)	0.65	K	I_b	40	---	mAdc
D	1301	Short and discontinuity		0.4	K	---	---	---	---
		Quality conformance inspection, part 2							
	1051	Low-frequency vibration	R_p = 2,000 ohms	---	---	E_p	---	75	mVac
D	1061	Shock	500 G	15	S2	---	---	---	---
	1071	Vibration fatigue		---	---	---	---	---	---
	---	Post-shock and vibration-fatigue test end points	Low-frequency vibration	---	---	E_p	---	150	mVac
			Heater-cathode leakage	---	---	I_{hk}	---	20	μAdc
			Transconductance (1)	---	---	g_m	1,975	3,400	μmhos
	1301	Heater current		---	---	I_f	275	325	mA
	1236	Heater-cathode leakage		---	---	I_{hk}	---	20	μAdc
	1356	Electrode current (2) (anode)	E_c = -24 Vdc	---	---	I_b	0	20	μAdc
	1406	Transconductance (2)	E_b = 90 Vdc; E_c = 0	---	---	g_m	2,400	3,000	μmhos
	1316	Amplification factor		---	---	μ_{gk}	18	22	---
D	1211	Insulation of electrodes		4.0	S2	---	---	---	---
D	1121	Metallic base sleeve quality		---	---	---	---	---	---
D	1126	Glass envelope strain		4.0	I	---	---	---	---
D	1101	Resonance of base, cap, or insert		---	---	---	---	---	---
D	1111	Base pin solder depth		---	---	---	---	---	---
D	1106	Permanence of marking		---	---	---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.

MIL-STD-750 METHOD	REQUIREMENT OR TEST	CONDITIONS	MIL SPECIFIED REJECTS	INSPECTION LEVEL OR CLASS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3							
---	Life-test provisions	Group A; Ebb = +300 Vdc	---	---	---	---	---	---
---	Life-test end point (500 hours)	Transconductance (1)	---	---	Sm	1,350	---	µmhos

NOTES:

1. Tube types 12J5 and 12J5WGT are hereby deleted from this tube specification sheet. For replacement purposes, use tube type 12J5GT in accordance with EIA release No. 168.
2. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.
3. The mount shall show no pronounced mechanical resonance below 100 Hz.
4. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 99

Review activities:
Army - EL, MU
Navy -
Air Force - 11, 17, 99
DSA - ES

User activities:
Army -
Navy - AS, CH, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2425-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.