MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6AQ6

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the electron tube described herein shall consist of this specification sheet and the latest issue of MIL-E-1.

DESCRIPTION: Triode, miniature, high-Mu, duplex diode

Outline --- 5-2 (EIA)

Base --- E7-1

Envelope --- T5-1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	g	k	h	h	2p (diodes)	1p	p (triode)

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec	E1b	E2b	I1b	I2b	Ehk	Alt
Unit:	V	V dc	V dc	V dc	V dc	mA dc	mA dc	v	ft
Maximum:	6.9	330	---	---	---	1.0	1.0	110	(see note 1)
Minimum:	5.7	---	---	---	---	---	---	---	
TEST CONDITIONS:	6.3	250	-3	0	0	---	---	---	---

GENERAL:

Qualification - Not required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:50Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1								
1266	Total grid current	2		0.65	II	Ic	0	-0.6	µA dc
1321	AC amplification		Ebb = 100 V dc; Esig = 0.2 V ac	0.65	II	Ep	7.5	---	V ac
1231	Emission (diode No. 1)		E1b = 10 V dc	0.65	II	I1s	0.8	---	mA dc
1231	Emission (diode No. 2)		E2b = 10 V dc	0.65	II	I2s	0.8	---	mA dc
1231	Emission (triode)	2	Eb = Ec = 30 V dc	0.65	II	Is	25	---	mA dc
1201	Short and discontinuity detection			0.4	II	---	---	---	---
	Quality conformance inspection, part 2								
1246	Audio frequency noise	3	Esig = 70 mV ac Rp = 0.2 Meg	4.0	I	---	---	---	---
1031	Low-frequency vibration		Rp = 10,000 ohms	6.5	S3	Ep	---	150	mV ac
1121	Base strain			6.5	S3	---	---	---	---
2126	Envelope strain			4.0	I	---	---	---	---
1301	Heater current			6.5	S3	If	138	162	mA
1336	Heater-cathode leakage			6.5	S3	Ihk	---	20	µA dc
1256	Electrode current (triode anode)			6.5	S3	Ib	0.5	1.8	mA dc
1306	Transconductance			6.5	S3	Sm	900	1,600	µmhos
1211	Insulation of electrodes			4.0	S3	R	10	---	Meg
1316	Amplification factor			6.5	S3	Mu	57	83	---
1105	Permanence of marking			---	---	---	---	---	---

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3						
1501	Intermittent life		Group A; Ehk = 100 V dc; I1b = I2b = 1.0 mA dc (min); Rg = 50,000 ohms (min)	---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:50Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3 - Continued						
---	Intermittent life-test end points (500 hours):						
1321	AC amplification		Ebb = 100 V dc; Esig = 0.2 V ac	Ep	6.0	---	V ac
1231	Emission (diode No. 1)		E1b = 10 V dc	I1S	0.3	---	mA dc
1231	Emission (diode No. 2)		E2b = 10 V dc	I2S	0.3	---	mA dc

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage in MIL-E-1.
2. This test shall be performed at the conclusion of the holding period.
3. The rejection level shall be set at the VU meter reading obtained during calibration.
4. Revision letters are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 99
DLA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5960-3338)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:50Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:50Z
Check the source to verify that this is the current version before use.