MIL-E-1/71E
27 September 1968
SUPERSEDING
MIL-E-1/71D
22 October 1964

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 26A7GT

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Twin beam power amplifier

Outline --- 9-33 or 9-44 (EIA) (E)

Base --- B8-6

Envelope --- T9

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8
Element	---	1g1	k, g3	2g1	2p	g2	h	h	1p

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ik	Pp	Pg2	(E) Ehk	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	mAdc	W	W	v	ft
Maximum:	29.1	55	---	55	125	2.2	0.55	100	10,000
Minimum:	23.9	---	---	---	---	---	---	---	---
TEST CONDITIONS:	26.5	26.5	-4.5	26.5	---	---	---	---	---

GENERAL:

Qualification - Required

(E) denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:52Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	See notes 1 and 5	0.65	II	Ic1	0	-2.0	µAdc
(E) 1231	Emission	Eb = Ec1 = Ec2 = 10 Vdc (see notes 2 and 4)	0.65	II	Ils	70	---	mAdc
(E) 1246	Audio frequency noise	Esig = 200 mVac; Rp = 500 ohms; Ec1 = -4.5 Vdc; R1g1+2g1 = 0.1 Meg (see notes 1 and 6)	0.65	II	---	---	---	---
1256	Electrode current (anode)	See note 2	0.65	II	Ib	12	28	mAdc
1341	Power output	Rp = 1,500 ohms; Esig = 3.2 Vac (see note 2)	0.65	II	Po	140	---	mW
1201	Short and discontinuity detection	See note 3	0.4	II	---	---	---	---
---	Visual and mechanical inspection criteria		---	---	---	---	---	---
(E) ---	Dimensions	Outlines 9-33 or 9-44; dimensions A thru D	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
(E) 1211	Insulation of electrodes		6.5	S3	---	---	---	---
1031	Low-frequency vibration	Rp = 2,000 ohms; Ec1 = -7 Vdc (see note 1)	6.5	S3	Ep	---	1,000	mVac
1256	Electrode current (screen grid)	See note 2	6.5	S3	Ic2	---	4.0	mAdc
1301	Heater current		6.5	S3	If	500	650	mAdc
1306	Transconductance	See note 2	6.5	S3	Sm	4,500	7,500	µmhos
1336	Heater-cathode leakage		6.5	S3	Ihk	---	100	µAdc
1111	Base pin solder depth	See note 5	6.5	S3	---	---	---	---
1101	Secureness of base, cap, or insert		6.5	S3	---	---	---	---
(E) 1105	Permanence of marking		---	---	---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:52Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						MIN	MAX	
	Quality conformance inspection, part 3							
1501	Life-test provisions (intermittent)	Group A; Eb = Ec2 = 50 Vdc; Ec = -9 Vdc; Ehk = 100 V; Rg1 = 0.1 Meg (min) per grid	---	---	---	---	---	---
---	Life-test end point (intermittent) (500 hours)	Power output	---	---	Po	100	---	mW

NOTES:

1. Test units in parallel.
2. Test each unit separately. Apply a bias of -25 volts to unit not under test.
3. (E) Test equipment shall be ac operated, and shall be capable of indicating tap shorts of 50,000 ohms, or less.
4. This test to be performed at the conclusion of the holding period.
5. This test applies to flexible leads as well as rigid leads.
6. The rejection level shall be set at the VU meter reading obtained during calibration.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2289-21)

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:52Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:52Z
Check the source to verify that this is the current version before use.