MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5676

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Triode, subminiature, rf oscillator

(B) Outline --- 2-1 (EIA)

Base --- Pinch press

Envelope --- T2X3

Cathode --- Coated filament

Base connections:

Pin No.	---	1	2	3	4
Element	---	a red dot	-f	g	+f

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ik	(B) Alt
Unit:	Vdc	Vdc	Vdc	mAdc	ft
Maximum:	1.50	150	---	11	See note 3
Minimum:	1.00	---	---	---	---
TEST CONDITIONS:	1.25	135	-5.0	---	---

GENERAL:

Qualification - Required

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:53Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Qualification inspection							
1202	Filament burnout		---	---	---	---	---	---
	Quality conformance inspection, part 1							
1266	Total grid current	See note 1	0.65	II	Ic1	0	-0.5	μAdc
1256	Electrode current (anode)		0.65	II	Ib	3.0	5.0	mAdc
1306	Transconductance (2)	Ef = 1.0 V (see note 1)	0.65	II	Sm	1,200	2,000	μmhos
(B) 1201	Tap shorts		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
(B) 1116	Lead fatigue		4.0	S3	---	---	---	---
1301	Filament current		---	---	If	106	134	mAdc
1316	Amplification factor		---	---	Mu	12.75	17.5	---
1331	Direct-interelectrode capacitance	See note 2	---	---	Cgp	1.0	1.6	pF
					Cin	1.0	1.7	pF
					Cout	2.5	4.0	pF
1306	Transconductance (1)		---	---	Sm	1,300	2,000	μmhos
(B) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
---	Life-test provisions	Group A; Rg = 0.010 Meg (min); Ef = 1.25 Vdc or Vac with equivalent bias	---	---	---	---	---	---
---	Life-test end point (100 hours)	Transconductance (1)	---	---	Sm	950	---	μmhos

NOTES:

1. This test to be performed at the conclusion of the holding period.
2. Close fitting shield connected to negative filament.
3. Altitude test not required as operating voltage is less than 280 volts. Requirements covering altitude vs. voltage breakdown relationship are specified in basic document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:53Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL
Navy -
Air Force - 80
DSA - ES

User activities:
Army - MU, WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Army - EL

Agent: DSA - ES

(Project 5960-2401-58)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:53Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:53Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL-TD-SS
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:53Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-E-1/79B, ELECTRON TUBE, RECEIVING TYPE 5676

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:53Z
Check the source to verify that this is the current version before use.