INCH-POUND
MIL-PRF-1/126F
14 March 2013
SUPERSEDING
MIL-PRF-1/126E
24 April 2007

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPES 6V6 AND 6V6GT 1/ 2/
a b

Inactive for new design
after 7 March 1997.

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described
herein shall consist of this specification sheet and MIL-PRF-1.

DESCRIPTION: Beam power pentode

Outline	a	- - -	8-6 (EIA).
Outline	b	- - -	9-11 or 9-41 (EIA).
Base	a	- - -	B7-22 (phenolic).
Base	b	- - -	Phenolic (see note 1).
Envelope	a	- - -	MT8.
Envelope	b	- - -	T9.

Cathode a, b - - - Coated unipotential.

Base connections:

Pin No.		- - -	1	2	3	4	5	7	8
Element	a	- - -	sh	h	a	g2	g1	h	k, g3
Element	b	- - -	nc or no pin	h	a	g2	g1	h	k, g3

ABSOLUTE RATINGS:

Parameter:		Ef	Eb	Ec1	Ec2	Ik	Pp	Pg2	Ehk	Alt
Unit:		V	V dc	V dc	V dc	mA dc	W	W	v	ft
Maximum:	a, b	6.9	350	- - -	310	65	13.2	2.2	100	10,000
Minimum:	a, b	5.7	- - -	- - -	- - -	- - -	- - -	- - -	- - -	- - -
Test conditions:	a, b	6.3	250	-12.5	250	- - -	- - -	- - -	- - -	- - -

GENERAL:

Qualification - Not required.

This specification sheet uses accept on zero defect sampling in accordance with MIL-PRF-1, table III.

1/ To identify those tests that are applicable to a given type or to several types; tube types are designated by letters.

2/ Formerly tube types 6V6Y and 6V6GTY.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements and tests.

MIL-STD-1311 method	Requirement or test	Type	Conditions	Symbol	Limits		Unit
					Min	Max	
	Conformance inspection, part 1						
1266	Total grid current	a, b	See note 2	Ic1	0	-2.0	μA dc
1256	Electrode current (anode)	a, b		Ib	33	57	mA dc
1256	Electrode current (screen grid)	a, b		Ic2	0	7.5	mA dc
1341	Power output	a, b	Class A amplifier; Esig = 8.8 V ac; Rp = 5,000 ohms	Po	3.6	- - -	W
1246	Audio frequency noise	a, b	Esig = 280 mV ac; Rp = 2,000 ohms, (see note 3)	EB	- - -	- - -	VU
1231	Emission	a, b	Eb = Ec2 = Ec1 = 30 V dc (see note 2)	Is	100	- - -	mA dc
1201	Shorts and discontinuity detection	a, b		- - -	- - -	- - -	- - -
	Conformance inspection, part 2						
1031	Low-frequency vibration	a, b	Ec1 = -25 V dc; Rp = 2,000 ohms	Ep	- - -	500	mV ac
1301	Heater current	a, b		If	410	490	mA
1336	Heater-cathode leakage	a, b		Ihk	- - -	50	μA dc
1306	Transconductance	a, b		Sm	3,000	5,200	μmhos
1331	Direct-interelectrode capacitance	a b	No shield Shield No. 308	Cgp Cin Cout	- - - 7.9 5.6	0.9 11.1 13.5	pF pF pF
1101	Secureness of base wafer insert	a		- - -	- - -	- - -	- - -
1101	Secureness of base	b		- - -	- - -	- - -	- - -
1111	Base pin solder depth	a, b	See note 4.	- - -	- - -	- - -	- - -
1211	Insulation of electrodes	a, b		- - -	10	- - -	MegΩ
1105	Permanence of marking	a, b		- - -	- - -	- - -	- - -

See notes at the end of the table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements and tests - Continued.

MIL-STD-1311 method	Requirement or test	Type	Conditions	Symbol	Limits		Unit
					Min	Max	
	Conformance inspection, part 3						
1501	Intermittent life	a, b	Group A; Eb = Ec2 = 300 V dc; Ec1 = -20 V dc; Ehk = 100 V	- - -	- - -	- - -	- - -
- - -	Life-test end point (intermittent) (500 hours)	a, b	Power output	Po	2.3	- - -	W

NOTES:

1. The base shall be one of the following: B6-81, B6-84, B7-7, B7-59, or B8-251.
2. This test to be performed at the conclusion of the holding period.
3. The rejection level shall be set at the VU meter reading obtained during calibration.
4. This test applies for flexible leads as well as for rigid leads.

Referenced documents. In addition to MIL-PRF-1, this document references MIL-STD-1311.

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5960-2013-002)

Review activities:
Army - AR, AV, MI
Navy - AS, CG, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:57Z
Check the source to verify that this is the current version before use.