MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 1Z2

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Rectifier, half wave, high vacuum

Outline, Base, Envelope } See figure 1

Cathode --- Thoriated tungsten

Base connections:

Pin No. ---	1	2	3	4	5	6	7	Cap
Element ---	-f int sd	+f	-f int sd	-f int sd	+f	-f int sd	+f	a

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	epx	ib	Io	CL	Rl	Fl
Unit:	Vac	kv	ma	mAdc	μF	Meg	kHz
Maximum:	1.25 ± 5%	15	8.5	1.5	---	--- (see note 1)	200
Minimum:	---	---	---	---	---	---	---
TEST CONDITIONS:	1.25	15	---	1.5	0.01	4.2	---

GENERAL:

Qualification - Not required

© denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:48Z
Check the source to verify that this is the currentversion before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1353	Operation of rectifiers	Ef = 1.2 V; Zp rb = 8.5 ma (min) (see notes 2 and 3)	0.65	II	---	---	---	---
1231	Emission current	Ef = 1.35 V; Eb = 100 Vdc	0.65	II	Is	9.5	---	mAdc
	Quality conformance inspection, part 2							
1301	Filament current		---	---	If	245	285	mA
1031	Low-frequency vibration	No voltages	---	---	---	---	---	---
(C) 1101	Secureness of base, cap, or insert		---	---	---	---	---	---
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
(C) 1501	Intermittent life	Group A: 250 hours with Ef = 1.25 V, or 500 hours with Ef = 1.2 V; Zp rb = 8.5 ma	---	---	---	---	---	---
---	Intermittent life-test end point	Failure to rectify and emission	---	---	Is	8.5	---	mAdc

NOTES:

1. The supply source impedance shall be at least 300,000 ohms.
2. (C) The tube shall be operated in a half-wave rectifier circuit at 50 to 60 Hz. Apply heater and anode voltage simultaneously to cold tube. After cathode has reached operating temperature, key anode current three times, no arcing shall occur.
3. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - EL
Navy -
Air Force - 11, 85
DSA - ES


User activities:
Army - MU, ME, WC
Navy - AS, OS, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2401-19)

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:48Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
Quality conformance inspection, part 1		
A		.75 (19.05)
C		2.70 (68.58)
D	2.34 (59.44)	2.47 (62.74)
Quality conformance inspection, part 3 (periodic check)		
E	Cap: C1-3	
F	Base: E7-1	
G	Envelope: T5½	

FIGURE 1. Outline drawing of electron tube type 1Z2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:48Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:48Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-15T12:48Z
Check the source to verify that this is the current version before use.