MIL-E-1 95C
4 June 1970
SUPERSEDING
MIL-E-1/95B
12 June 1963

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5886

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, subminiature, filamentary electrometer

(C) Outline --- 2-1 (EIA)

Base --- Pinch press (5 leads)

Envelope --- T2X3

Cathode --- Coated filament

Base connections:

Pin No.	---	1	2	3	4	7
Element	---	a	g2	+f, 1g3	-f, 2g3	g1

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Ebb	Eb	Ec2	Ec1	Ik	Rl	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	Vdc	μAdc	Ohms	ft
Maximum:	1.5	---	22.5	22.5	---	300	---	10,000
Minimum:	1.0	---	---	---	---	---	---	---
TEST CONDITIONS:	1.25	22.5	---	---	-3.0	---	60,000 (triode connected)	---

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	See notes 1 and 2	0.65	II	Ic1	0	2.5×10^{-13}	Adc
---	Voltage gain	Esig = 0.2 Vac	0.65	II	Ep	0.24	---	Vac
1201	Short and discontinuity detection		0.4	II	---	---	---	---
1256	Electrode current (anode)		0.65	II	Ib	175	225	µAdc
	Quality conformance inspection, part 2							
1301	Filament current		---	---	If	8.8	11.2	mAdc
1306	Transconductance	Eb = 10.5 Vdc; Rl = 0	---	---	Sm	120	240	µmhos
1316	Amplification factor (triode)	Eb = 10.5 Vdc; Rl = 0	---	---	Mu	1.6	2.1	---
1331	Direct-interelectrode capacitance	No shield	---	---	Cg1-all	1.0	3.0	pF
(C) 1116	Lead fatigue		---	---	---	---	---	---
(C) 1211	Insulation of electrodes		---	---	---	---	---	---
(C) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
(C) ---	Life-test provisions	Group C; triode connected	---	---	---	---	---	---
---	Life-test end points (500 hours)	Voltage gain	---	---	Ep	0.22	---	Vac
		Total grid current	---	---	Ic1	---	5×10^{-13}	Adc
(C) ---	Life-test provisions	Group C; triode connected (see note 3)	---	---	---	---	---	---
---	Life-test end point (10,000 hours)	Voltage gain	---	---	Ep	0.22	---	Vac

NOTES:

1. Measurement shall be made with tube in an electrostatically shielded, light-tight container. One hour preheating is permitted prior to testing.
2. This test to be performed at the conclusion of the holding period.
3. During months in which there is production, the manufacturer shall conduct one test per month on at least five tubes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL, MU
Navy -
Air Force - 11, 85
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2401-76)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T12:54Z
Check the source to verify that this is the current version before use.