INCH-POUND

MIL-B-23964D
AMENDMENT 3
22 February 1995
SUPERSEDING
AMENDMENT 2
4 March 1993

MILITARY SPECIFICATION

BOLT, SELF-RETAINING, POSITIVE LOCKING

This amendment forms a part of MIL-B-23964D, dated 10 August 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Beneficial comments block: Delete "Naval Air Engineering Center, SESD (Code 53)" and substitute "Naval Air Warfare Center Aircraft Division Lakehurst, Systems Requirements Department, Code SR3."

PAGE 8

TABLE II: Delete locking balls push-out force column and substitute:

Locking Balls Push-out Force (lb. min)
10
20
20
20
40
60
60
80
80
80
80

PAGE 12

Delete paragraph 3.6.2 and substitute the following:

"3.6.2 Stress durability (class 3). Bolts shall withstand the specified load for the specified time without failing or developing cracks (see 4.5.22)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

PAGE 12

Add new paragraph 3.6.10:

3.6.10 Stress corrosion (class 1 only). Bolts shall withstand the various stress corrosion conditions without cracking (see 4.5.24).

PAGE 13

"TABLE V: Change "Stress durability (except Class 4)" to "Stress durability (Class 3)"

ADD: "Stress Corrosion (Class 1)"

PAGE 14

"TABLE VI: Change "Stress durability (except Class 4)" to "Stress durability (Class 3)"

ADD: "Stress Corrosion (Class 1)"

"TABLE VI: Delete "100%" from the Sampling plan column, for Locking ball push-out force, and substitute "R".

PAGE 16

4.4.2.1: Delete in its entirety and substitute:

"A production lot shall consist of finished bolts that are of the same head configuration, shank diameter, grip length, thread size, material, heat treatment by the same method in one continuous run and submitted to inspection at the same time."

4.5.3 Delete in its entirety and substitute:

"Each bolt shall be 100 percent functionally checked from both the unlocked and locked positions to determine if the operation is correct, without the loss of any element. Each bolt shall be 100 percent inspected for presence and containment of the locking elements and retention devices."

4.5.5: Add as last sentences:

"The sample shall be 10 percent of the lot size, minimum of 5 bolts with a maximum of 15 bolts. There shall be no failures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

Add new paragraph 4.5.24:

"4.5.24 Stress corrosion. The stress corrosion test shall be conducted on a minimum of one sample per lot using the procedure called out in accordance with MIL-TD-1312, Test 9. The induced load shall be 75 percent of the tested ultimate tensile strength of the bolts. Free running, cadmium plated MS21133 or equivalent nuts shall be used with self-retaining bolts for this test. The bolts shall be in the stressed condition for 72 hours. The test shall be continued an additional day for each day that the examination was not performed. Nuts required for this test shall be new and shall not be used more thanonce in the performance of this test.

Add as new paragraph 6.2.2:

"6.2.2 Inventory. Inventory produced before 1 January 1991 may be used until stock is exhausted."

NOTE: The margins of this amendment are marked with vertical lines to indicate where changes (additions, modifications, and corrections) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Navy - AS
Air Force - 99

Preparing activity:
DLA-IS

(Project No. 5306-1820)

Review activity:
Air Force - 82

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.