MILITARY SPECIFICATION

COMPRESSORS , HIGH PRESSURE AIR, 100 C. F. M. ,

NAVAL SHIPBOARD SERVICE

This amendment forms a part of Military Specification MIL-C-23961A(SHIPS), 23 December 1965.

Pages 1 and 2, paragraph 2. 1: Under “SPECIFICATIONS MILITARY add:

"MIL-A-22895 - Adhesive, Metal Identification Plate”.

Page 3, paragraph 3.2. 1, line 5: Delete "inspection" and substitute "injection".

Page 3, paragraph 3.3.2, second sentence Delete and substitute: "If vee - belt drive is provided, static free belts, protective guards and means for adjusting belt tension shall also be provided."

Page 3, paragraph 3.3.3, line 2: After “pressure switch” insert", air filter”.

Page 4, paragraph 3.4.5.1: line 2: Delete "class HI” and substitute “class I", third sentence; Delete,

Page 5, paragraph 3.4. 13.1, line 2: Delete "MIL-S-17331" and substitute "MIL-B-17931".

Page 5, paragraph 3.4. 14. 1, line 3: Delete "MIL-L-17731" and substitute "MIL-L- 17331"'

Page 6, paragraph 3.4. 14. 5, second sentence: Delete and substitute. "If driven by a separate motor, the motor shall be electrically interlocked with the compressor motor to assure that it operating whenever and for as long as the compressor motor is energized “

Page 6, paragraph 3.4. 16, third and fourth sentences: Delete and substitute: “Access openings with covers shall be provided for observation and adjustment of the bearings . A crankcase vent shall be provided, which shall be piped through an efficient oil separator, to the compressor suction. “

Page 7, Paragraph 3.4.18.2, line 6: Delete "10 seconds" and substitute “60 seconds ", to last sentence add: "directly in the cooling water flow path”.

Page 7, paragraph 3.4. 18, 5, last two sentence Delete and substitute: “Suitable water relief valves or rupture discs shall be fitted on the water side

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:30Z
Check the source to verify that this is the current version before use.

of each air cooler except for first and second stage coolers, Water relief valves shall be set at 185 p.s, i, (see 3,4.23), Rupture discs shall rupture at a higher pressure, not to exceed 265 p.s. i, “

Page 7, paragraph 3, 4, 19, 1: Delete and substitute:

“3, 4, 19, 1 A moisture separator shall be provided after each intercooler and after cooler for removing free moisture and oil from the air. The manufacturer s separator design calculations shall be submitted to the Naval Ship Engineering Center (NAVSEC) for design review and approval. The storage capacity of each separator s'nail be sized to require drainage not oftener than every 30 minutes when intake air is at 122° F. and 50 percent relative humidity - ity' and cooling water is at any temperature in the range of 28” F, through 85°F.''

Page 8, paragraph 3,4.21, 1, 1, line 2: Between “the” and "pressure" insert “inlet and outlet”; to last sentence add: “before and after the oil filter”.

Page 8, paragraph 3.4,21.3, last line: Delete "on" and substitute "from".

Page 9, paragraph 3.4.23: Add "If rupture discs are used in lieu of water relief valves, the discs shall be provided with means for discharging water and air downward. "

Page 10, paragraph 3.4, 29, 1: Delete and substitute:

“3.4 .29.1 Identification plates shall be type A, D or H in accordance with MIL-P - 15024, except that plates of plastic material are not acceptable and type H plates shall be of aluminum only. The plates shall be secured either by corrosion resistant metallic fasteners or by an adhesive, such as that speci- - fied in MIL-A-22895. “

Page 12, paragraph 3, 6.2.2.2: Add "Two pressure sw'itches may be used to perform this function, "

Page 13, table II: Add “Valves, lubricator check, sets" and indicate quantity “1 “ in each column.

Page 14, paragraph 3.8.2.3, line 2: Delete “may be submitted to” and Substitute "shall be submitted to and approved by”.

Page 21, paragraph 4.4.3.7, second sentence: Delete,

Page 22, paragraph 4.4.4, line 2: Delete "class III and substitute "class I", second sentence: Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:30Z
Check the source to verify that this is the current version before use.

Throughout the specification: -Delete “Bureau of Ships” and substitute "Naval Ship Engineering Center”.

Preparing activity:
Navy - SH
(Project 4310-N045SH)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:30Z
Check the source to verify that this is the current version before use.