INCH-POUND

MIL-DTL-23971/5C
14 May 2007
SUPERSEDING
MIL-DTL-23971/5B
23 April 2002

DETAIL SPECIFICATION SHEET

POWER DIVIDERS, N-WAY, O DEGREES, FLAT PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the power divider described herein shall consist of this specification sheet and MIL-DTL-23971.



	Dimensions			
	Inches		Millimeters	
	Max	Min	Max	Min
A	N/A	.313	N/A	7.95
B	.41	.35	10.4	8.9
C	.019 dia	.015 dia	0.48 dia	0.38 dia
D	.11	.05	2.8	1.3
E	.11	.09	2.8	2.3
F	.26	.24.	6.6	6.1
G	.36	.34	9.1	8.6
H	.53	.47	13.5	11.9
J	.072	.052	1.83	1.32
K	.125	N/A	3.18	N/A

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Pins that are marked are grounded to the internal circuit of the power divider by the manufacturer.

FIGURE 1. Dimensions and configuration, 2-way, dash numbers 01 and 03.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:34Z
Check the source to verify that this is the current version before use.



	Dimensions			
	Inches		Millimeters	
	Max	Min	Max	Min
A	N/A	.313	N/A	7.95
B	.41	.35	10.4	8.9
C	.019 dia	.015 dia	0.48 dia	0.38 dia
D	.11	.05	2.8	1.3
E	.119	.099	3.02	2.51
H	.53	.47	13.5	11.9
J	.072	.052	1.83	1.32
K	.125	N/A	3.18	N/A

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Pins that are marked are grounded to the internal circuit of the power divider by the manufacturer.

FIGURE 1. Dimensions and configuration 3-way, dash number 02.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:34Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical performance characteristics and physical requirements.

M23971 /5-	Imped-ance (ohms)	Frequency range (MHz)	Average coupling (dB)	VSWR max	Insertion loss max (dB)	Isolation min (dB)	Phase balance max (degree)	Amplitude balance (dB) max	Power level		Weight pounds (grams)	Ambient temperature		Figure
									avg (W)	pk (W)		Operating	Storage	
01	50	5-25	3. +.2, -.0	1.3:1	0.3	25	±1.0	±0.1	0.5	1.0	.006 (2.83)	-35° to +105°C	-40° to +125°C	1
02	50	0.2-200	4.8 +.5 -0.0	1.3:1	0.5	25	±2.0	±0.2	0.5	.5	.006 (2.83)	-55° to +125°C	-55° to +125°C	2
03	50	10-500	3. +.2 -0.0	1.3:1	0.5	30	±1.0	±0.1	1.0	N/A	.006 (2.83)	-55° to +85°C	-55° to +85°C	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:34Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction: See figures 1 and 2.

Case: Hermetically sealed.

Material: Cold rolled steel or iron nickel alloy in accordance with SAE-AMS-I-23011, class I (KOVAR).

Finish: Gold electroplated per SAE-AMS-2422 or ASTM-B488, type III, class 2, over nickel strike .00002-.00005 thick.

Cover: Cold rolled steel or iron nickel alloy in accordance with SAE-AMS-I-23011, class I (KOVAR).

Finish: Electroless nickel per SAE-AMS-C-26074, class I, 0.00012 inch thick.

Terminals: Iron nickel alloy in accordance with SAE-AMS-I-23011, class I (KOVAR). Gold-plated in accordance with SAE-AMS-2422 or ASTM-B488, type III, class 2, over nickel strike .00002-.00005 thick.

Nickel is to be used in this component only if specification cannot be met using alternate material means.

Electrical characteristics: See table I.

Weight: See table I.

Ambient temperature: See table I.

Environmental tests: In accordance with MIL-DTL-23971 except:

Dash No. 01:
Barometric pressure: Not applicable.
Thermal shock: In accordance with method 107 of MIL-STD-202, test condition A (but using upper temperature limit +125°C and lower temperature limit -40°C).
Vibration: In accordance with method 204 of MIL-STD-202, test condition D.
Shock: In accordance with method 213 of MIL-STD-202, test condition I.
Salt spray: Not applicable.

Resistance to soldering heat: +600°F for 10 seconds.

Part number: M23971/5- (dash number from table I).

Referenced documents. In addition to MIL-DTL-23971, this specification sheet references the following:
SAE-AMS-I-23011 SAE-AMS-2422 SAE-AMS-C-26074 ASTM-B488 MIL-STD-202

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-2007-011)

Review activities:
Navy - AS, MC, OS
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:34Z
Check the source to verify that this is the current version before use.