MIL-I-23970A(SHIPS)
15 May 1964
SUPERSEDING
MIL-I-23970(SHIPS)
10 January 1964
(See 6.4)

MILITARY SPECIFICATION

INDICATOR, OWN SHIP'S POSITION

(NAVAL SHIPBOARD)

1. SCOPE

1.1 Scope.- This specification covers the design of an own ship's position indicator for use in Naval ships for remote indication of own ship's geographic position.

1.2 Classification.- Own ship's position indicator shall be of the following types, as specified (see 6.2):

Type I - An indicator which is capable of receiving a three speed (1X, 36X, 360X) own ship's position signal from two sources (primary and secondary).

Type II - An indicator which is capable of receiving a single source of two speed (1X, 36X) position signal.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-25 - Capacitors, Fixed, Paper-Dielectric, Direct Current, (Hermetically Sealed in Metallic Cases), General Specification for.
MIL-S-901 - Shock Tests, H. I. (High-Impact); Shipboard Machinery, Equipment and Systems, Requirements for.
MIL-I-983 - Interior Communication Equipment, Naval Shipboard; Basic Design, Requirements for.
MIL-Q-9858 - Quality Program Requirements.
MIL-E-17555 - Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of.
MIL-S-20708 - Synchros, 60 and 400 Cycle; General Specification.
MIL-S-22432 - Servo Motor; General Specification.

STANDARDS

MILITARY

MIL-STD-701 - Preferred and Guidance Lists of Semiconductor Devices.

DRAWINGS

BUREAU OF SHIPS

815-1853017 - Transistorized Amplifier.
9000-S6504-F-73687 - Standard Dial Markings for Interior Communication Order and Indicating Systems.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 6320

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OFFICIAL CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.

(Application for copies should be addressed to the Official Classification Committee, 1 Park Avenue at 33rd Street, New York 16, N.Y.)

AMERICAN GEAR MANUFACTURERS ASSOCIATION (AGMA)
Standard 236 - Inspection of Fine-Pitch Gears (ASA B6.11-1956).

(Application for copies should be addressed to the American Gear Manufacturers Association, #1 Thomas Circle, N.W., Washington 5, D.C.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Preproduction sample.- Prior to beginning production a sample shall be tested as specified in 4.3 (see 6.3).

3.2 Description.- The own ship's position indicator shall be a bulkhead mounted assembly which presents a continuous visual display of own ship's geographic position in latitude and longitude. A selector switch provides for a choice of input signal sources (primary or secondary) as specified in table I. The latitude and longitude indicators shall be capable of indicating all possible own ship's geographic positions.

Table I - Input signals.

Indicator	Type I	Type II
Latitude	18CX4 - 1X, 36X, 360X	18CX4 - 1X, 36X
Longitude	18CX4 - 1X, 36X, 360X	18CX4 - 1X, 36X

NOTES:

1. 1X indicates that one revolution of the synchro shaft equals 360 degrees of latitude or longitude.
2. 36X indicates that thirty-six revolution of the synchro shaft equals 360 degrees of latitude or longitude (one revolution equals 10 degrees of latitude or longitude).
3. 360X indicates that 360 revolutions of the synchro shaft equals 360 degrees of latitude or longitude (one revolution equals one degree of latitude or longitude).

3.3 General features.- The equipment shall be in accordance with the following paragraphs of MIL-I-983 in addition to the requirements specified herein. (Whenever a requirement of MIL-I-983 conflicts with a requirement of this specification, the requirement of this specification shall govern):

General requirements
Definitions
Materials, general
Substitution of (equal or superior) materials or parts
Fungus-inert materials
Flammable materials
Arc-resistant materials
Toxic materials
Wood
Metals
Plastics
Ceramics
Impregnating, embedding and encapsulating compounds
Glass

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

Lubricants and lubrication
Painting
Protection against corrosion
Bolts, machine screws, studs and nuts
Gaskets
Dials and pointers
Dial sizes
Locking devices
Washers
Ball bearings (precision grade required) (see 3.4.2)
Parts - electrical - general
Requirements for semiconductor devices (see 3.4.11)
Transients
Capacitors
Variable resistors
Transformers
Relays
Synchros
Electrical tapes
Batteries
Dial illumination lamps
Switches
Indicator lights and lampholders
Fuses
Fuseholders and fuse clips
Metallic rectifiers
Printed wiring and circuits
Enclosures - general
Enclosure - accessibility (see 3.5.2)
Enclosure - degree of (dripproof) (see 3.5.1)
Enclosure - mounting
Stiffening grooves
Minimum sheet metal thicknesses (watertight enclosures)
Through bolting
Cable entrance
Ventilation
Size (for submarines)
Threaded devices
Rounded corners and edges
Internal subassembly protection (see 3.5.2)
Drilled and tapped holes
Welding
Temperature and humidity
Accelerated life
Shock (see 3.4.13), vibration (vital vibration test required), and inclination (inclination test is not required)
Primary power supply circuits
Power supply tolerances
Personnel protection
Shielding and radio frequency noise reduction
Ground potential and grounding
Soldering
Electrical parts mounting
Internal subassembly connection
Terminal boards, connectors and terminals
Wiring
Dial illumination
Electrical insulation
Dielectric strength and insulation resistance clearances
Airborne noise
Structureborne noise
Drawings - general

Source: https://assist.dla.mil -- Downloaded: 202640-19T18:31Z
Check the source to verify that this is the current version before use.

Drawings - preliminary
Drawings - working
Schematic diagrams
Wiring diagram
Drawing list
Assembly drawings
Drawings - manufacturing
Bill of materials
Interchangeability and standardization (see 3.4.6)
Manuals
Repair parts
Repair parts (electronic)
Designation and marking (serial numbers are required)
Reports
Nomenclature
Workmanship and general examination

3.4 Design.- The equipment shall be so designed that vibration, shock, or acceleration, which may be encountered in service aboard any of the types of ships for which the equipment is intended, will not adversely affect the accuracy of the equipment under normal conditions, nor, under extreme conditions, derange any part of the equipment beyond normal adjustment at sea. The equipment shall be so designed that the operator will not receive an electric shock when making any ordinary adjustment while the equipment is in operation.

3.4.1 Excessive play between moving parts, resulting in noise when the equipment is subjected to vibration, shall be eliminated insofar as practicable.

3.4.2 Resolvers, friction disks, lead screws, rollers and other mechanical components shall be of a suitable material, properly and evenly hardened or treated to prevent wear. They shall, wherever practicable, be provided with oil-saturated felt wipers for lubrication.

3.4.3 Viewing windows, where required, shall be so mounted as to minimize danger of breakage or cracking due to stress at the edges.

3.4.4 Protective devices.- Protective devices such as mechanical stops, clutches, limit switches or similar devices shall be provided where necessary to prevent damage or operational malfunctions if the equipment is permitted to exceed the maximum ranges of any parameters.

3.4.5 Parts of the equipment requiring accurate placing shall be marked or doweled, so that when disassembled for repairs or adjustments, the parts can be replaced in their proper position. Parts requiring occasional renewal due to unavoidable service wear, shall be designed for maximum practicable ease of replacement and alignment.

3.4.6 Interchangeability.- Except as specifically provided herein, similar parts and component assemblies, including repair parts or corresponding apparatus furnished on the same contract or order shall be interchangeable without the necessity of further machining or hand fitting of any kind.

3.4.7 Proposed changes in approved design affecting parts or assemblies, including repair parts, shall be specifically approved as satisfactory to the bureau or agency concerned before being made effective.

3.4.8 Mercury and radium in any form, shall not be used in this equipment or in its manufacture or testing.

3.4.9 All cable shields shall be tied to a common point and grounded at that point within the equipment.

3.4.10 Gears.- Gears used in critical backlash applications shall be precision 1C or better as defined by Publication AGMA 236, and of a material satisfactory to the bureau or agency concerned. Corrosion resisting steel gears may be used where this material will provide superior performance. Low torque, high precisions gears shall not be lubricated unless they are fully sealed in an enclosure.

3.4.11 Semiconductor devices.- Semiconductor devices shall be selected from MIL-STD-701. The supplier shall submit a tentative semiconductor complement report to the bureau or agency concerned as soon as the equipment design requirements have been determined. In the event a change in the complement of

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

semiconductor is found necessary, it shall be reported within 30 days. In order to assure sufficient quantity for maintenance of equipment in the Naval service, the supplier shall furnish the bureau or agency with a final semiconductor complement report after the equipment design has been completed and before production has begun. These reports shall be submitted on the same form DD 816 as used for electron tubes, and shall be combined into a consolidated form for each equipment (these forms may be obtained upon application to the Government inspector).

3.4.12 Accuracies.- The error of the equipment shall not exceed the values shown below under all test conditions specified in 4.6:

	Type I	Type II
(a) Latitude	±0.1 minute	±0.5 minute
(b) Longitude	±0.1 minute	±0.5 minute

The error shall be determined by comparison of the input signal and the indicated value on the own ship's position indicator.

3.4.13 Shock.- The equipment shall conform to the High Impact (HI) shock requirements of MIL-S-901 for grade A equipment.

3.5 Mechanical features.-

3.5.1 Enclosure.- All parts required for the proper operation of the equipment shall be mounted in an enclosing case (degree of enclosure dripproof). Provision shall be made for the protection of moving parts from dust. Mounting and external wiring of the equipment shall be accomplished without removal of components from the enclosure and without exposing the gear to dust. Internal subassemblies shall not be supported by the enclosure. The enclosure shall be designed for mounting on a bulkhead.

3.5.2 Accessibility.- All units and subassemblies of the equipment shall be easily accessible for repair and adjustment and shall not require removal of components or modules, or require the use of extension cables to accomplish calibration or adjustments. Protection of the internal subassemblies shall be provided in accordance with MIL-I-983. Suitable supports shall be furnished where necessary to allow repair work without the units resting on electrical components, electrical connections or on components that may be disarranged or otherwise damaged. Knurled knob captive screws with a screwdrive slot shall be used on all covers that require removal or opening for operating adjustments.

3.5.3 Controls and indicators.- The following operating controls and indicators shall be provided:

(a) Illumination power and intensity control (see 3.6.7).
(b) Input source selector and master power switch (see 3.6.8).
(c) Latitude indicator (see 3.6.9).
(d) Longitude indicator (see 3.6.10).

3.5.4 Lettering and marking.- The size and characteristics of lettering and markings for all dials and indicators shall be in accordance with drawing 9000-S6504-F-73687.

3.5.5 Weight and size.- The size of the equipment shall not exceed 12 inches high by 12 inches deep by 20 inches wide and shall not weigh more than 50 pounds. The weight and size shall, however, be held to a minimum.

3.6 Electrical features.-

3.6.1 Servo amplifiers.- The servo amplifiers shall operate on 400 cycle synchro signals, shall be transistorized (see drawing 815-1853017 or equivalent), and shall consist of the necessary items arranged on a removable chassis. The total power taken from each amplifier shall not exceed 10 watts. The amplifier chassis shall be grounded to the case, and a B minus bus isolation from the chassis shall be provided for the servo amplifiers, which shall be positively connected (bonded) to the case of the equipment at one physical point only. Matching transformers shall be used between amplifier output and servo motor control field if the servo motor is not directly matched to the amplifier during manufacture. The servo motor shall not be modified to match the impedance of the amplifier. All servo trimming circuit shall be external to the amplifier package. Servo amplifiers shall have adjustable gain controls capable of adjusting the gain over a plus or minus 6 decibel (db) range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

3.6.2 Servo motors.- The servo motors shall be in accordance with the requirements of MIL-S-22432 including high impact shock and audible structureborne noise. Motors shall be equipped with sealed for life bearings.

3.6.3 Synchro capacitors.- The correct synchro capacitors shall be provided for all synchro control transformers to maintain unity power factor. These capacitors shall be mounted as close to the control transformers as possible. The capacitor section shall be rated for 600 volts or greater and shall be in accordance with MIL-C-25 for 60 cycle application. For 400 cycle applications, capacitors shall be rated for 1000 volts. Each synchro capacitor shall have the capacitance of its three capacitor sections balanced within 1 percent, as measured by the divergence of the capacitance of any one leg from the arithmetical mean of the three.

3.6.4 Effect of synchro bus load on synchro control transformers.- In order to prevent excessive reflected errors on the synchro bus, the secondary load on the synchro control transformers used in this equipment shall be greater than 15,000 ohms.

3.6.5 Power supply.- The equipment shall operate from a power supply of three phase, 400 cycle, 115-volt, alternating current (a.c.). Sixty cycle, 115-volt a.c. shall be accepted as an input to the equipment and for illumination.

3.6.6 Blown fuse indicators.- Blown fuse indicators shall be located on the left side of the equipment front panel to indicate loss of power supply and loss of excitation to each of the important circuits.

3.6.7 Illumination control.- All indicators shall be illuminated in red only and shall be controlled by a single rheostat or other device as specified for dial illumination lamps in MIL-I-983, except that the device shall also serve as an "ON-OFF" switch. The dial illumination requirements of MIL-I-983 do not apply.

3.6.8 Input source selector.- The input source selector switch shall be a single three position "on-off-on" switch capable of selecting either the primary input signals for both indicators or the secondary input signals or no input signals.

3.6.9 Latitude indicator.- The latitude indicator shall present the ship's latitude position in degrees and minutes corresponding to the selected input signal (see table I). Selection of the input signal shall be made by the input source selector switch (see 3.6.8). The indicator shall be a 4-drum counter presentation capable of indicating latitude from 00 degrees 00 minutes to 90 degrees 00 minutes. The counter shall be equipped with an indicator to show correct hemisphere by the letters "N" and "S" as appropriate and with automatic reversing devices so that the latitude counters reverse when the ship crosses the equator. The minute unit drum shall be marked along the right side edge in .1 minute increments and numerals to indicate every minute. The .5 minute increment shall be emphasized. The unilluminated counter shall appear as white on black and under illumination shall appear as red or white on black. Numerals and letters shall not be less than 1/4 inch high. The indicator shall have a minimum setting rate of 10 degrees of latitude (or longitude) per minute.

3.6.9.1 The type I latitude indicator shall be designed to receive a three speed (1X, 36X and 360X) 120 volt, 400 cycle signal. The type II latitude indicator shall be designed to receive a two speed (1X and 36X) 120 volt, 400 cycle signal.

3.6.10 Longitude indicator.- The longitude indicator shall present the ship's longitude position in degrees and minutes corresponding to the selected input signal (see table I). Selection of the input signal shall be made by the input source selector switch (see 3.6.8). The indicator shall be a 5-drum counter presentation capable of indicating 000 degrees 00 minutes to 180 degrees 00 minutes. The counter shall be equipped with an indicator to show correct hemisphere by the letters "E" and "W" as appropriate and with reversing devices so that the longitude counters reverse when the ship crosses the prime meridian and the 180th meridian. Illumination, dial marking and minimum setting speed shall be the same as required for the latitude indicator.

3.6.10.1 The type I longitude indicator shall be designed to receive a three speed (1X, 36X and 360X) 120 volt, 400 cycle signal. The type II longitude indicator shall be designed to receive a two speed (1X and 36X) 120 volt, 400 cycle signal.

3.6.11 All signals shall be received on size 11CT4 synchro control transformers. All synchros shall comply with MIL-S-20708.

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:31Z
Check the source to verify that this is the current version before use.

3.6.12 Input signal isolation.- The excitation power for the latitude-longitude and the speed inputs shall be isolated from each other to allow operation of the equipment when inputs are on different phases of 3 phase power or are provided from different sources of 400 cycle power.

3.7 Combined panel arrangement.- Approval of the internal arrangements of the panel shall be considered as a part of drawing approval.

3.8 Federal stock number.- Federal stock numbers for the equipment will be furnished to the supplier, by the bureau or agency concerned, 45 days after the time of approval of the working drawings, and upon the written request of the supplier. Federal stock numbers shall be applied to the identification plates of the equipment prior to shipment by the supplier.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality control system.- The supplier shall provide and maintain a quality control system acceptable to the Government. The system of quality control shall be in accordance with MIL-Q-9858. The supplier is in no way relieved of the final responsibility to furnish indicators meeting the requirements of this specification.

4.2 General inspection.- The procedures for the various tests to be performed on the equipment shall be as specified hereinafter.

4.3 Preproduction inspection.- One sample of the indicators shall be subjected to the examination and tests shown in table II. Tests shall be performed in general in the order listed.

Table II - Preproduction inspection.

Examination and tests	Requirement paragraph	Test reference
General examination	3.3	4.5
Operating and setting rate	3.6.9	4.6.1
Shielding and radio frequency noise reduction	3.3	MIL-I-983
Airborne noise	3.3	MIL-I-983
Structureborne noise	3.3	MIL-I-983
Enclosure	3.3 and 3.5.1	MIL-I-983
Illumination	3.6.7	4.6.2
Accuracy	3.4.12	4.6.3
Transients	3.3	MIL-I-983
Accelerated life (Includes tests for supply line voltage, accuracy, temperature and humidity, dielectric strength, insulation, resistance, shock and vibration)	3.3	4.6.4 and MIL-I-983

4.4 Quality conformance inspection.-

4.4.1 Group A.- All equipment offered for delivery on the contract or order shall be subjected to the group A examination and tests specified in table III. Any equipment failing to meet the requirements of this specification shall not be offered for delivery.

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:31Z
Check the source to verify that this is the current version before use.

Table III - Group A examination and tests.

Examination and tests	Requirement paragraph	Test reference
General examination	3.3	4.5
Operating and setting rate	3.6.9	4.6.1
Dielectric strength 1/	3.3	MIL-I-983
Insulation resistance 1/	3.3	MIL-I-983
Accuracy	3.4.12	4.6.3
Transients	3.3	MIL-I-983

1/For all but rotating components of equipment.

4.4.2 Group C.- Group C tests, specified in table IV, shall be conducted on one complete equipment when the basic design of the equipment or the material of a vital part has been changed.

Table IV - Group C tests.

Examination and tests	Requirement paragraph	Test reference
Illumination	3.6.7	4.6.2
Accelerated life (see table II)	3.3	4.6.4
Enclosure	3.3 and 3.5.1	MIL-I-983
Vibration	3.3	MIL-I-983
Shielding and radio frequency noise reduction	3.3	MIL-I-983
Airborne noise	3.3	MIL-I-983
Structureborne noise	3.3	MIL-I-983

4.5 General examination.- The general examination shall be conducted in accordance with MIL-I-983.

4.6 Test procedures.-

4.6.1 Operating and setting rate test.- The operating test shall consist of energizing the indicators with normal or rated power and normal level dummy operating signals to check for smoothness of operation throughout the entire scale range. The rate shall not be slower than as specified in 3.6.9.

4.6.2 Illumination.- Prototype or first production units shall be installed in a room suitable for dark conditions at the manufacturer's plant for evaluation of the internal illumination by the representatives of the inspector.

4.6.3 Accuracy.- The accuracy test shall consist of the following:

4.6.3.1 Latitude and longitude indicators.- Using the test circuit used for the operating test (4.6.1), energize the indicator with dummy input signals. The indicated latitude and longitude shall agree with the dummy input signals within ±0 degrees 00.1 minutes. Readings shall be taken at each 2 minute increment over the range from 0 degrees to 1 degree and at each 5 degree increment over the entire setting range.

4.6.4 Accelerated life.- The accelerated life test shall be conducted as specified in MIL-I-983, except that the ambient temperature during hours 175-300 shall be 149°F. (65°C.) in lieu of the 131°F. (55°C.) specified, with a constantly varying course input synchro signal of 360 degrees per minute in each direction, and a constantly varying speed input synchro speed of single harmonic motion of from 5 to 35 knots with a 60-second period for 500 hours. The heat dissipated from the sides and back of the equipment shall be restricted by means of low heat conducting bulkheads placed adjacent to the sides and back of the equipment.

5. PREPARATION FOR DELIVERY

5.1 Domestic shipment and early equipment installation and for storage of onboard repair parts.-

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

5.1.1 Own ship's position indicator.-

5.1.1.1 Preservation and packaging.- Preservation and packaging shall be sufficient to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the using activity and until early installation and may conform to the supplier's commercial practice when such meets these requirements.

5.1.1.2 Packing.- Packing shall be accomplished in a manner which will insure acceptance by common carrier at the lowest rate and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Rules and Regulations or other carrier regulations as applicable to the mode of transportation and may conform to the supplier's commercial practice when such meets these requirements.

5.1.1.3 Marking.- Shipment marking information shall be provided on interior packages and exterior shipping containers in accordance with the supplier's commercial practice. The information shall include nomenclature, Federal stock number or manufacturer's part number, contract or order number, manufacturer's name and destination.

5.1.2 Onboard repair parts.- Onboard repair parts shall be preserved and packaged by level A; packed by level C, and marked by levels A and C respectively in accordance with MIL-E-17555.

5.2 Domestic shipment and storage or overseas shipment.- The requirements, and levels of preservation, packaging, packing and marking for shipment shall be specified by the procuring activity (see 6.2).

(5.2.1 The following provides various levels for protection during domestic shipment and storage or overseas shipment, which may be required when procurement is made:

5.2.1.1 Preservation, packaging, packing and marking.- The equipment, accessories, repair parts and manuals shall be preserved and packaged level A or C; packed level A, B or C, as specified, and marked in accordance with MIL-E-17555.)

6. NOTES

6.1 Intended use.- The equipment covered by this specification is intended for Naval service where it is expected to withstand continuous use for long periods, under Military service conditions without benefit of overhaul. The equipment is in each case a vital instrument intended for important use by the forces concerned. Failure at a critical moment invariably results in serious reduction in the battle efficiency of the ship. Functional use is specified in 3.2.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) Inventory control point for repair parts (see 3.3).
(d) Quantity of manuals required (see 3.3).
(e) Preservation, packaging, packing, and marking requirements if other than as specified in 5.1 (see 5.2).

6.3 Preproduction.- Invitations for bids should provide that the Government reserves the right to waive the requirement for preproduction samples as to those bidders offering a product which has been previously procured or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending procurement.

6.4 CHANGES FROM PREVIOUS ISSUE. THE EXTENT OF CHANGES (DELETIONS, ADDITIONS, ETC.) PRECLUDE THE ANNOTATION OF THE INDIVIDUAL CHANGES FROM THE PREVIOUS ISSUE OF THIS DOCUMENT.

Preparing activity:
Navy - Ships
(Project 6320-N028Sh)

Source: https://assist.dla.mil -- Downloaded: 202640-19T18:31Z
Check the source to verify that this is the currentversion before use.

FOLD

DEPARTMENT OF THE NAVY
BUREAU OF SHIPS
WASHINGTON 25, D. C.

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
NAVY DEPARTMENT

CHIEF, BUREAU OF SHIPS
SPECIFICATIONS AND STANDARDIZATION BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:31Z
Check the source to verify that this is the current version before use.