MIL-L-23956A(OS)
Amendment 2
10 July 1975
SUPERSEDING
Amendment 1
4 August 1972

MILITARY SPECIFICATION

LAUNCHING GROUP MARK 16 MOD 4

This amendment forms a part of Military Specification MIL-L-23956A(OS), dated 18 September 1969, and is approved for use by all Departments and agencies of the Department of Defense

* Pages 1, 2, and 3, wherever it appears delete "Naval Ordnance Systems Command" and add "Naval Sea Systems Command (Code Ident 10001)."

Page 5, paragraph 3.2.5 (Interchangeability): Delete in its entirety.

Page 5, paragraph 3.2.6 (Gages): Delete in its entirety.

Page 5, paragraph 3.2.7. Delete and substitute:
"3.2.7 Threads. Unless otherwise specified, all threads shall be in accordance with National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings."

Page 5, paragraph 3.2.8 (Requests for deviation): Delete in its entirety.

Page 5, paragraph 3.2.9. Delete and substitute:
"3.2.9 Conflicting requirements. In the event of conflict between the documents referenced herein and the contents of this specification, the contents of this specification shall apply."

Page 11, paragraph 3.3.21. Delete and substitute:
"3.3.21 Missile snubbers. The missile snubbers shall be positioned to conform with Drawing 1735447. Time required for retraction shall be as specified in 3.3.22. Sequence of snubber extension shall be visually verified with a loaded rail to ensure side snubbers are in their fully-extended position prior to contact of the missile with the bottom snubbers."

* Page 19, paragraph 4.6.14. Delete and substitute:
"4.6.14 Train centering pin. With centering pin extended, use air drive motor to apply torque through train-drive gearing to training circle until no further movement occurs. Torque shall be applied in both directions of train. The carriage shall lock in the stow position and shall

FSC 1055

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:28Z
Check the source to verify that this is the current version before use.

exhibit no more than 0.050 "total movement measured at 36 ± 1/32" from center of rotation. The train power drive shall not start when the train centering pin handle is in the SECURE position."

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Navy - OS

Preparing Activity
Navy - OS
Project No. 1055-N058

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:28Z
Check the source to verify that this is the current version before use.