MIL-E-15465G(SHIPS)
AMENDMENT-6
23 May 1980
SUPERSEDING
AMENDMENT-5
13 December 1976

MILITARY SPECIFICATION

EJECTOR ASSEMBLIES, AIR

This amendment forms a part of Military Specification MIL-E-15465G(SHIPS), dated 9 November 1960.

PAGE 1

2.1, under "SPECIFICATIONS, MILITARY": Add:

"MIL-S-1222 - Studs, Bolts, Hex Cap Screws, and Nuts.
"MIL-Q-9858 - Quality Program Requirements.
"MIL-P-15024 - Plates, Tags, and Bands for Identification of Equipment.
"MIL-P-15024/5 - Plates Identification."

2.1, under "STANDARDS, MILITARY": Add:

"MIL-STD-438 - Schedule of Piping, Valves, Fittings, and Associated Piping Components for Submarine Service.
"MIL-STD-777 - Schedule of Piping, Valves, Fittings, and Associated Piping Components for Surface Ships."

PAGE 2

2.1: After "DRAWINGS" add:

"PUBLICATION
NAVAL SEA SYSTEMS COMMAND
NAVSEA 0900-LP-001-7000 - Instructions for Torch Brazing of Ferrous and Non-ferrous Piping."

2.2, under "AMERICAN SOCIETY FOR TESTING MATERIALS": Add:

"A296 - Corrosion-Resistant Iron-Chromium and Iron-Chromium Nickel Alloy Casting for General Application.
"B150 - Aluminum Bronze Rod, Bar and Shapes."

3.2.2: Delete and substitute:

"3.2.2 Flanges, valves, piping, and fittings shall be in accordance with MIL-STD-777 for surface ships or MIL-STD-438 for submarines. Root connections shall have the increased wall thickness required by Drawing B-218. Nozzles shall be of minimum length possible for through bolts."

FSC 4320

Source: https://assist.dla.mil -- Downloaded: 202640-18T06:16Z
Check the source to verify that this is the current version before use.

3.2.3: Add:

"Brazing of piping joints, including root connections, shall be accomplished in accordance with NAVSEA 0900-LP-001-7000. Where these joints are equal to or greater than 1/2 inch in nominal size, preinserted ring fittings shall be used. Face feed fittings may be used in sizes less than 1/2 inch."

PAGE 4

Table II: Delete and substitute:

"TABLE II. Material for air ejector units.

Part	Material	Applicable document
Steam chest	Cast steel, grade 60-30 or	ASTM A27
	steel bars, grades 1008 thru 1035	ASTM A108
Suction chamber	Gun metal, alloy 1-B	ASTM B143
	or cast steel, grade 60-30 or fabricated	ASTM A27
	steel or valve bronze	ASTM A285 (firebox)
	alloy 2A or aluminum	ASTM B143
	bronze alloy, alloy 9C	ASTM B148
Diffusers	Gun metal, alloy 1-B	ASTM B143
	or valve bronze, alloy	ASTM B143
	2A or aluminum bronze	ASTM B148
	alloy 9C	
	Steel, corrosion	
	resisting, type 304 or	ASTM A276 and
	316 bar with steel and	ASTM A285
	flanges, firebox quality	
	Steel corrosion resisting,	
	type 304 or 316, cast,	ASTM A296
	grade CF-8M	
	Aluminum bronze bar, alloy 1,	ASTM B150 and
	with steel end flanges,	ASTM A285
	firebox quality	
Nozzles	Steel, corrosion resisting,	
	type 303	ASTM A276
Nozzle rings	Steel, corrosion resisting,	
	type 303	ASTM A276
Gaskets (nozzle)	Copper, annealed, commercial	---
	or steel, sheet, hot-rolled,	---
	commercial	
Bolts and nuts	---	MIL-S-1222 or ASTM A193 grade B7 (high temperature service)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:16Z
Check the source to verify that this is the current version before use.

PAGE 5

3.4.6, line 4: Delete "Drilled".

3.4.6: Add as last sentence:

"Covers shall not be fitted with any connection for a blow valve. Covers may be straight thread plugs with metal gaskets if thread size is less than or equal to 1 inch in diameter. An acceptable alternative will be to use a separate strainer attached by welding to the steam chest so as to form a compact arrangement. The separate strainer shall meet the above requirements and the inlet connection shall be provided with a flange."

PAGE 6

Add as new paragraph 3.5.2.9.4:

"3.5.2.9.4 Manual cleanout ports shall be provided in each condenser section to provide access to the shell internals to permit manual removal of corrosion products. Minimum inside dimensions of these ports shall be 4 inches in diameter, or 3 inches by 4 inches if rectangular. Condenser drains shall be located and connected so as to minimize plugging due to corrosion products."

PAGE 9

3.7.5: Delete and substitute:

"3.7.5 Zinc anode protection. Provisions for the future installation of zinc anodes shall be made in accordance with MIL-A-19521, class A, but the zinc anodes and their supporting plugs shall not be furnished. Tapped bosses provided for the zinc anode supporting plugs shall be plugged with plugs of the material specified for the zinc supporting plugs in MIL-A-19521."

PAGE 10

3.8.5: Delete and substitute:

"3.8.5 Zinc protectors. The water box shall be provided with zinc protectors in accordance with MIL-A-19521, class A."

3.9: Delete and substitute:

"3.9 Identification plates. Identification plates shall be furnished on each ejector unit. They shall be type A or type B in accordance with MIL-P-15024 and MIL-P-15024/5. Identification plates of plastic or aluminum are not acceptable.

"3.9.1 Identification plates shall be secured to equipment with corrosion resistant metallic screws or rivets.

Source: https://assist.dla.mil -- Downloaded: 202640-18T06:16Z
Check the source to verify that this is the current version before use.

"3.9.2 Ejector unit identification plates shall contain data as follows:

(a) Manufacturer's name.
(b) Government contract number.
(c) Command or agency stock number (allow 17 spaces).
(d) Date of manufacture.
(e) Manufacturer's model or type and size.
(f) Service application.
(g) Test pressure, ejector parts (omit if classified).
(h) Test pressure, tube side (surface ships only).
(i) Blank space for Government inspector's stamp.
(j) Blank space for unit number (2 spaces - to be stamped by shipyard).
(k) NAVSEA manual number."

PAGE 12

3.13, line 2: Delete "type II of".

4.1: Delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Add as 4.1.1, 4.1.1.1, 4.1.1.2, and 4.1.1.3:

"4.1.1 Quality program requirements. The contractor shall provide and maintain a quality program acceptable to the Government for the supplies covered by this specification. The quality program shall be in accordance with MIL-Q-9858 supplemented as specified in 4.1.1.1 to 4.1.1.3, inclusive.

"4.1.1.1 Description of procedures. Procedures shall be assembled in manual form and shall include a flow chart showing the developments of the product through the manufacturing cycle. The procedures shall indicate organization and responsibility for the quality program.

"4.1.1.2 Inspection during manufacture. The contractor shall establish as a minimum, four inspection points located as follows:

(a) Initial set-up.
(b) First assemble.
(c) Second assemble.
(d) Roving floor.

Source: https://assist.dla.mil -- Downloaded: 20260-18T06:16Z
Check the source to verify that this is the current version before use.

"4.1.1.3 Storage. Supplies shall be stored in a dry area."

NOTE: The margins of this amendment are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 4320-N177)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:16Z
Check the source to verify that this is the current version before use.