MIL-H-15505K(NU)
INTERIM AMENDMENT 1
13 November 1996
SUPERSEDING
MIL-H-15505K
31 May 1989

MILITARY SPECIFICATION

HAT, SERVICE, WOMAN'S

This amendment forms a part of MIL-H-15505K(NU), dated 31 May 1989, and is approved for use by all departments and agencies of the Department of Defense.

PAGE 1

1.2, line 4, Under "Type I", delete "Polyester/Wool Tropical" and substitute "Wool Serge".

PAGE 2

2.1.1, Under "SPECIFICATIONS", "FEDERAL", delete "V-T-276 - Thread, Cotton" and "DDD-T-86 - Tape, Textile; Cotton, General Purpose (Unbleached, Bleached or dyed)". Add new documents "A-A-50199 - Thread, Polyester Core, Cotton - or Polyester-Covered" and "A-A-52094 - Thread, Cotton".

2.1.1, Under "SPECIFICATIONS", "MILITARY", delete "MIL-T-5038 - Tape, Textile and Webbing, Textile Reinforcing Nylon", "MIL-C-21115 - Cloth, Tropical: Wool, Polyester/Wool", "MIL-C-24927 - Cloth, Twill, Polyester/Cotton (Durable Press)" and "MIL-T-43548 - Thread Polyester Core: Cotton-, Rayon-, or Polyester-Covered". Add the following new documents: "MIL-C-823 - Cloth, Serge, Wool, Wool and Nylon: Polyester and Wool" and "MIL-C-87052 - Cloth, Twill, Polyester, White".

2.1.1, Under "STANDARDS", "MILITARY", delete "MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes".

(Application for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, NY 10018-3308)."

PAGE 3

2.2 Add to Non-Goverment publications at end of paragraph:

"AMERICAN NATIONAL STANDARDS INSTITUTE
ANSI/ASQC Z1.4 - Sampling Procedures and Tables for Inspection By Attributes

PAGE 4

3.3.1.1, delete paragraph in its entirety and substitute the following:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:17Z
Check the source to verify that this is the current version before use.

"3.3.1.1 Basic material. The 100% wool serge material to be used for the brim, band and mount, and band streamer pieces for the hat shall conform to Type I, Class 5 of MIL-C-823. The material shall be dyed to match Blue Shade 3346 and the piece number for the standard sample is 89096."

3.3.1.2.1, delete the first two lines and substitute the following:
"3.3.1.2.1 Cloth, reinforcement. The interlining cloth used for the front visor and back visor".

3.3.1.2.2, delete the first two lines and substitute the following:
"3.3.1.2.2 Cloth, interlining. The interlining cloth used for the top and side (innershell) crown pieces and the side (outershell) crown piece shall have 42 (±) warp ends per inch of".

PAGE 6

3.3.1.7, lines 2-4, delete "V-T-276, types IB2,.number 50 of MIL-T-43548." and substitute "A-A-52094, type II, ticket no. 24, 4-ply; or type III, ticket no. A, 0, 00, 3-ply as applicable; or a covered polyester thread conforming to ticket no. 50 of A-A-50199.".

3.3.1.7.1, line 5, delete "V-T-276 or MIL-T-43548" and substitute "A-A-52094 or A-A-50199" respectively.

3.3.1.8, line 1, after "crown" add "and to make the top crown pocket".

3.3.1.9.4, delete paragraph in its entirety.

3.3.1.9.5, line 3, after "C12044-012-4" add "size 3/4 inches wide, 1/2 inch long, black".

PAGE 7

3.3.1.10.3 and 3.3.1.10.3.1 delete paragraph in their entirety. Add new paragraph 3.3.1.10.3 as follows:

"3.3.1.10.3 Alternate mount construction. As an alternate construction, the mounts may be constructed from a leatherette material backing with a felt like material bonded to the front surface. The felt like material must match the basic shade of the brim and band and shall be constructed so as to prevent frayed edges around the curved section of the mount. The backing material shall be sufficiently heavy and afford enough stiffness so that when finished, equals or exceeds the standard mount. The felt like material shall show a minimum of "good" fastness to crocking and water when tested as specified in 4.4.1."

PAGE 8

3.3.2.1, delete paragraph in its entirety and substitute the following:

"3.3.2.1 Basic material. The basic material for the removeable hat cover (top crown and side crown) shall be a 100% texturized polyester twill cloth conforming to MIL-C-87052, White Shade 3006 and the piece number for the standard sample is 89233."

3.3.2.1.1 Fusible interlining. The top crown and side crown pieces shall be fused to 100% nylon tricot. The weight of the fusible interlining should be 2-1/2 to 3 ounces per linear yard based on 60 inch width and conform to the following requirements when tested as specified in 4.4.1:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:17Z
Check the source to verify that this is the current version before use.

Component testing requirements

Appearance of the fused sample:	
Initial	No evidence of bubbling, delamination of the bond, color change or strike-through
After 6 dry cleanings	No evidence of bubbling, delamination of the bond, color change or strike-through".

3.3.2.3, line 2-4, delete "type ICI", "V-T-276" and "MIL-T-43548" and substitute "type III", "A-A-52094" and "A-A-50199" respectively.

3.3.2.4, After last sentence, add new sentence: "The size of the label shall be no more than 1 inch in width and of sufficient length to accommodate the inscription."

PAGE 10

3.5.3, Table of Pattern Parts, under "Type I - Hat Frame", Under "Material", delete "Polyester/wool tropical" and substitute "Wool, serge".

3.5.3, Under "Material" delete "Cloth, interlining (innershell)" and substitute "Cloth, interlining (reinforcement)". Under "Material" "Cloth, interlining (innershell)", under "Pattern Parts and Cut Parts" delete "Crown, top (innershell) 1, and "Crown, side (innershell) 2". Under "Pattern Parts" delete "Back brim reinforcement" and substitute "Back visor reinforcement".

Under "Material" "Cloth, interlining (outershell)" add the following pattern parts and cut parts: "Crown, top (innershell) 1", and "Crown, side (innershell) 2".

Under "Material" "Plastic lining", add the following pattern part and cut part: "Crown, top protector, pocket (plastic) 1".

3.5.3, Table of Pattern Parts, under "Type IV - Hat Cover", delete "Cloth, cotton, double plain weave" and substitute "Cloth, twill, polyester, white". Under "Pattern Parts", delete "Cover, top and Cover, side" and substitute "Crown, top and Crown, side".

Add the following under "Material, Pattern Parts and Cut Parts": "Fusible interlining, Crown, top, interlining and Crown, side, interlining".

PAGE 11

3.7.1, line 1, delete "polyester/wool tropical" and substitute "wool serge".

PAGE 12

Table III, Operation 1b, lines 2 and 3, delete "polyester/wool" and substitute "wool serge". Line 5, after "ends" add "and all twill directional lines shall run in the same direction when component parts are assembled".

Table III, Operation 3, line 2, delete "polyester/wool" and substitute "wool serge".

Table III, Operation 4a, line 3, delete "polyester/wool" and substitute "wool serge". Operation 4b, line 2, delete "polyester/ wool" and substitute "wool serge".

PAGE 13

Table III, Operation 4c, line 1, delete "polyester/wool" and substitute "wool serge". After Operation 4f, add the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:17Z
Check the source to verify that this is the current version before use.

" OR	301	Ssa-1	12-14	0/3	0/3
g. As an alternate construction, the mounts may be made of the materials as specified in 3.3.1.10.3. In this case, the leatherette material shall be permanently fused/bonded to the felt like outer material and then cleanly die cut to the proper shape as required by the mount template. Topstitch approximately 1/16 inch from the edge around outer curve of the fabric covered mount. Extend stitching down to bottom of mount. Make a 1/8 inch diameter hole following the instruction of operation 4f."					

Table III, Operation 5a, line 5, delete "polyester/wool tropical" and substitute "wool serge". Line 9, delete "brim" and substitute "visor". Line 15, delete "polyester/wool tropical" and substitute "wool serge".

Table III, Operation 5b, delete second sentence and substitute the following: "Baste stitch together, with ends of plastic brim and interlining and felt brim interlining abutted, simultaneously inserting and positioning the front visor reinforcement piece and the back visor reinforcement piece between the two plies according to notches on pattern."

PAGE 15

Table III, Operation 5J, line 3, delete "20 (± 1)" and substitute "a minimum of 19,". Line 8, delete "17 (±)" and substitute "a minimum of 16".

PAGE 17

Table III, Operation 7a, delete in entirety and substitute the following: "a. The crown lining shall consist of three (3) ply top (crown top lining material and an underside of plastic sheeting and a plastic sheeting pocket piece) and a one-piece bias cut side lining piece."

Operation 7c, renumber as operation 7d. Add new operation 7c, as follows:

"c. Superimpose the crown, top protector pocket onto the crown, top protector in accordance with the pattern marks and stitch the circumference 1/4 inch from the cut plastic edge. NOTE: This operation may be done during operation 7d if the contractor so elects."	301 or 401	Ssa-1	12-14	0/3 0/3	0/3 00/3

Table III, renumbered Operation 7d, line 1, after "protector" add "and top crown protector pocket". At end of operation 7d add the following: "NOTE: The crown lining shall be so assembled so that on the completed hat the top crown protector pocket shall be positioned on the front portion of the hat."

PAGE 18

Table III, Operation 9a, line 4, delete "center" and substitute "bottom edge".

PAGE 19

Table III, Operation 10a, line 4, after "inner raw edge of" delete "crown" and substitute "brim".

Table III, Operations 11a, 11b, 11c and 11d, delete and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:17Z
Check the source to verify that this is the current version before use.

"a. Fold under one side of band in length direction 1/4 inch, and stitch 1/16 inch from the folded edge.	401	Efa-1	12-14	0/3	00/3
b. Fold opposite end of band in half lengthwise, with the raw edge 1/16 inch from the folded edge formed in 11a. Double stitch the folded side of band 1/8 to 3/16 inch gauge, with the outer row not less than 1/16 inch from the folded edge.	401	Osf-2	12-14	0/3	00/3
c. Steam and hot press band using the curved band shaper template. NOTE: Guide marks shall be made on the band for positioning the two snap fastener sockets (at front and back) and two buttonholes (one on each side) to correspond with the crown of the frame.					
d. Secure snap fastener sockets according to guide marks. The sockets shall be inserted through the inner ply only. Trim raw edge of band and stitch 3/16 inch from folded edge formed in 11a."	401	Ssa-1	12-14	0/3	00/3

PAGE 20

Table III, Operation 11f, delete in its entirety and substitute the following:

"f. Make two horizontal straight style buttonholes with a cut opening of 7/8 (± 1/16) inch on each side of the band as previously marked Buttonholes shall be barred at each end. NOTE: Buttonhole location shall ensure that the band will fit onto the hat allowing the snap fasteners to correctly line up with their mates without causing distortion in the band."	Buttonhole		45 per button hole	00/3 00/3

Table III, Operation 13, delete title "Attach streamer to band." and substitute the following new title "Attach streamer and mount to band." Operation 13, add "a." before operation paragraph. Add new Operation 13b as follows:

"b. Center mount onto back of band with square notch centered over front snap fastener socket. Bottom edge of mount shall be even with bottom edge of band. Stitch mount to band with two rows of stitching superimposed over existing band stitching at both top and bottomof band on inner row of double stitching. As an alternate, bottom edge of mount may be attached while band is being constructed."	301	Lsa-2	12-14	0/3	0/3

PAGE 21

Table III, Operation 14c, line 1, delete "Prepare" and substitute "Assemble".

PAGE 22

Table IV, before Operation 4a, insert the following new operation:
"Superimpose fusible interlining to backside of crown side and top. Press fusible interlining to cover pieces in accordance with directions of the fusible manufacturer."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:17Z
Check the source to verify that this is the current version before use.

PAGE 23

Table IV, Operation 4h, delete operation in its entirety and substitute the following new 4h:

"h. Stitch other edge of the sweatband to the side pieces 1/16 inch from edge of sweatband."	301	---	10-12	0/3 0/3

Table IV, after Operation 4h, add the following new Operation 4i:

"i. Label. Position and stitch both the size label and the care label described in 3.3.2.4 onto the back area of the sweatband so that they finish 1 (± 1/2) inch on either side of the center back seam. Both labels shall be positioned over the sweat band so that their height onto the cover is kept as low as possible. As an alternate, the size label may be placed over the center back seam of the sweatband."

Table IV, Operation 5, line 4, delete "1/4" and substitute "5/16". Line 7, after "positioned" add ", measuring from the center of the buttonhole,".

PAGE 25

3.8.1, Table V, under subparagraph "F)", line 1, delete "top crown seam" and substitute "edge of top crown piece."

PAGE 27

4.4.1, line 8, after "3.3.1.9.5)," add "the color and weight requirements for the fusible as required (see 3.3.2.1.1),".

PAGE 28

4.4.1, Table VII, delete the following component:

"Tape, Cotton or Nylon (yds)	Colorfastness:		
	Wet drycleaning	3.3.1.10.3.1	5622
	Crocking	3.3.1.10.3.1	5651
	Laundering	3.3.1.10.3.1	5614"

At the bottom of Table IV add the following new components:

"Fusible Interlining	Appearance of fused sample	3.3.2.1.1	
	Initial		Visual
	After 6 dry cleanings		Visual
Leatherette (alternate)	Colorfastness:		
	Crocking	3.3.1.10.3	5651 1/
	Water	3.3.1.10.3	5630 1/"

PAGE 34

4.4.2.3, Defect VII Crown lining, hat frame, add new defects "c and d" as follows:

Defect	Point Value
"c. Crown top protector pocket missing	2
d. Crown top protector pocket misplaced onto back portion of crown top protector instead of front portion	1"

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:17Z
Check the source to verify that this is the current version before use.

4.4.2.3, Defect VIIIc, line 1, delete "not 17 (+)." and substitute "a minimum of 16."

PAGE 35

4.4.2.3, Defect X, delete title "Band and streamer assembly, hat frame" and substitute "Band, mount and steamer assembly, hat frame". Add the following new defects "n to r":

Defect	Point Value
"n. Mount positioned too high or low on band by more than 1/8 inch	2
o. Frayed edges around circular position of mount when alternate construction method is used	2
p. Not cleanly die cut when alternate construction method is used	2
q. Felt like outer material not properly fused/bonded to the backing, in that the materials are visually separating, when alternate construction method is used	2
r. Mount not edge stitched as required when alternate construction method is used	2"

PAGE 36

4.4.2.3, Defect XII, at end of title of "Buttonholes, hat cover" add "and band".

4.4.2.3, Defect XV, delete "Eyelet, button" from title and substitute "Button, washer, and screwpost".

PAGE 41

5.1.1.1, lines 27 and 29, delete "10-3/4" and substitute "10".

PAGE 42

5.2.1.1, line 1, delete "Twenty-four (24)" and substitute "Twelve (12)". Line 5, delete "Inside" and substitute "Outside". Lines 5 and 6, delete "33, 24, and 24" and substitute "24-1/2, 21, and 19" respectively.

5.2.2.1, line 1, delete "Twenty-four (24)" and substitute "Twelve (12)". Line 4, at end of line delete "," and substitute ".". Line 5, delete "three in length, two in width, four in depth". Line 5, delete "Inside" and substitute "Outside". Line 6, delete "33, 24, and 24" and substitute "24-1/2, 21 and 19" respectively.

PAGE 43

5.3, line 2, after "intermediate," delete "or". After 5.3, add new paragraph as follows:

"5.3.1 Polyethylene bagged packages. Polyethylene bagged packages shall have the required information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall indicate the following information:

NOMENCLATURE:
STOCK NO.
SIZE:
QUANTITY:"

5.4, line 4, delete "means C, K, and L or O or P." and substitute "methods C and D or F or G."

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:17Z
Check the source to verify that this is the current version before use.

PAGE 44

6.8, lines 3, 4 and 5, delete "The eyelets (3.3.1.9.4) are available from E. P. Stimpson, 900 Sylvan Avenue, Bayport, NY 11705."

After 6.8, add the following new paragraph:

"6.9 Fusible interlining for covers. Materials meeting the requirements of 3.3.2.1.1 may be obtained from Fabrite Laminating, 70 Passaic Street, Woodridge, NJ 07075, Telephone No. (201)771-1406."

Paragraph numbers "6.9, 6.10, 6.11 and 6.12" renumber as "6.10, 6.11, 6.12, and 6.13" respectively.

PAGE 45

Paragraph number "6.13" renumber as "6.14".

PAGE 48

Replace Figure 3 with revised Figure 3. See attached.

Custodians
Navy - NU

Preparing activity:
DLA - CT

Project No.
8410-0337

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:17Z
Check the source to verify that this is the current version before use.