The documentation and process conversion measures necessary to comply with this revision shall be completed by 14 September 1994

INCH-POUND

MIL-S-19500/558B
14 June 1994
SUPERSEDING
MIL-S-19500/558A
6 September 1990

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, UNITIZED, PNP, SILICON,
SWITCHING FOUR TRANSISTOR ARRAY
TYPES 2N6987, 2N6987U, AND 2N6988, JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for PNP, silicon, switching transistors, four independent chip array. Four levels of product assurance are provided for each device type as specified in MIL-S-19500.

1.2 Physical dimensions. See figures 1, 3, and 4 (14-pin dual-in-line, 14-pin flat-pack, and 20-pin leadless chip carrier) and (see 3.3).

1.3 Maximum ratings. 1/

	P_T T_A = +25°C 2/	V_{CBO} 3/	V_{EBO} 3/	V_{CEO} 3/	I_C 3/	T_{OP} and T_{STG}
	W	V dc	V dc	V dc	mA dc	°C
2N6987	1.5	60	5	60	600	-65 to +200
2N6987U	1.0	60	5	60	600	-65 to +200
2N6988	0.4	60	5	60	600	-65 to +200

1/ Maximum voltage between transistors shall be ≥ 500 V dc.
2/ Derate linearly 8.57 mW/°C above T_A = +25°C for 2N6987 and 2N6987U.
Derate linearly 2.286 mW/°C above T_A = +25°C for 2N6988. Ratings apply to total package.
3/ Ratings apply to each transistor in the array.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Electronics Supply Center, ATTN: DESC-ELDT, 1507 Wilmington Pike, Dayton, OH 45444-5765, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configuration for type 2N6987.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A		.200		5.08	
b	.014	.023	.36	.58	8
b_1	.030	.070	.76	1.78	2, 8
c	.008	.015	.20	.38	8
D		.785		19.94	4
E	.220	.310	5.59	7.87	4
E_1	.290	.320	7.37	8.13	7
e	.100 BSC		2.54 BSC		5, 9
L	.125	.200	3.18	5.08	
L_1	.150		3.81		
Q	.015	.060	.38	1.52	3
S		.098		2.49	6
S_1	.005		.13		6
α	0°	15°	0°	15°	

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Index area; a notch or pin one identification mark shall be located adjacent to pin one and shall be located within the shaded area shown. The manufacturer's identification shall not be used as a pin one identification mark.
4. The minimum limit for dimension b_1 may be .023 inch (.58 mm) for leads number 1, 7, 8, and 14 only.
5. Dimension Q shall be measured from the seating plane to the base plane.
6. This dimension allows for off-center lid, meniscus and glass overrun.
7. The basic pin spacing is .100 inch (2.54 mm) between centerlines. Each pin centerline shall be located within ±.010 inch (.25 mm) of its exact longitudinal position relative to pins 1 and 14 (see figure 6).
8. Applies to all four corners (leads number 1, 7, 8, and 14).
9. Lead center when α is 0°. E_1 shall be measured at the centerline of the leads.
10. All leads.
11. Twelve spaces.
12. No organic or polymeric materials shall be molded to the bottom of the package to cover the leads.

FIGURE 1. Dimensions and configuration for type 2N6987 - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T03:20Z
Check the source to verify that this is the current version before use.




FIGURE 2. Lead gauge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

MIL-S-19500, and as specified herein.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
ϕB	.0323	.0333	.82	.85	
b_1		.002		.05	
ϕC	.119	.129	3.02	3.28	4
D	1.750		44.45		
d_1	.200 NOM		5.08 NOM		
E	.750		19.05		4
E_1	.300 BSC		7.62 BSC		
e	.100 BSC		2.54 BSC		
e_1	.375		9.53		6
L_1	.090	.099	2.29	2.51	4
N	14		14		2
Y_1		.010		.25	
Y_2		.002		.05	3, 5
W	8	12	8	12	

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Dimensioning and tolerancing per ANSI Y14.5.
4. N is the number of ϕB lead position holes in each gauge variation.
5. W equals the milligrams of weight per lead to be applied perpendicular to the top of devices.
6. Maximum dimensions at D, E, and e_1 are manufacturing options with e_1 = E/2.
7. The seating plane shall be established by inserting the terminal leads of a device into the gauge with weight (W) applied to the top of the device. Dimensions A, Q, and L (see figure 1) can then be measured.
8. Height of leg optional, but sufficient to prevent lead of inserted device from bottoming on measuring table.

FIGURE 2. Lead gauge - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026Ø10-19T03:20Z
Check the source to verify that this is the current version before use.




FIGURE 3. Physical dimensions for type 2N6988.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A	.030	.085	.76	2.18	
b	.010	.019	.25	.48	5
c	.003	.006	.08	.15	5
D		.280		7.11	3
E	.240	.260	6.10	6.60	
E_1		.290		7.37	3
E_2	.125		3.18		
E_3	.030		.76		
e	.050 BSC		1.27 BSC		4, 6
k	.008	.015	.20	.38	10
L	.250	.370	6.35	9.40	
Q	.005	.040	.13	1.02	2
S_1	.005		.13		7, 8
S_2	.004		.10		11
α	30°	90°	30°	90°	12

NOTES:
1. Index area; a notch or pin one identification mark shall be located adjacent to pin one and shall be located within the shaded area shown. The manufacturer's identification shall not be used as a pin one identification mark. Alternatively, a tab (dim k) may be used to identify pin one.
2. Dimension Q shall be measured at the point of exit of the lead from the body.
3. This dimension allows for off-center lid, meniscus and glass overrun.
4. The basic pin spacing is .050 inch (1.25 mm) between centerlines. Each pin centerline shall be located within ±.005 inch (.13 mm) of its exact longitudinal position relative to pins 1 and 14.
5. All leads - increase maximum limit by .003 inch (.08 mm) measured at the center of the flat when the lead finish is solder.
6. Twelve spaces.
7. Applies to all four corners (leads number 2, 6, 9, and 13).
8. Dimension S_1 may be .000 inch (.00 mm if leads number 2, 6, 9, and 13) bend toward the cavity of the package within one lead width from the point of entry of the lead into the body or if the leads are brazed to the metallized ceramic body.
9. No organic or polymeric materials shall be molded to the bottom of the package to cover the leads.
10. Optional, see note 1. If a pin one identification mark is used in addition to this tab, the minimum limit of dimension k does not apply.
11. Applies to leads number 1, 7, 8, and 14.
12. Lead configuration is optional within dimension E except dimensions b and c apply.
13. Dimensions are in inches.
14. Metric equivalents are given for general information only.

FIGURE 3. Physical dimensions for type 2N6988 - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-19T03:20Z
Check the source to verify that this is the currentversion before use.




Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.063	.075	1.60	1.90
D	.345	.355	8.76	9.02
D_1	.195	.205	4.95	5.21
D_2	.050 TYP		1.27 TYP	
D_3	.070	.080	1.76	2.03
E	.025 REF		0.64 REF	
L_1	.150 REF		3.81 REF	
L_2	.080	.090	2.03	2.28


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 inch (0.13 mm).

FIGURE 4. Physical dimensions for type 2N6987U.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T03:20Z
Check the source to verify that this is the currentversion before use.



14-lead flat-package or dual-in-line (top view)



20 pin leadless chip carrier (top view).

FIGURE 5. Schematic and terminal connections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Characteristics apply to each transistor in the array.

Limits	h_{FE2} 1/ V_{CE} = 10 V dc I_C = 1.0 mA dc	h_{FE4} 1/ V_{CE} = 10 V dc I_C = 150 mA dc	C_{obo} V_{CB} = 10 V dc I_E = 0 100 kHz ≤ f ≤ 1 MHz	Switching t_{on} see fig.7	Switching t_{off} see fig.8
			pF	ns	ns
Min	100	100			
Max	450	300	8	45	300

Limits	h_{fe} V_{CE} = 20 V dc I_C = 50 mA dc f = 100 MHz	$V_{CE(sat)2}$ 1/ I_C = 500 mA dc I_B = 50 mA dc	$V_{BE(sat)2}$ 1/ I_C = 500 mA dc I_B = 50 mA dc
		V dc	V dc
Min	2.0		
Max	8.0	1.6	2.6

1/ Pulsed (see 4.5.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-S-19500 - Semiconductor Devices, General Specification for.

STANDARD

MILITARY

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Defense Printing Service Detachment Office, Building 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Associated detail specification. The individual item requirements shall be in accordance with MIL-S-19500 and as specified herein.

3.2 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-S-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

3.3 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-S-19500, and on figures 1, 3, and 4 herein.

3.3.1 Lead finish. Lead finish shall be solderable in accordance with MIL-S-19500. Pure tin can be used as a lead finish until December 31, 1994 for the dual-in-line package (figure 1).

3.3.2 Schematic and terminal connections. The schematic and terminal connections shall be as shown on figure 5.

3.4 Marking. Marking shall be in accordance with MIL-S-19500.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-S-19500, and as specified herein.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-S-19500.

4.3 Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with table II of MIL-S-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table II of MIL-S-19500)	Measurements	
	JANS level	JANTX & JANTXV levels
7(a) or 14(a)	Maximum leak rate = 1 x 10^{-7} atm cc/s Test condition C, step 1 only	Maximum leak rate = 1 x 10^{-7} atm cc/s Test condition C, step 1 only
11	I_{CBO1} and h_{FE4}	I_{CBO1} and h_{FE4}
12	See 4.3.1	See 4.3.1
13	Subgroups 2 and 3 of table I herein; ΔI_{CBO1} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent of initial value.	Subgroup 2 of table I herein; ΔI_{CBO1} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent of initial value.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: T_A = Room ambient as defined in the general requirements of MIL-STD-750, (see 4.5); V_{CB} = 30 V dc; P_T = 1.5 W for 2N6987; P_T = 1.0 W for 2N6987U, and P_T = 0.4 W for 2N6988.

NOTE: No heat sink or forced air cooling on the devices shall be permitted.

4.4 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-S-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-S-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in IVa (JANS) and table IVb (JAN, JANTX, and JANTXV) of MIL-S-19500. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

4.4.2.1 Group B inspection, table IVa (JANS) of MIL-S-19500.

Subgroup	Method	Condition
B4	1036	V_{CB} = 10 V dc; P_T = 1.5 W for 2N6987, P_T = 1.0 W for 2N6987U, P_T = 0.4 W for 2N6988; at T_A = +25°C ± 3°C; t_{on} = t_{off} = 3 minutes minimum for 2,000 cycles. No heat sink or forced-air cooling on the devices shall be permitted.
B5	1027	V_{CB} = 10 V dc, T_A = +125°C ±25°C for 96 hours; P_T = 1.5 W for 2N6987, P_T = 1.0 W for 2N6987U, P_T = 0.4 W for 2N6988 at T_A = +100°C or adjusted as required by the chosen T_A to give an average lot T_J = +275°C.
B6		Not Applicable.

4.4.2.2 Group B inspection, table IVb (JAN, JANTX, and JANTXV) of MIL-S-19500.

Subgroup	Method	Condition
B3	1027	V_{CB} = 10 V dc; P_T = 1.5 W for 2N6987, P_T = 1.0 W for 2N6987U, and P_T = 0.4 W for 2N6988; at T_A = +30°C ±5°C. No heat sink or forced-air cooling on the devices shall be permitted.
B5		Not applicable.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table V of MIL-S-19500. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein.

Subgroup	Method	Condition
C2	2036	Test condition E: 3 oz. weight; three bends of 15°for 2N6988; three bends of 30° for 2N6987. (Not applicable to 2N6987U).
C6	1027	V_{CB} = 10 V dc; P_T = 1.5 W for 2N6987, P_T = 1.0 W for 2N6987U, P_T = 0.4 W for 2N6988; at T_A = +30°C ± 5°C. No heat sink or forced-air cooling on device shall be permitted.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Input capacitance. This test shall be conducted inaccordance with MIL-STD-750, method 3240, except the output capacitor shall be omitted.

4.5.3 Independent transistor inspections. Inspections shall be performed on each transistor in the array.

4.5.4 Transistor-to-transistor resistance. The leads of each transistor shall be shorted together for this test. The resistance shall be measured between each transistor in the array.

Source: https://assist.dla.mil -- Downloaded: 202610-19T03:20Z
Check the source to verify that this is the currentversion before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Breakdown voltage collector to base	3001	Bias condition D; I_C = 10 µA dc	$V_{(BR)CBO}$	60		V dc
Breakdown voltage emitter to base	3026	Bias condition D; I_E = 10 µA dc	$V_{(BR)EBO}$	5		V dc
Breakdown voltage collector to emitter	3011	Bias condition D; I_C = 10 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	60		V dc
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 50 V dc	I_{CBO1}		10	nA dc
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 3.5 V dc	I_{EBO}		50	nA dc
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 0.1 mA dc	h_{FE1}	75		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 1.0 mA dc	h_{FE2}	100	450	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 10 mA dc	h_{FE3}	100		
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 150 mA dc; pulsed (see 4.5.1)	h_{FE4}	100	300	
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 500 mA dc; pulsed (see 4.5.1)	h_{FE5}	50		
Collector to emitter voltage (saturated)	3071	I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		0.4	V dc
Collector to emitter voltage (saturated)	3071	I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		1.6	V dc
Base to emitter saturated voltage	3066	Test condition A; I_C = 150 mA dc; I_B = 15 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)1}$		1.3	V dc

See footnote at end of table.


Source: https://assist.dla.mil -- Downloaded: 20261O-19T03:20Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Base to emitter saturated voltage	3066	Test condition A; I_C = 500 mA dc; I_B = 50 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)2}$		2.6	V dc
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 50 V dc	I_{CBO2}		10	µA dc
Low temperature operation:		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 10 V dc; I_C = 1.0 mA dc	h_{FE6}	50		
Subgroup 4						
Small-signal short-circuit forward-current transfer ratio	3206	V_{CE} = 10 V dc; I_C = 1 mA dc; f = 1 kHz	h_{fe}	100		
Magnitude of small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 20 V dc; I_C = 50 mA dc; f = 100 MHz	$\|h_{fe}\|$	2.0	8.0	
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		8.0	pF
Input capacitance (output open-circuited)	3240	V_{EB} = 2.0 V dc; I_C = 0; 100 kHz ≤ f ≤ 1 MHz; See 4.5.2	C_{ibo}		30	pF
Turn-on time		See figure 7	t_{on}		45	ns
Turn-off time		See figure 8	t_{off}		300	ns
Transistor-to-transistor resistance		$\|V_{T-T}\|$ = 500 V dc; See 4.5.3	R_{T-T}	10^{10}		ohms


1/ For sampling plan see MIL-S-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.



NOTES:
1. The rise time (t_r) and fall time (t_f) of the applied pulse shall be each ≤ .2 ns; duty cycle ≤ 2 percent; generator source impedance shall be 50 Ω.
2. Output sampling oscilloscope: Z_{in} ≥ 100 kΩ; C_{in} ≤ 12 pF; rise time ≤ 5.0 ns.

FIGURE 7. Saturated turn-on switching time test circuit and waveform.



NOTES:
1. The rise time (t_r) and fall time (t_f) of the applied pulse shall be each ≤ .2 ns; duty cycle ≤ 2 percent; generator source impedance shall be 50 Ω.
2. Output sampling oscilloscope: Z_{in} ≥ 100 kΩ; C_{in} ≤ 12 pF; rise time ≤ 5.0 ns.

FIGURE 8. Saturated turn-off switching time test circuit and waveform.

Source: https://assist.dla.mil -- Downloaded: 202610-19T03:20Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-S-19500.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-S-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Issue of DODISS to be cited in the solicition.

b. Lead finish (see 3.3.1).

c. Type designation and product assurance level.

6.3 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - MI, AR, SM
Navy - AS, CG, MC
Air Force - 13, 15, 19, 85, 99

Preparing activity:
DLA - ES

(Project 5961-1625)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-S-19500/5588	2. DOCUMENT DATE (YYMMDD) 94/06/14

3. DOCUMENT TITLE
SEMICONDUCTOR DEVICE, UNITIZED, PNP, SILICON, SWITCHING, FOUR TRANSISTOR ARRAY, TYPES 2N6987, 2N6987U, AND 2N6988, JANTX, JANTXV, AND JANS

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	e. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Alan Barone	b. TELEPHONE (Include Area Code) (1) Commercial 513-296-6048 (2) AUTOVON 986-6048
c. ADDRESS (Include Zip Code) Defense Electronics Supply Center Attn: DESC-ELDT Dayton, Ohio 45444-5765	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:20Z
Check the source to verify that this is the current version before use.