The documentation and process conversion measures necessary to comply with this document shall be completed by 16 October 2025.

INCH-POUND

MIL-PRF-19500/558L
w/AMENDMENT 1
16 July 2025
SUPERSEDING
MIL-PRF-19500/558L
20 November 2020

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, UNITIZED, PNP, SILICON, SWITCHING,
FOUR TRANSISTOR ARRAY, TYPES 2N6987, AND 2N6988,
JAN, JANTX, JANTXV, JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for PNP, silicon, switching transistors, four independent chip array. Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500. Radiation hardness assurance (RHA) level designators “M”, “D”, “P”, “L”, “R”, “F”, “G”, and “H” are appended to the device prefix to identify devices which have passed RHA requirements.

1.2 Package outlines. The device package for the encapsulated device types are as follows: 14-pin dual-in-line in accordance with figure 1, 14-pin flat-pack in accordance with figure 2, and 20-pin leadless chip carrier in accordance with figure 3.

1.3 Maximum ratings, unless otherwise specified T_A = +25°C. (1)

	P_T T_A = +25°C (2)	P_T $T_{A(AM)}$ = +25°C (2)	$R_{\theta JA}$ (3)	$R_{\theta JA(AM)}$ (3) (4)	V_{CBO} (5)	V_{EBO} (5)	V_{CEO} (5)	I_C (5)	T_J and T_{STG}
	W	W	°C/W	°C/W	V dc	V dc	V dc	mA dc	°C
2N6987	1.5	N/A	85	N/A	-60	-5	-60	-600	-65
2N6987U	1.0	N/A	160	N/A	-60	-5	-60	-600	to
2N6988	1.0	1.0	175	23	-60	-5	-60	-600	+200

(1) Maximum voltage between transistors shall be ≥ 500 V dc.
(2) For derating see figure 5, figure 6, figure 7, and figure 8.
(3) For thermal impedance graphs, see figure 9, figure 10, figure 11, and figure 12.
(4) Thermally conductive adhesive mount to infinite heat sink.
(5) Ratings apply to each transistor in the array.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
FSC 5961

* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Characteristics apply to each transistor in the array.

Limits	h_{FE2} (1)	h_{FE4} (1)	C_{obo}	Switching	
	V_{CE} = -10 V dc I_C = -1.0 mA dc	V_{CE} = -10 V dc I_C = -150 mA dc	V_{CB} = -10 V dc I_E = 0 100 kHz ≤ f ≤ 1 MHz	t_{on} see figure 13	t_{off} see figure 14
			pF	ns	ns
Min	100	100			
Max	450	300	8	45	300

Limits	$\lvert h_{fe} \rvert$	$V_{CE(sat)2}$ (1)	$V_{BE(sat)2}$ (1)
	V_{CE} = -20 V dc I_C = -50 mA dc f = 100 MHz	I_C = -500 mA dc I_B = -50 mA dc	I_C = -500 mA dc I_B = -50 mA dc
		V dc	V dc
Min	2.0		
Max	8.0	-1.6	-2.6

(1) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level.

1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", "JANTXV", and "JANS".

1.5.2 Radiation hardness assurance (RHA) designator. The RHA levels that are applicable for JANS devices in this specification sheet from lowest to highest are as follows: ("M", "D", "P", "L", "R", "F", "G", and "H"). The RHA levels that are applicable for JANTXV devices in this specification sheet from lowest to highest are as follows: ("R", and "F").

1.5.3 Device type. The designation system for the device types of semiconductors covered by this specification sheet are as follows.

1.5.3.1 First number and first letter symbols. The semiconductors of this specification sheet use the first number and letter symbols "2N".

1.5.3.2 Second number symbols. The second number symbols for the semiconductors covered by this specification sheet are as follows: "6987", and "6988".

1.5.4 Suffix symbols. The following suffix symbols are incorporated in the PIN for this specification sheet:

	A blank second suffix symbol indicates a 14-pin dual-in-line (2N6987) in accordance with figure 1, or a 14-pin flat-pack (2N6988) in accordance with figure 2.
U	Indicates a 20-pin leadless chip carrier. (see figure 3).

1.5.5 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

1.6 Radiation features. The following radiation features are applicable for RHA devices supplied to this specification sheet.

* 1.6.1 Maximum total ionizing dose (TID). The maximum TID that RHA devices were tested to in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of MIL-STD-750 are as follows:

For device type 2N6987, 2N6987U, AND 2N6988:.....300 krad(Si) 1/

* 1/ The manufacturers supplying these device types have performed characterization testing in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of MIL-STD-750. The radiation end point limits are guaranteed only to a maximum TID level of 300 krad(Si).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configuration for type 2N6987.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.


Symbol	Inches		Millimeters		Notes
	Min	Max	Min	Max	
BH		.200		5.08	
LW	.014	.023	0.36	0.58	10
LW_1	.030	.070	0.76	1.78	4, 10
LT	.008	.015	0.20	0.38	10
BL		.785		19.94	4
BW	.220	.310	5.59	7.87	4
BW_1	.290	.320	7.37	8.13	9
LS	.100 BSC		2.54 BSC		7, 11
LL	.125	.200	3.18	5.08	
LL_1	.150		3.81		
LO_2	.015	.060	0.38	1.52	5
LO_1		.098		2.49	8
LO	.005		0.13		8
α	0°	15°	0°	15°	

* NOTES:

1. Dimensions are in inches.
2. Millimeters are given for information only.
3. Index area; a notch or pin one identification mark shall be located adjacent to pin one and shall be located within the shaded area shown. The manufacturer's identification shall not be used as a pin one identification mark.
4. The minimum limit for dimension LW_1 may be .023 inch (0.58 mm) for lead numbers 1, 7, 8, and 14 only.
5. Dimension LO_2 shall be measured from the seating plane to the base plane.
6. This dimension allows for off-center lid, meniscus, and glass overrun.
7. The basic pin spacing is .100 inch (2.54 mm) between centerlines. Each pin centerline shall be located within ±.010 inch (±0.25 mm) of its exact longitudinal position relative to pins 1 and 14.
8. Applies to all four corners (lead numbers 1, 7, 8, and 14).
9. Lead center when α is 0 degrees. BW_1 shall be measured at the centerline of the leads.
10. All leads: Increase maximum limit by .003 inch (0.08 mm) measured at the center of the flat, when lead finish A is applied. Pointed or round lead ends are allowed.
11. Twelve spaces.
12. No organic or polymeric materials shall be molded to the bottom of the package to cover leads.
13. For terminal connections, see figure 4.

FIGURE 1. Dimensions and configuration for type 2N6987 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CH	.030	.115	0.76	2.92	
LW	.010	.019	0.25	0.48	6
TL	.008	.015	0.20	0.38	11
BL		.280		7.11	4
BW	.240	.260	6.10	6.60	
LU		.290		7.37	4
BW_2	.125		3.18		

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BW_3	.030		0.76		
LS	.050 BSC		1.27 BSC		5, 7
LT	.003	.006	0.076	0.152	6
LL	.250	.370	6.35	9.40	
LD_2	.005	.040	0.13	1.02	3
LO	.005		0.13		8, 9
LO_3	.004		0.10		12
α	30°	90°	30°	90°	13

* NOTES:


1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Index area: A notch or pin one identification mark shall be located adjacent to pin one and shall be located within the shaded area shown. The manufacturer's identification shall not be used as a pin one identification mark. Alternatively, a tab (dim TL) may be used to identify pin one.
4. Dimension LD_2 shall be measured at the point of exit of the lead from the body.
5. This dimension allows for off-center lid, meniscus, and glass overrun.
6. The basic pin spacing is .050 inch (1.27 mm) between centerlines. Each pin centerline shall be located within ±.005 inch (0.13 mm) of its exact longitudinal position relative to pins 1 and 14.
7. All leads: Increase maximum limit by .003 inch (0.08 mm) measured at the center of the flat when the lead finish is solder.
8. Twelve spaces.
9. Applies to all four corners (leads number 2, 6, 9, and 13).
10. Dimension LO may be .000 inch (0.00 mm if leads number 2, 6, 9, and 13) bend toward the cavity of the package within one lead width from the point of entry of the lead into the body or if the leads are brazed to the metallized ceramic body.
11. No organic or polymeric materials shall be molded to the bottom of the package to cover the leads. This view shows one of two optional lead configurations available.
12. Optional, see note 2. If a pin one identification mark is used in addition to this tab, the minimum limit of dimension TL does not apply.
13. Applies to leads number 1, 7, 8, and 14.
14. Lead configuration is optional within dimension BW except dimensions LW and LT apply.

* 15. For Transistor 1, collector = Pin 1, base = Pin 2, emitter = Pin 3.
* 16. For Transistor 2, collector = Pin 7, base = Pin 6, emitter = Pin 5.
* 17. For Transistor 3, collector = Pin 8, base = Pin 9, emitter = Pin 10.
* 18. For Transistor 4, collector = Pin 14, base = Pin 13, emitter = Pin 12.

19. Pins 4 and 11 are no contacts.

FIGURE 2. Physical dimensions for type 2N6988.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.073	.085	1.85	2.16
A_1	.063	.075	1.60	1.90
D	.345	.355	8.76	9.02
D_1	.195	.205	4.95	5.21
D_2	.050 TYP		1.27 TYP	
D_3	.070	.080	1.76	2.03
E	.025 REF		0.64 REF	
L_1	.050 REF		1.27 REF	
L_2	.080	.090	2.03	2.28


* NOTES:
1. Dimensions are in inches. Millimeters equivalents are given for general information only.
2. Unless otherwise specified, tolerance is ±.005 inch (0.13 mm).
3. For terminal connections, see figure 4.

FIGURE 3. Physical dimensions for type 2N6987U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.



14-lead flat-package or dual-in-line (top view)



20 pin leadless chip carrier (top view).

FIGURE 4. Schematic and terminal connections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1. General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2. Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML-19500) before contract award (see 4.2 and 6.3).

3.3. Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

PCB	Printed circuit board.
$R_{\theta JA}$	Thermal resistance junction to ambient.
$R_{\theta JA(AM)}$	Thermal resistance ambient (adhesive mount to PCB).
$T_{A(AM)}$	Temperature ambient (adhesive mount to PCB).

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1, figure 2, figure 3, and figure 4 herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Schematic and terminal connections. The schematic and terminal connections shall be as shown on figure 4.

* 3.5 RHA. Radiation hardness assurance requirements, PIN designators, and test levels shall be as defined in MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Marking. Marking shall be in accordance with MIL-PRF-19500. The radiation hardened designator M, D, P, L, R, F, G, or H shall immediately precede (or replace) the device "2N" identifier (depending upon degree of abbreviation required).

3.9. Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I and table II).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (JANS, JANTX and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500 appendix E, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANS level	Measurements for JANTX and JANTXV levels
(1) 3c	Thermal impedance, method 3131 of MIL-STD-750, see 4.3.2.	Thermal impedance, method 3131 of MIL-STD-750, see 4.3.2.
9	I_{CBO2} and h_{FE4}	Not applicable.
10	24 hours minimum.	24 hours minimum.
11	I_{CBO2} and h_{FE4} ΔI_{CBO2} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent of initial value.	I_{CBO2} and h_{FE4}
12	See 4.3.1.	See 4.3.1.
13	Subgroups 2 and 3 of table I herein; ΔI_{CBO2} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent of initial value.	Subgroup 2 of table I herein; ΔI_{CBO2} = 100 percent of initial value or 5 nA dc, whichever is greater; Δh_{FE4} = ±15 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; TX and TXV do not need to be repeated in screening requirements.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: V_{CB} = -10 - -30 V dc; P_T = 1.5 W for 2N6987; P_T = 1.0 W for 2N6987U, and P_T = 1.0 W for 2N6988. T_A ambient rated as defined in 1.3. NOTE: No heat sink or forced air-cooling on the devices shall be permitted. Power ratings apply to total package. With approval of the qualifying activity and preparing activity, alternate burn-in criteria (hours, bias conditions, T_J, and mounting conditions) may be used for JANTX and JANTXV quality levels. A justification demonstrating equivalence is required. In addition, the manufacturing site's burn-in data and performance history will be essential criteria for burn-in modification approval.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed on each die in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{MD} (and V_C where appropriate). The thermal impedance limit shall comply with the thermal impedance graph on figure 9, figure 10, figure 11, and figure 12 (less than or equal to the curve value at the same t_H time) and shall be less than the process determined statistical maximum limit as outlined in method 3131. See table II, subgroup 4 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein. If alternate screening is being performed in accordance with MIL-PRF-19500, a sample of screened devices shall be submitted to and pass the requirements of table I, group A1 and group A2 inspection only (table E-VIb, group B, subgroup 1 is not required to be performed again if group B has already been satisfied in accordance with 4.4.2 herein).

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

* 4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with 4.4.2.1 for quality level JANS and 4.4.2.2 for quality levels JAN, JANTX, and JANTXV. Electrical measurements (end-points) and delta for JAN, JANTX, and JANTXV shall be after each step in 4.4.2.2 and shall be in accordance with table I, subgroup 2 and 4.5.5 herein.

* 4.4.2.1 Group B inspection, table E-VIA (JANS) of MIL-PRF-19500. Group B inspection for quality level JANS shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA of MIL-PRF-19500 and herein. Delta measurements shall be in accordance with 4.5.5 herein, delta parameters apply to subgroups B4 and B5.

	Subgroup	Method	Condition
*	B4	1037	V_{CB} = -10 V dc.
	B5	1027	V_{CB} = -10 V dc, $P_D \geq$ 100 percent of max rated P_T (see 1.3). (NOTE: If a failure occurs, resubmission shall be at the test conditions of the original sample.) Option 1: 96 hours minimum sample size in accordance with MIL-PRF-19500, table E-Via, adjust T_A or P_D to achieve T_J = +275°C minimum. Option 2: 216 hours minimum, sample size = 45, c = 0; adjust T_A or P_D to achieve T_J = +225°C minimum.

* 4.4.2.2 Group B inspection, (JAN, JANTX, and JANTXV). Group B inspection for quality levels JAN, JANTX, and JANTXV shall be conducted in accordance with the conditions specified in table E-VIC (small die flow) of MIL-PRF-19500 and herein. Electrical measurements (end-points) and delta measurements shall be after each step and shall be in accordance with table I, subgroup 2 and 4.5.5 herein. Separate samples may be used for each step. In the event of a lot failure, the resubmission requirements of MIL-PRF-19500 shall apply. In addition, all catastrophic failures during CI shall be analyzed to the extent possible to identify root cause and corrective action. Whenever a failure is identified as wafer lot and wafer processing related, the entire wafer lot and related devices assembled from the wafer lot shall be rejected unless an appropriate determined corrective action to eliminate the failure mode has been implemented and the devices from the wafer lot are screened to eliminate the failure mode.

Step	Method	Condition
1	1026	Steady-state life: 1,000 hours minimum, V_{CB} = -10 V dc, power shall be applied to achieve T_J = +150°C minimum using a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45 devices, c = 0.
2	1048	Blocking life, T_A = +150°C, V_{CB} = 80 percent of rated voltage, 48 hours minimum. n = 45 devices, c = 0.
3	1032	High-temperature life (non-operating), t = 340 hours, T_A = +200°C. n = 22, c = 0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

4.4.2.3 Group B sample selection. Samples selected from group B inspection shall meet all of the following requirements:

a. For JAN, JANTX and JANTXV samples shall be selected randomly from a minimum of three wafers (or from each wafer in the lot) from each wafer lot. For JANS, samples shall be selected from each inspection lot. See MIL-PRF-19500.

b. Shall be chosen from an inspection lot that has been submitted to and passed table I, subgroup 2, conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for life test (subgroups B4 and B5 for JANS, and group B for JAN, JANTX, and JANTXV) may be pulled prior to the application of final lead finish.

* 4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and in 4.4.3.1 (JANS) and 4.4.3.2 (JAN, JANTX, and JANTXV) herein for group C testing. Delta measurements shall be in accordance with 4.5.5 herein, delta parameters apply to subgroup C6.

4.4.3.1 Group C inspection, table E-VII (JANS) of MIL-PRF-19500.

	Subgroup	Method	Condition
*	C2	2036	Test condition E, 3 ounce (85.049 g) weight: Three bends of 15 degrees for 2N6988; three bends of 90 degrees for 2N6987; not applicable to 2N6987U.
	C6	1026	1,000 hours at V_{CB} = -10 - -30 V dc; T_J = +150°C minimum. No heat sink or forced-air cooling on device shall be permitted.

4.4.3.2 Group C inspection, table E-VII (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

	Subgroup	Method	Condition
*	C2	2036	Test condition E, 3 ounce (85.049 g) weight: Three bends of 15 degrees for 2N6988; three bends of 90 degrees for 2N6987; not applicable to 2N6987U.
	C5	3131	$R_{\theta JA}$, see 1.3.
	C6		Not applicable.

4.4.3.3 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any inspection lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes group A tests for conformance inspection. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

4.4.4 Group D inspection. Conformance inspection for hardness assured JANS and JANTXV types shall include the group D tests specified in table II herein. These tests shall be performed as required in accordance with MIL-PRF-19500 and method 1019 of MIL-STD-750 for total ionizing dose or method 1017 of MIL-STD-750 for neutron fluence, as applicable (see 6.2 herein), except group D, subgroup 2 may be performed separate from other subgroups. Alternate package options may also be substituted for the testing provided there is no adverse affect to the fluence profile.

4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E-IX of MIL-PRF-19500 and as specified in table III herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Input capacitance. This test shall be conducted in accordance with method 3240 of MIL-STD-750, except the output capacitor shall be omitted.

4.5.3 Independent transistor inspections. Inspections shall be performed on each transistor in the array.

4.5.4 Transistor-to-transistor resistance. The leads of each transistor shall be shorted together for this test. The resistance shall be measured between each transistor in the array.

* 4.5.5 Delta measurements. Delta measurements shall be as specified below:

Step	Inspection	MIL-STD-750		Symbol	Limit
		Method	Conditions		
1	Collector-base cutoff current	3036	Bias condition D, V_{CB} = -50 V dc	ΔI_{CB02} (1)	100 percent of initial value or ±8 nA dc, whichever is greater.
2	Forward current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -150 mA dc; pulsed see 4.5.1	Δh_{FE4} (1)	±25 percent change from initial reading.

(1) Devices which exceed the table I limits for this test shall not be accepted.

* 4.5.6 Displacement damage characterization. For RHA devices, each supplier shall perform a displacement damage characterization. The characterization shall demonstrate exposure versus data and does not indicate pass or fail criteria. The exposure shall be conducted in accordance with method 1017 of MIL-STD-750. The following details shall apply:

a. Samples may be taken from any wafer of the qualification lot.

b. As a minimum, testing shall be at 2E+12 n/cm^2 plus two additional fluence levels chosen by the manufacturer.

c. If the device degrades less than 5 percent of the specification at the highest fluence level, a single data point may be sufficient.

Alternate package options may be substituted for characterization. The displacement damage characterization data shall be made available from the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
		Method	Conditions		Min	Max	
	Subgroup 1 2/						
	Visual and mechanical examination	2071					
	Solderability 3/ 4/	2026	n = 15 leads, c = 0				
	Resistance to solvents 3/ 4/ 5/	1022	n = 15 devices, c = 0				
	Temp cycling 3/ 4/	1051	Test condition C, 25 cycles. n = 22 devices, c = 0				
	Hermetic seal 4/ Fine leak Gross leak	1071	n = 22 devices, c = 0				
	Electrical measurements 4/		Table I, subgroup 2				
	Bond strength 3/ 4/	2037	Precondition T_A = +250°C at t = 24 hours or T_A = +300°C at t = 2 hours. n = 11 wires, c = 0				
	Decap internal visual (design verification) 4/	2075	n = 1 device, c = 0				
	Subgroup 2						
	Thermal impedance 6/	3131	See 4.3.2	$Z_{\theta JX}$			°C/W
	Collector to base, cutoff current	3036	Bias condition D; V_{CB} = -60 V dc	I_{CBO1}		-10	µA dc
*	Emitter to base, cutoff current	3061	Bias condition D; V_{EB} = -5 V dc	I_{EBO1}		-10	µA dc
	Breakdown voltage collector to emitter	3011	Bias condition D; I_C = -10 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	-60		V dc
	Collector to base cutoff current	3036	Bias condition D; V_{CB} = -50 V dc	I_{CBO2}		-10	nA dc
*	Emitter to base cutoff current	3061	Bias condition D; V_{EB} = -4 V dc	I_{EBO2}		-50	nA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Forward-current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -0.1 mA dc	h_{FE1}	75		
Forward-current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -1.0 mA dc	h_{FE2}	100	450	
Forward-current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -10 mA dc	h_{FE3}	100		
Forward-current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -150 mA dc pulsed (see 4.5.1)	h_{FE4}	100	300	
Forward-current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -500 mA dc pulsed (see 4.5.1)	h_{FE5}	50		
Collector to emitter voltage (saturated)	3071	I_C = -150 mA dc; I_B = -15 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$		-0.4	V dc
Collector to emitter voltage (saturated)	3071	I_C = -500 mA dc; I_B = -50 mA dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$		-1.6	V dc
Base to emitter saturated voltage	3066	Test condition A; I_C = -150 mA dc; I_B = -15 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)1}$		-1.3	V dc
Base to emitter saturated voltage	3066	Test condition A; I_C = -500 mA dc; I_B = -50 mA dc; pulsed (see 4.5.1)	$V_{BE(sat)2}$		-2.6	V dc
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to base cutoff current	3036	Bias condition D; V_{CB} = -50 V dc	I_{CBO3}		-10	µA dc
Low temperature operation:		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = -10 V dc; I_C = -1.0 mA dc	h_{FE6}	50		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 4						
Small-signal short-circuit forward-current transfer ratio	3206	V_{CE} = -10 V dc; I_C = -1 mA dc; f = 1 kHz	h_{fe}	100		
Magnitude of small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = -20 V dc; I_C = -50 mA dc; f = 100 MHz	$\|h_{fe}\|$	2.0	8.0	
Open circuit output capacitance	3236	V_{CB} = -10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1 MHz	C_{obo}		8.0	pF
Input capacitance (output open-circuited)	3240	V_{EB} = -2.0 V dc; I_C = 0; 100 kHz ≤ f ≤ 1 MHz; see 4.5.2	C_{ibo}		30	pF
Turn-on time		See figure 13	t_{on}		45	ns
Turn-off time		See figure 14	t_{off}		300	ns
Transistor-to-transistor resistance		$\|V_{T-T}\|$ = 500 V dc; see 4.5.4	R_{T-T}	10^{10}		ohms
Subgroups 5 and 6						
Not applicable						

1/ For sampling plan see MIL-PRF-19500.
2/ For resubmission of failed subgroup 1, double the sample size of the failed test or sequence of tests. A failure in group A, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for JANS devices.
5/ Not required for laser marked devices.
6/ This test required for the following end-point measurements only:
Group B, subgroups 3, 4 and 5 (JANS).
Group B, step 1(JAN, JANTX, JANTXV).
Group C, subgroups 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection and end-point limits.

	Inspection 1/ 2/ 3/	MIL-STD-750 Method	MIL-STD-750 Conditions	Symbol	Limits Min	Limits Max	Unit
	Subgroup 1 4/						
	Neutron irradiation	1017	Neutron exposure V_{CES} = 0 V				
	Collector to base cutoff current	3036	Bias condition D; V_{CB} = -60 V dc	I_{CBO1}		-20	µA dc
*	Emitter to base cutoff current	3061	Bias condition D; V_{EB} = -5 V dc	I_{EBO1}		-20	µA dc
	Breakdown voltage collector to emitter	3011	Bias condition D; I_C = -10 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	-60		V dc
	Collector to base cutoff current	3036	Bias condition D; V_{CB} = -50 V dc	I_{CBO2}		-20	nA dc
	Emitter to base cutoff current	3061	Bias condition D; V_{EB} = -4.0 V dc	I_{EBO2}		-100	nA dc
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -0.1 mA dc	[h_{FE1}] 5/	[37.5]		
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -1.0 mA dc	[h_{FE2}]5/	[50]	450	
	Forward-current transfer ratio	3076	V_{CE} = -10V dc, I_C = -10 mA dc	[h_{FE3}] 5/	[50]		
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -150 mA dc; pulsed (see 4.5.1)	[h_{FE4}] 5/	[50]	300	
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -500 mA dc; pulsed (see 4.5.1)	[h_{FE5}] 5/	[25]		
	Collector to emitter voltage (saturated)	3071	I_C = -150 mA dc, I_B = -15 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)1}$		-0.46	V dc
	Collector to emitter voltage (saturated)	3071	I_C = -500 mA dc, I_B = -50 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)2}$		-1.84	V dc
	Base to emitter saturated voltage	3066	Test condition A, I_C = -150 mA dc, I_B = -15 mA dc, pulsed (see 4.5.1)	$V_{BE(sat)1}$		-1.50	V dc
	Base to emitter saturated voltage	3066	Test condition A, I_C = -500 mA dc, I_B = -50 mA dc, pulsed (see 4.5.1)	$V_{BE(sat)2}$		-3.00	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection and end-point limits – Continued.

	Inspection 1/ 2/ 3/	MIL-STD-750 Method	MIL-STD-750 Conditions	Symbol	Limits Min	Limits Max	Unit
	Subgroup 2						
	Steady-state total dose irradiation	1019	Gamma exposure V_{ECS} = -48 V Condition A,				
	Collector to base cutoff current	3036	Bias condition D; V_{CB} = -60 V dc	I_{CBO1}		-20	µA dc
*	Emitter to base cutoff current	3061	Bias condition D; V_{EB} = -5 V dc	I_{EBO1}		-20	µA dc
*	Breakdown voltage Collector to emitter	3011	Bias condition D; I_C = -10 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$	-60		V dc
	Collector to base cutoff current	3036	Bias condition D; V_{CB} = -50 V dc	I_{CBO2}		-20	nA dc
	Emitter to base cutoff current	3061	Bias condition D; V_{EB} = -4.0 V dc	I_{EBO2}		-100	nA dc
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -0.1 mA dc	[h_{FE1}] 5/	[37.5]		
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -1.0 mA dc	[h_{FE2}] 5/	[50]	450	
	Forward-current transfer ratio	3076	V_{CE} = -10V dc, I_C = -10 mA dc	[h_{FE3}] 5/	[50]		
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -150 mA dc; pulsed (see 4.5.1)	[h_{FE4}]] 5/	[50]	300	
	Forward-current transfer ratio	3076	V_{CE} = -10 V dc, I_C = -500 mA dc; pulsed (see 4.5.1)	]h_{FE5}] 5/	[25]		
	Collector to emitter voltage (saturated)	3071	I_C = -150 mA dc, I_B = -15 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)1}$		-0.46	V dc
	Collector to emitter voltage (saturated)	3071	I_C = -500 mA dc, I_B = -50 mA dc, pulsed (see 4.5.1)	$V_{CE(sat)2}$		-1.84	V dc
	Base to emitter saturated voltage	3066	Test condition A, I_C = -150 mA dc, I_B = -15 mA dc, pulsed (see 4.5.1)	$V_{BE(sat)1}$		-1.50	V dc
	Base to emitter saturated voltage	3066	Test condition A, I_C = -500 mA dc, I_B = -50 mA dc, pulsed (see 4.5.1)	$V_{BE(sat)2}$		-3.00	V dc


1/ Tests to be performed on all devices receiving radiation exposure.
2/ For sampling plan, see MIL-PRF-19500.
3/ Electrical characteristics apply to all device types unless otherwise noted.
4/ See 6.2.e herein.
5/ See method 1019 of MIL-STD-750 for how to determine [h_{FE}] by first calculating the delta (1/h_{FE}) from the pre and post-radiation h_{FE}. Notice that [h_{FE}] is not the same as h_{FE} and cannot be measured directly. The [h_{FE}] value can never exceed the pre-radiation minimum h_{FE} that it is based upon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) - for qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, subgroup 2 and 4.5.5 herein.	
Subgroup 2			45 devices c = 0
Intermittent life	1037	Intermittent operation life: V_{CB} = -10 - -30 V dc, 6,000 cycles. Adjust device current, or power, to achieve a minimum ΔT_J of +100°C.	
Electrical measurements		See table I, subgroup 2 and 4.5.5 herein.	
Subgroup 4			
Thermal impedance curves		See MIL-PRF-19500.	Sample size N/A
Subgroup 5			
Not applicable			
* Subgroup 6			
ESD	1020		
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	
* Subgroup 12			
Neutron Irradiation	1017	See 4.5.6	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.




NOTES:

1. Top curve is thermal runaway loci and cannot be used as a derate design curve since it exceeds the maximum ratings for this part. Operating under this curve using these mounting conditions assures the device will not have a thermal runaway. This is the true inverse of the worst case thermal resistance value extrapolated out to the thermal runaway point.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 5. Temperature-power derating ($R_{\theta JA}$) for 2N6987 (DIP14).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.




NOTES:

1. Top curve is thermal runaway loci and cannot be used as a derate design curve since it exceeds the maximum ratings for this part. Operating under this curve using these mounting conditions assures the device will not have a thermal runaway. This is the true inverse of the worst case thermal resistance value extrapolated out to the thermal runaway point.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 6. Temperature-power derating ($R_{\theta JA}$) for 2N6987U, (20 pin leadless chip).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.




NOTES:

1. Top curve is thermal runaway loci and cannot be used as a derate design curve since it exceeds the maximum ratings for this part. Operating under this curve using these mounting conditions assures the device will not have a thermal runaway. This is the true inverse of the worst case thermal resistance value extrapolated out to the thermal runaway point.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 7. Temperature-power derating ($R_{\theta JA}$) for 2N6988 (14 pin flat pack).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.




NOTES:

1. Top curve is thermal runaway loci and cannot be used as a derate design curve since it exceeds the maximum ratings for this part. Operating under this curve using these mounting conditions assures the device will not have a thermal runaway. This is the true inverse of the worst case thermal resistance value extrapolated out to the thermal runaway point.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curve chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

FIGURE 8. Temperature-power derating ($R_{\theta JC(AM)}$) for 2N6988 (14 pin flat pack epoxy mount).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance




NOTE: For response curve characteristics for a single chip while other chips are powered identically but independently, multiply the vertical axis thermal impedance values by 4.

FIGURE 9. Thermal impedance graph ($R_{\theta JA}$) for 2N6987 (DIP14).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance




NOTE: For response curve characteristics for a single chip while other chips are powered identically but independently, multiply the vertical axis thermal impedance values by 4.

FIGURE 10. Thermal impedance graph ($R_{\theta JA}$) for 2N6987U (20 pin leadless chip).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance




NOTE: For response curve characteristics for a single chip while other chips are powered identically but independently, multiply the vertical axis thermal impedance values by 4.

FIGURE 11. Thermal impedance graph ($R_{\theta JA}$) for 2N6988 (14 pin flat pack).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.


Maximum Thermal Impedance



NOTE: For response curve characteristics for a single chip while other chips are powered identically but independently, multiply the vertical axis thermal impedance values by 4.

FIGURE 12. Thermal impedance graph ($R_{\theta JC(AM)}$) for 2N6988 (14 pin flat pack epoxy mount).


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.



NOTES:

1. The rise time (t_r) and fall time (t_f) of the applied pulse shall be each ≤ 2.0 ns; duty cycle ≤ 2 percent; generator source impedance shall be 50 Ω.
2. Output sampling oscilloscope: Z_{in} ≥ 100 kΩ; C_{in} ≤ 12 pF; rise time ≤ 5.0 ns.

* FIGURE 13. Saturated turn-on switching time test circuit and waveform.



NOTES:

1. The rise time (t_r) and fall time (t_f) of the applied pulse shall be each ≤ 2.0 ns; duty cycle ≤ 2 percent; generator source impedance shall be 50 Ω.
2. Output sampling oscilloscope: Z_{in} ≥ 100 kΩ; C_{in} ≤ 12 pF; rise time ≤ 5.0 ns.

* FIGURE 14. Saturated turn-off switching time test circuit and waveform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

e. The complete Part or Identifying Number (PIN), see 1.5 and 6.4.


f. For acquisition of RHA designed devices, table II, subgroup 1 testing of group D is optional. If subgroup 1 testing is desired, it should be specified in the contract.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

6.4 PIN construction example.

6.4.1 Encapsulated devices. The PINs for encapsulated devices are constructed using the following form.



6.5 List of PINs.

6.5.1 PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for types 2N6987 (1)	PINs for types 2N6988 (1)
JAN2N6987	JAN2N6988
JAN2N6987U	JANTX2N6988
JANTX2N6987	JANTXV2N6988
JANTX2N6987U	JANTXVR2N6988
JANTXV2N6987	JANTXVF2N6988
JANTXV2N6987U	JANS2N6988
JANTXVR2N6987	JANS#2N6988
JANTXVF2N6987	
JANTXVR2N6987U	
JANTXVF2N6987U	
JANS2N6987	
JANS2N6987U	
JANS#2N6987	
JANS#2N6987U	

(1) The number sign (#) represents one of eight RHA designators available (M, D, P, L, R, F, G, or H).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.

* 6.6 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - SH
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS
Air Force - 19, 71

Preparing activity:
DLA - CC

(Project 5961-2025-051)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:19Z
Check the source to verify that this is the current version before use.