The documentation and process conversion measures necessary to comply with this revision shall be completed by 11 November 2020.

INCH-POUND

MIL-PRF-19500/731C
11 August 2020
SUPERSEDING
MIL-PRF-19500/731B
22 May 2015

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICES, DIODE, SILICON, SCHOTTKY,
DUAL DIE TYPES 1N7058CCU3, 1N7058CCU3C,
AND SINGLE DIE TYPE 1N7038U3,
QUALITY LEVELS JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for silicon, Schottky, dual and single die, power rectifier diodes for use in high frequency switching power supplies and resonant power converters. Four levels of product assurance (JAN, JANTX, JANTXV, and JANS) are provided for each encapsulated device.

1.2 Package outlines. The device package outlines are a metal lid (U3) or a ceramic lid (U3C) surface mount TO-276AA (SMD .5) package in accordance with figure 1 for all encapsulated device types.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25 °C.

Column 1	Column 2	Column 3	Column 4	Column 5		Column 6
Types	V_{RWM}	I_O (1) (2) T_C = +100 °C	I_{FSM} tp = 8.3 ms T_C = +25 °C	$R_{\theta JC}$ (2)	$R_{\theta JC}$ (3)	T_{STG} and T_J
	V dc	A dc	A (pk)	°C/W	°C/W	°C
1N7038U3	150	30	140 (2)	1.82		-65 to +150
1N7058CCU3 1N7058CCU3C	150	30	130 (2)	1.75	3.5	

(1) See temperature-current derating curves in figures 2 and 3.
(2) Entire package.
(3) Each diode.

1.4 Primary electrical characteristics.

a. $R_{\theta JC}$ = 1.82°C/W maximum for 1N7038U3 (figure 4).
b. $R_{\theta JC}$ = 1.75°C/W maximum entire package for 1N7058CCU3 and 1N7058CCU3C (figure 5);
$R_{\theta JC}$ = 3.5°C/W maximum each diode.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", "JANTXV" and "JANS".

1.5.2 Device type. The designation system for the device types of diodes covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The diodes of this specification sheet use the first number and letter symbols "1N".

1.5.2.2 Second number symbols. The second number symbols for the diodes covered by this specification sheet are as follows: "7038" and "7058".

1.5.3 Suffix symbols. The following suffix letters are incorporated in the PIN for this specification sheet.

1.5.3.1 Internal circuit. The suffix symbols (or lack thereof) that designate the internal circuit for the devices covered by this specification sheet are as follows:

Blank	No designator (blank) identifies a single die internal circuit configuration (type 1N7038 only).
CC	This designator identifies a dual die, common cathode internal circuit configuration (type 1N7058 only).

1.5.3.2 Package type. All devices are packaged in a TO-276AA (SMD .5) package of figure 1. The suffix symbols for the package types are as follows:

U3	The suffix symbols "U3" are used to designate device types that have a metal lid.
U3C	The suffix symbols "U3C" are used to designate device types that have a ceramic lid (1N7058 only).

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS


MIL-PRF-19500 – Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 – Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions				Symbol	Dimensions			
	Inches		Millimeters			Inches		Millimeters	
	Min	Max	Min	Max		Min	Max	Min	Max
BL	.395	.405	10.03	10.29	LS1	.150 BSC		3.81 BSC	
BW	.291	.301	7.39	7.65	LS2	.075 BSC		1.91 BSC	
CH (2)	.108	.124	2.74	3.15	LW1	.281	.291	7.14	7.39
CH (3)	.1195	.1335	3.035	3.390	LW2	.090	.100	2.29	2.54
LH	.010	.020	0.25	0.51	Q1	.030		0.76	
LL1	.220	.230	5.59	5.84	Q2	.030		0.76	
LL2	.115	.125	2.92	3.18					

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Dimension CH for metal lid TO-276AA (U3) packages.
3. Dimension CH for ceramic lid TO-276AA (U3C) packages.
4. Dimensions are in accordance with ASME Y14.5M.

FIGURE 1. Dimensions and configuration for TO-276AA package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 herein.

3.4.1 Polarity. Polarity and terminal configuration shall be in accordance with figure 1 herein.

3.4.2 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750 and herein. Where a choice of finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in tables I and II herein.

3.7 Marking. Marking shall be in accordance with MIL-PRF-19500 and herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II herein).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E inspection. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

4.3 Screening (quality levels JANS, JANTXV, and JANTX only). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurement	
	JANS level	JANTX and JANTXV levels
3b (1) (2)	Surge current (4.3.4)	Surge current (4.3.4)
3c (2)	Thermal impedance (see 4.3.2)	Thermal impedance (see 4.3.2)
3d	Avalanche energy test (see 4.3.3)	Avalanche energy test (see 4.3.3)
9, 10	Not applicable	Not applicable
11	V_{F1} and I_{R1}	V_{F1} and I_{R1}
12	See 4.3.1	See 4.3.1
13	Subgroup 2, of table I herein excluding thermal impedance; V_{F1} and I_{R1}; ΔV_{F1} = ±50 mV (pk); ΔI_{R1} = ±100 percent from the initial value or ±100uA, whichever is greater.	Subgroup 2, of table I herein excluding thermal impedance; V_{F1} and I_{R1}; ΔV_{F1} = ±50 mV (pk); ΔI_{R1} = ±100 percent from the initial value or ±100uA, whichever is greater.

(1) Surge testing shall precede thermal impedance.
(2) Thermal impedance and surge current shall be performed any time after screen 3a and before screen 13. Quality levels JANTX and JANTXV levels do not need to be repeated in screening verifications.

4.3.1 Power burn-in conditions. Burn-in shall be in accordance with test condition A of method 1038 of MIL-STD-750. The following conditions shall apply: V_R = 120 V dc; T_J = +125 °C.

4.3.2 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3101 or 4081 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{MD}. See table III, subgroup 4 herein.

4.3.3 Avalanche energy test. The avalanche energy test shall be performed in accordance with method 4064 of MIL-STD-750 using the circuit as shown on figure 6 or equivalent. The Schottky rectifier under test shall be capable of absorbing the reverse energy, as follows: I_{RM} = 170 mA, V_{RSM} = 150 V minimum.

4.3.4 Surge current. The surge current test shall be performed in accordance with condition A of method 4066 of MIL-STD-750. The following details shall apply: I_O = 0; $V_{RM(w)}$ = 0; I_{FSM} = see 1.3, column 4.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500, and table I herein. Electrical measurements (end-points) and delta requirements shall be in accordance with the applicable steps of table II herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in 4.4.2.1 for quality level JANS and 4.4.2.2 for quality levels JAN, JANTX, and JANTXV and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2, forward voltage test (V_{F1}) and reverse leakage test (I_{R1}) herein. Delta measurements shall be in accordance with table II herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

4.4.2.1 Quality level JANS (table E-VIA of MIL-PRF-19500).

Subgroup	Method	Condition
B4	1037	I_F = 2 A minimum for 2,000 cycles; ΔT_C = +85 °C.
B5	1038	Condition A, V_R = 120 V dc, T_J = +125 °C, t = 340 hours min; heat sinking allowed. This test shall be extended to 1000 on each JANS wafer lot.
B6	4081	Limit for thermal resistance for 1N7038U3 is 1.82 °C/W. Limit for thermal resistance for 1N7058CCU3 is 3.5 °C/W for each diode. Limit for thermal resistance for 1N7058CCU3C is 3.5 °C/W for each diode.

4.4.2.2 Quality levels JAN, JANTX, and JANTXV (table E-VIB of MIL-PRF-19500).

Subgroup	Method	Condition
B3	1037	I_F = 2 A minimum for 2,000 cycles; ΔT_C = +85 °C.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2, forward voltage test (V_{F1}) and reverse leakage test (I_{R1}) herein. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition
C2	2036	Not required.
C6	1037	I_F = 2 A minimum for 6,000 cycles; ΔT_C = +85 °C.
C6	1038	Condition A, V_R = 120 Vdc, T_J = +125 °C, t = 1000 hours minimum; (heat sinking allowed), for TX, TXV only.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-IX of MIL-PRF-19500, and table III herein. Delta measurements shall be in accordance with table II herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Dielectric withstanding voltage (DWV). The test for DWV shall be performed in accordance with test method 1016 of MIL-STD-750. The following details shall apply: V_R = 500 V dc; all leads shorted; measure from leads to case; the sample shall be n = 116, c = 0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/ 2/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance	3101	See 4.3.2	$Z_{\theta JC}$			°C/W
Forward voltage	4011	Condition B; pulsed test (see 4.5.1)	V_{F1}			
1N7038U3		I_F = 15A (pk)			.96	V dc
1N7058CCU3		I_F = 7.5A (pk)			1.05	V dc
1N7058CCU3C		I_F = 7.5A (pk)			1.05	V dc
Forward voltage	4011	Condition B; pulsed test (see 4.5.1)	V_{F2}			
1N7038U3		I_F = 30 A (pk)			1.18	V dc
1N7058CCU3		I_F = 15 A (pk)			1.20	V dc
1N7058CCU3C		I_F = 15 A (pk)			1.20	V dc
Reverse current	4016	Condition A or B	I_{R1}			
1N7038U3		V_R = 150 V			.12	mA dc
1N7058CCU3		V_R = 150 V			.02	mA dc
1N7058CCU3C		V_R = 150 V			.02	mA dc
Subgroup 3						
High temperature operation:		T_C = +125 °C				
Forward voltage	4011	Condition B; pulsed test (see 4.5.1)	V_{F3}			
1N7038U3		I_F = 15A (pk)			.75	V dc
1N7058CCU3		I_F = 7.5A (pk)			.72	V dc
1N7058CCU3C		I_F = 7.5A (pk)			.72	V dc
Forward voltage	4011	Condition B; pulsed test (see 4.5.1)	V_{F4}			
1N7038U3		I_F = 30 A (pk)			.92	V dc
1N7058CCU3		I_F = 15 A (pk)			.85	V dc
1N7058CCU3C		I_F = 15 A (pk)			.85	V dc
Reverse current	4016	Condition A or B	I_{R2}			
1N7038U3		V_R = 150 V			6.0	mA dc
1N7058CCU3		V_R = 150 V			7.0	mA dc
1N7058CCU3C		V_R = 150 V			7.0	mA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection − Continued.

Inspection 1/ 2/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 3 - continued						
Low temperature operation:		T_C = -55 °C				
1N7038U3		I_F = 15A (pk)			1.07	V dc
1N7058CCU3		I_F = 7.5A (pk)			1.06	V dc
1N7058CCU3C		I_F = 7.5A (pk)			1.06	V dc
Forward voltage	4011	Condition B, pulsed test (see 4.5.1)	V_{F6}			
1N7038U3		I_F = 30 A (pk)			1.26	V dc
1N7058CCU3		I_F = 15 A (pk)			1.23	V dc
1N7058CCU3C		I_F = 15 A (pk)			1.23	V dc
Subgroup 4						
Junction capacitance	4001	V_R = 5 V dc, f = 1 MHz, V_{SIG} = 50 mV (p-p)	C_J			
1N7038U3					340	pF
1N7058CCU3					130	pF
1N7058CCU3C					130	pF
Subgroup 5						
Not applicable						
Subgroup 6						
Surge current	4066	See 1.3, column 4 herein, ten surges each diode. 60 seconds between surges, (see 4.5.1).				
Electrical measurements		See table I, subgroup 2 herein.				
Subgroup 7						
Dielectric withstanding voltage 3/	1016	See 4.5.2.	I_{RES}		10	µA
Scope display evaluation	4023	Condition A, stable only.				
Electrical measurements		See table I, subgroup 2 herein.				

1/ For sampling plan, see MIL-PRF-19500.
2/ Electrical characteristics apply to all package styles and polarities.
3/ Not required for 1N7058CCU3C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

TABLE II. Delta measurements for groups B, C, and E. 1/ 2/ 3/ 4/ 5/ 6/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Forward voltage 1N7038U3 1N7058CCU3 1N7058CCU3C	4011	Condition B, pulsed (see 4.5.1) I_F = 15 A (pk) I_F = 7.5 A (pk)	ΔV_{F1}	±50 mV dc from initial reading.		
2.	Reverse current	4016	Condition A, V_R = 150 V	ΔI_{R1}	±100 pecent from initial reading or ±100µA whichever is greater.		
3.	Thermal impedance	3101	See 4.3.2	$Z_{\theta JX}$			

1/ Each individual diode.
2/ The delta measurements taken during group B inspection for quality level JANS (table E-VIA of MIL-PRF-19500) shall be as follows:
   a. In addition to the measurements specified for subgroup 4, the measurements of steps 1, 2, and 3 of this table shall also be taken.
   b. In addition to the measurements specified for subgroup 5, the measurements of steps 1 and 2 of this table shall also be taken.
3/ The delta measurements taken during group B inspection for quality levels JAN, JANTX, and JANTXV (table E-VIB of MIL-PRF-19500 shall be as follows:
   a. In addition to the measurements specified for subgroup 2, the measurements of steps 1, 2, and 3 of this table shall also be taken.
   b. In addition to the measurements specified for subgroup 3, the measurements of steps 1, 2, and 3 of this table shall also be taken.
   c. In addition to the measurements specified for subgroup 6, the measurements of steps 1 and 2 of this table shall also be taken.
4/ The delta measurements taken during group C inspection for all quality levels (table E-VII of MIL-PRF-19500) shall be as follows:
   a. In addition to the measurements specified for subgroups 2 and 3, the measurements of steps 1, 2, and 3 of this table shall also be taken for all levels.
   b. In addition to the measurements specified for subgroup 6, the measurements of steps 1, 2, and 3 of this table shall also be taken for all levels.
5/ The delta measurements taken during group E inspection for all quality levels (table E-IX of MIL-PRF-19500) shall be as follows:
   a. In addition to the measurements specified for subgroup 1, the measurements of steps 1, 2, and 3 of this table shall also be taken.
   b. In addition to the measurements specified for subgroup 2, the measurements of steps 1 and 2 of this table shall also be taken.
6/ Devices which exceed the table I limits for this test shall not be accepted.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) − for qualification and requalification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling (air to air)	1051	Test condition G, 500 cycles, -55 °C to +150 °C.	
Hermetic seal	1071	Fine and gross leak.	
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 2			45 devices, c = 0
Life test	1048	t = 1,000 hours, T_J = +125 °C, V_R = 80 percent rated voltage (see 1.3, column 2 herein).	
Electrical measurements		See table I subgroup 2 and table II herein.	
Subgroup 4			
Thermal impedance curves	3101	See MIL-PRF-19500.	
Subgroup 10 1/			n = 5, c = 0
Surge current	4066	Condition A, 100 surges of 8.3 ms superimposed on I_O. V_R = 0; I_O = 0 A pk half sine wave, continuous, T_A = +25 °C.	
1N7038U3 1N7058CCU3, 1N7058CCU3C		I_{FSM} = 140 A I_{FSM} = 130 A	
Electrical measurements		See table I subgroup 2 (V_F and I_R only).	

1/ Each individual diode.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 150 °C) and current rating specified (see 1.3 herein).
3. Derate design curve chosen at T_J ≤ 125 °C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤, 125 °C, and 110 °C to show current rating where most users want to limit T_J in their application.

FIGURE 2. Temperature-current derating curve (entire package) 1N7038U3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.



NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ 150 °C) and current rating specified (see 1.3 herein).
3. Derate design curve chosen at T_J ≤ 125 °C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125 °C, and 110 °C to show current rating where most users want to limit T_J in their application.

FIGURE 3. Temperature-current derating curve (for each leg) for 1N7058CCU3. and1N7058CCU3C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.




FIGURE 4. Thermal impedance 1N7038U3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.





FIGURE 5. Thermal impedance (for each leg), 1N7058CCU3 and 1N7058CCU3C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.



PROCEDURE:
1. With S open, adjust pulse width to test current of 1 amps across R_S.
2. Close S, verify test current with current sense.
3. Read peak output voltage (see 4.3.3).

NOTES:
1. The following input pulse details shall apply: V_G = 10 Volts, duty cycle ≤ 1 percent.
2. The following test circuit component values shall apply: L = 150 mH, Z_G = 50 ohms, R_{in} = 50 ohms, 1 watt, R_S = 0.1 ohms, 1 watt, T = 2N6768 (IRF350 or equivalent).
3. The supply voltage V_{CC} ≈ 10 volts.

FIGURE 6. Avalanche energy test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.


b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.5.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QPDSIS-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 PIN construction example. The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.

6.5 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level	PINs for devices of the "S" quality level
JAN1N7038U3	JANTX1N7038U3	JANTXV1N7038U3	JANS1N7038U3
JAN1N7058CCU3	JANTX1N7058CCU3	JANTXV1N7058CCU3	JANS1N7058CCU3
JAN1N7058CCU3C	JANTX1N7058CCU3C	JANTXV1N7058CCU3C	JANS1N7058CCU3C

6.6 Cross reference substitution list. A PIN for PIN replacement listing follows, and these devices are directly interchangeable.

Preferred PIN	Non-preferred PIN
JANS, JANTXV, JANTX, JAN1N7038U3	30LJQ150
JANS, JANTXV, JANTX, JAN1N7058CCU3	30CLJQ150
JANS, JANTXV, JANTX, JAN1N7058CCU3C	30CLJCQ150

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army − CR
Navy − EC
Air Force − 85
NASA − NA
DLA − CC

Review activity:
Air Force − 19

Preparing activity:
DLA − CC

(Project 5961−2020−045)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:17Z
Check the source to verify that this is the current version before use.