INCH-POUND

MIL-PRF-19500/736
5 July 2006

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, POWER DARLINGTON
TYPES 2N7572, 2N7573, AND 2N7574, JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon, power darlington transistors. Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (TO-61).

1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Types	P_T T_A = +25°C	P_T T_C = +25°C (1)	$R_{\theta JC}$ (2)	V_{CBO} and V_{CEX}	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}
	W	W	°C/W	V dc	V dc	V dc	A dc	A dc	°C
2N7572	6	140	1.25	350	300	4.0	2.5	20	-65 to +200
2N7573	6	140	1.25	400	350	4.0	2.5	20	-65 to +200
2N7574	6	140	1.25	450	400	4.0	2.5	20	-65 to +200

(1) See figure 2 for temperature-power derating curves.
(2) See figure 3 for thermal impedance graph.

Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/.

AMSC N/A FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics at T_C = +25°C.

Limits	h_{FE1} V_{CE} = 5 V dc I_C = 10 A dc (1)	h_{FE2} V_{CE} = 5 V dc I_C = 20 A dc (1)	$V_{BE(sat)}$ I_C = 15 A dc I_B = 1.2 A dc	$V_{CE(sat)}$[1] I_C = 15 A dc I_B = 1.2 A dc
			V dc	V dc
Min	75	50		
Max	500		2.6	1.5

Limits	$\|h_{fe}\|$	C_{obo}	Switching (2)			
	V_{CE} = 10 V dc I_C = 1 A dc f = 1 MHz	V_{CB} = 10 V dc I_E = 0 100 KHz < f < 1 MHz	t_d	t_r	t_s	t_f
		pF	µs	µs	µs	µs
Min	25	150				
Max		375	0.1	0.3	1.2	0.3

(1) Pulsed (see 4.5.1).
(2) See figure 4 (pulse response circuit).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.


DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.



TO-61

Ltr	Dimension				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A_1		.270		6.86	
CD	.570	.610	14.48	15.49	
CD_1	.610	.687	15.49	17.45	
CH	.325	.460	8.26	11.68	
HF	.667	.687	16.94	17.45	
HT	.090	.150	2.29	3.81	
OAH	.640	.875	16.26	22.22	4
PS	.340	.415	8.64	10.54	3, 6
PS_1	.170	.213	4.32	5.41	3, 6
SL	.422	.455	10.72	11.56	
SU		.090		2.29	
T	.047	.072	1.19	1.83	
T_1	.046	.077	1.17	1.96	
UD	.220	.249	5.59	6.32	

NOTES:
1. Dimensions are in inches, millimeters are given for general information only.
2. See NSB Handbook H28, “Screw-Thread Standards for Federal Services”.
3. The orientation of the terminals in relation to the hex flats is not controlled.
4. All three terminals.
5. Terminal spacing measured at the base seat only.
6. This dimension applies to the location of the center line of the terminals.
7. Terminal - 1, emitter; terminal - 2, base; terminal - 3, collector. all leads are isolated from the case.
8. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions (TO-61).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows:

V_{CEX} - Collector cutoff voltage (dc) with specified circuit between base and emitter.

3.4 Interface requirements and physical dimensions. The Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and figure 1 (TO-61 isolated).

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

4.3 Screening. Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurements	
	JANS level	JANTX and JANTXV levels
(1) 3c	Thermal Impedance (transient), Method 3131 of MIL-STD-750 (see 4.3.3).	Thermal Impedance (transient), Method 3131 of MIL-STD-750 (see 4.3.3).
9	I_{CEX1}	I_{CEX1}
11	I_{CEX1} and h_{FE2}; ΔI_{CEX1} = 100 percent of Initial value or 50 nA dc whichever is greater.	I_{CEX1} and h_{FE2}; ΔI_{CEX1} = 100 percent of initial value or 100 nA dc whichever is greater.
12	See 4.3.1	See 4.3.1
13	Subgroup 2 and 3 of table I herein: ΔI_{CEX1} = 100 percent of Initial value or 50 nA dc whichever is greater. Δh_{FE2} = ±15 percent of initial value.	Subgroup 2 of table I herein: ΔI_{CEX1} = 100 percent of Initial value or 100 nA dc whichever is greater. Δh_{FE2} = ±25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

4.3.1 Power burn-in conditions. Power burn-in conditions are: T_J = +175°C minimum, $V_{CB} \geq$ 30 V dc; T_A = +30°C maximum.

4.3.2 Insulation resistance test. Isolation resistance test conditions are as follows: Method 1016 of MIL-STD-750, short collector, emitter and base terminals together. Limit is 10^9 Ω minimum.

4.3.3 Thermal impedance. The thermal impedance and resistance measurements shall be performed in accordance with method 3161 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, (and V_H where appropriate). The thermal impedance limit used in 4.3, screen 3c and the subgroup 2 of table I shall comply with the thermal impedance graph on figure 3 (less than or equal to the curve value at the same t_H time) and shall be less than the process determined statistical maximum limit as outlined in method 3161. See group E, subgroup 4 herein. Measurement delay time (t_{MD}) ≤ 70 μs max.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA for JANS, table E-VIB for JAN, JANTX, and JANTXV, and in 4.4.2.1 and 4.4.2.2 herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with table II herein.

4.4.2.1 Group B inspection, table E-VIA (JANS) of MIL-PRF-19500

Subgroup	Method	Condition
B3	2037	Test condition A
B4	1037	2,000 cycles, adjust power or current to achieve a ΔT_J = +100°C.

4.4.2.2 Group B inspection, table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1027	For eutectic die attach: $V_{CB} \geq 30$ V dc; adjust P_T to achieve T_J = +175°C minimum; T_A = +30°C maximum
B3	1037	For solder die attach: 2,000 cycles, $V_{CB} \geq 100$ V dc.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with table II herein.

Subgroup	Method	Condition
C2	2036	Test condition A; weight = 10 pounds; time = 15 s.
C2	2036	Test condition D1; torque = 6 inch-ounce; time =15 s.
C2	2036	Stud torque , test condition D2; torque = 15 inch-pound; time = 15 s.
C5	3131	See 4.3.3, $R_{\theta JC}$ = 1.25°C/W.
C6	1027	For eutectic die attach: $V_{CB} \geq 100$ V dc; adjust P_T to achieve T_J = +175°C minimum; T_A = +30°C maximum, 1,000 hours minimum.
C6	1037	For solder die attach: 6,000 cycles, $V_{CB} \geq 100$ V dc.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E-IX of MIL-PRF-19500 and as specified in table III herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with table II herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1 Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3131	See 4.3.3	$Z_{\theta JX}$			°C/W
Collector to emitter breakdown voltage	3011	Bias condition D, I_C = 200 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$			
2N7572				300		V dc
2N7573				350		V dc
2N7574				400		V dc
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = -1.5 V dc	I_{CEX1}			
2N7572		V_{CE} = 350 V dc			0.1	mA
2N7573		V_{CE} = 400 V dc			0.1	mA
2N7574		V_{CE} = 450 V dc			0.1	mA
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = -1.5 V dc	I_{CEO}			
2N7572		V_{CE} = 300 V dc			0.1	mA
2N7573		V_{CE} = 350 V dc			0.1	mA
2N7574		V_{CE} = 400 V dc			0.1	mA
Collector to base cutoff current	3036	Bias condition D;	I_{CBO}			
2N7572		V_{CBO} = 350 V dc			0.1	mA
2N7573		V_{CBO} = 400 V dc			0.1	mA
2N7574		V_{CBO} = 450 V dc			0.1	mA
Emitter-base cutoff current	3061	Bias condition D, V_{EB} = 4 V dc	I_{EBO}		300	mA
Base emitter voltage	3066	Test condition A; I_C = 15 A dc; pulsed (see 4.5.1); I_B = 1.2 A dc	$V_{BE(SAT)}$		2.6	V dc
Collector to emitter saturated voltage	3071	I_C = 15 A dc; pulsed (see 4.5.1) I_B = 1.2 A dc	$V_{CE(SAT)1}$		1.5	V dc
Collector to emitter saturated voltage	3071	I_C = 20 A dc; pulsed (see 4.5.1) I_B = 1.2 A dc	$V_{CE(SAT)2}$		1.7	V dc
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 10 A dc; pulsed (see 4.5.1)	h_{FE1}	75	500	
Forward-current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 20 A dc; pulsed (see 4.5.1)	h_{FE2}	50		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High-temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = -1.5 V dc	I_{CEX2}			
2N7572		V_{CE} = 350 V dc			0.1	mA
2N7573		V_{CE} = 400 V dc			0.1	mA
2N7574		V_{CE} = 400 V dc			0.1	mA
Low-temperature operation :		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 5 V dc I_C = 10 A dc; pulsed (see 4.5.1)	h_{FE3}	20		
Subgroup 4						
Magnitude of common emitter small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 1 A dc; f = 1 MHz	$\|h_{fe}\|$	25		
Open capacitance (open circuit)	3236	V_{CB} = 10 V dc; I_E = 0; 100 kHz ≤ f ≤ 1.0 MHz	C_{obo}	150	375	pF
Pulse response:		V_{CC} = 300 V, I_C = 10 A I_{B1} = 0.5 A, $V_{BE(off)}$ = -5 V, tp = 50 us; see figure 4				
Pulse delay time			t_d		0.1	µs
Pulse rise time			t_r		0.3	µs
Pulse storage time			t_s		1.2	µs
Pulse fall time			t_f		0.3	µs
Subgroup 5						
Safe operating area (dc operation)	3051	T_C = +25°C, t = 1 s; 1 cycle; see figure 5				
Test 1 (All device types)		V_{CE} = 7.0 V dc; I_C = 20 A dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 5 - Continued						
Test 2 All device types		V_{CE} = 30 V dc; I_C = 1.5 A dc				
Test 3 (All device types)		V_{CE} = 100 V dc; I_C = 0.17 A dc				
Test 4 2N7572		V_{CE} = 300 V dc; I_C = 25 mA dc				
2N7573		V_{CE} = 350 V dc; I_C = 19 mA dc				
2N7574		V_{CE} = 400 V dc; I_C = 15 mA dc				
Inductive collector to emitter sustaining voltage (clamped at rated V_{CEO})	3053	T_A = +25°C, I_C = 2 A, I_{B1} = 0.1 A, I_{B2} = 0 A, L = 1 mH	$V_{CEO(sus)}$			
2N7572		Clamp voltage = 300 V dc		300		V dc
2N7573		Clamp voltage = 350 V dc		350		V dc
2N7574		Clamp voltage = 400 V dc		400		V dc
Inductive collector to emitter sustaining voltage (clamped at rated V_{CEO})	3053	T_A = +25°C, I_C = 2 A, I_{B1} = 0.5 A, $V_{BE(off)}$ = 1 V, L = 1 mH	$V_{CEX(sus)}$			
2N7572		Clamp voltage = 300 V dc		300		V dc
2N7573		Clamp voltage = 350 V dc		350		V dc
2N7574		Clamp voltage = 400 V dc		400		V dc
Subgroup 6						
Not applicable						
Subgroup 7						
Insulation resistance test	1016	See 4.3.2.	R_{ISO}	$10^9\Omega$		

1/ For sampling plan see MIL-PRF 19500.
2/ This test required for the following end-point measurements only:
Group B, subgroups 3, 4, and 5 (JANS).
Group B, subgroups 2 and 3 (JAN, JANTX, and JANTXV).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

TABLE II. Groups B, C, and E delta measurements. 1/ 2/ 3/ 4/ 5/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Collector to base cutoff current 2N7572 2N7573 2N7574	3036	Bias condition D V_{CE} = 350 V dc V_{CE} = 400 V dc V_{CE} = 450 V dc	ΔI_{CEX1}	100 percent of initial value or 100 nA whichever is greater.		
2.	Forward - current transfer ratio	3076	V_{CE} = 5 V dc; I_C = 20 A dc; pulsed (see 4.5.1)	Δh_{FE2}	± 25 percent change from initial reading.		
3.	Collector to emitter voltage (saturated)	3071	I_C = 15 A dc; I_B = 1.2 A dc, pulsed (see 4.5.1)	$\Delta V_{CE(sat)1}$	± 200 mV change from previously measured value.		


1/ Devices which exceed the group A limits for this test shall not be acceptable.
2/ The delta measurements for table E-VIA (JANS) of MIL-PRF-19500 are as follows:
   a. Subgroup 4, see table II herein, steps 1 and 2.
   b. Subgroup 5, see table II herein, steps 1 and 2.
3/ The delta measurements for table E-VIB (JAN, JANTX and JANTXV) of MIL-PRF-19500 are as follows:
   a. Subgroup 3, see table II herein, steps 1 and 2.
   b. Subgroup 6, see table II herein, step 2.
4/ The delta measurements for table E-VII of MIL-PRF-19500 are as follows:
   a. Subgroup 3, see table II herein, step 1.
   b. Subgroup 6, see table II herein, steps 1, 2 and 3.
5/ The delta measurements for table E-IX of MIL-PRF-19500 are subgroups 1 and 2, see table I herein, all steps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) - for qualification and re-qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Thermal shock glass strain	1056	0°C to +100°C, 100 cycles	
Hermetic seal Fine leak Gross leak	1071		
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	1,000 hours minimum, T_A = +150°C, V_{CB} = 80 percent of rated.	
Electrical measurements		See table I, subgroup 2 and table II herein.	
Subgroup 4			sample size N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 5			15 devices c = 0
Barometric pressure	1001	Condition C; see 1.3.	
Subgroup 6			3 devices
ESD	1020	Testing is not required for class 3 listing. Testing is required for a nonsensitive listing to prove capability.	
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition A for devices ≥ 400 V, condition B for devices < 400 V.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ +200°C) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ +150°C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ +125°C, and +110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 2. Temperature-power derating graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.



$R_{\theta JC}$ = 1.25 °C/W max.

FIGURE 3. Thermal impedance graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.




FIGURE 4. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.




FIGURE 5. Maximum safe operating area graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - MI

Preparing activity:
DLA - CC

(Project 5961-2005-008)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:21Z
Check the source to verify that this is the current version before use.