NOT MEASUREMENT SENSITIVE


MIL-B-3628/84A
30 July 1993
SUPERSEDING
MIL-B-3628/84
12 September 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED PISTOL SHOT, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL:
- PENDANT: Gilding Metal or Red Brass
- SUSPENSION BAR: Gilding Metal or Red Brass
- DEVICE: Gilding Metal

FINISH:
- PENDANT: Gold Plated, Matte Finish, Highlights and Rim Highly Polished and shall match TIOH Metal Finish Chip Number 8. REVERSE: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
- SUSPENSION BAR: Gold plated, Matte Finish, Highlights and Rim Highly Polished and shall match TIOH Metal Finish Chip Number 8. REVERSE: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
- DEVICE: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:25Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

PENDANT:

HEIGHT (Overall): 1-1/2 inches (3.81 cm) (REF)
WIDTH (Overall): 1-9/32 inches (3.25 cm (REF)
THICKNESS (Edge): 0.095 inch ± 0.005 inch (0.241 cm ± 0.012 cm)

SUSPENSION BAR:

HEIGHT (Overall): 11/32 inch (0.87 cm) (REF)
WIDTH (Overall): 1-13/16 inches (4.60 cm) (REF)
THICKNESS (Edge): 0.075 inch ± 0.005 inch (0.190 cm ± 0.012 cm)

DEVICE:

HEIGHT: 5/8 inch (1.59 cm) (REF)
WIDTH: 5/8 inches (1.59 cm) (REF)
THICKNESS: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-1/4 inches ± 1/32 inch (3.81 cm ± 0.08 cm) apart.

5. Lugs for the suspension bar and pendant shall be equidistant from each end and 7/8 inch ± 1/64 inch (2.22 cm ± 0.04 cm) on center. The lugs shall be fabricated from gold plated wire with a diameter of 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm). Lugs shall be hard soldered to the pendant or bar.

6. Links shall be fabricated from gold plated wire with a nominal diameter of 0.050 inch (0.127 cm). The overall dimension of the links shall be 1/4 inch (0.64 cm) in length and 7/32 inch (0.56 cm) in width.

7. The target shall be superimposed and secured to the pendant in the location shown using soft solder.

Custodian:
Army - IH
Air Force - 11

Preparing activities:
Army - IH

Review activities:
Air Force - 82, 99
DLA - CT

(Project No. 8455-0693)

User activities:
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:25Z
Check the source to verify that this is the current version before use.