NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/85B
15 November 1996
SUPERSEDING
MIL-B-3628/85A
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, EXCELLENCE IN COMPETITION, RIFLEMAN, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL:

PENDANT:
-1: Gilding Metal
-2: Gilding Metal or Red Brass

SUSPENSION BAR:
-1: Gilding Metal
-2: Gilding Metal or Red Brass

DEVICE:
-1, -2: Gilding Metal

DASH NO.
-1: Bronze, 1st Award
-2: Silver, 2nd Award

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:26Z
Check the source to verify that this is the current version before use.

FINISH:
  PENDANT:
    -1: Oxidized, Relieved, Lacquered Front, Back and Edges.
    -2: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
  SUSPENSION BAR:
    -1: Oxidized, Relieved.
    -2: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
  DEVICE:
    -1: Hard Enameled, Oxidized, Relieved.
    -2: Hard Enameled, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:
  PENDANT:
    DIAMETER: 1-19/32 inches (4.05 cm) (REF)
    THICKNESS (Edge): 0.095 inch ± 0.005 inch (0.241 cm ± 0.012 cm)
  SUSPENSION BAR:
    HEIGHT (Overall): 11/32 inch (0.87 cm) (REF)
    WIDTH (overall): 1-9/32 inches (3.25 cm) (REF)
    THICKNESS (Edge): 0.075 inch ± 0.005 inch (0.190 cm ± 0.012 cm)
  DEVICE:
    TARGET:
      HEIGHT: 3/8 inch (0.95 cm) (REF)
      WIDTH: 3/8 inch (0.95 cm) (REF)
      THICKNESS: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)
    COAT OF ARMS:
      HEIGHT: 5/18 inch (1.59 cm) (REF)
      WIDTH: 3/8 inch (0.95 cm) (REF)
      THICKNESS: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Blue	18
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-1/4 inches ± 1/32 inch (3.81 cm ± 0.08 cm) apart.

5. Lugs for the suspension bar and pendant shall be equidistant from each end and 7/8 inch ± 1/64 inch (2.22 cm ± 0.04 cm) on center. The lugs shall be fabricated from bronze wire for Dash No. -1 and nickel plated wire for Dash No. -2 with a diameter of 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm). Lugs shall be hard soldered to the pendant or bar.

6. Links shall be fabricated from nickel plated wire for Dash No. -2 and copper wire for Dash No. -1 with a nominal diameter of 0.050 inch (0.127 cm). The overall dimension of the links shall be 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and 7/32 inch ± 1/64 inch (0.56 cm ± 0.04 cm)) in width.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:26Z
Check the source to verify that this is the current version before use.

7. The target and coat of arms shall be superimposed and secured to the pendant in the location shown using soft solder.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:26Z
Check the source to verify that this is the current version before use.