NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/92A
15 November 1996
SUPERSEDING
MIL-B-3628/92
23 August 1994

DETAIL SPECIFICATION SHEET

BADGE, OCCUPATIONAL, INTELLIGENCE, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MASTER **SENIOR** **BASIC**

DASH NO.
-1: Basic, Regular Size
-2: Senior, Regular Size
-3: Master, Regular Size

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT (Overall):
-1: 3/4 inch (1.91 cm) (REF)
-2: 1-1/16 inches (2.70 cm) (REF)
-3: 1-3/16 inches (3.02 cm) (REF)
WIDTH (Overall): 1-5/8 inches (4.13 cm)
THICKNESS (At Thickest Point): 0.120 inch ± 0.010 inch (0.304 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:29Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. The attaching device shall be prong and clutch type. The prongs shall be located at each intersection of the horizontal center line of the badge and the center of the wreath.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:29Z
Check the source to verify that this is the current version before use.