MILITARY SPECIFICATION

ANTIDOTE, NERVE AGENTS, INJECTOR

This interim amendment is issued for use by Defense Personnel Support Center, with Military Specification MIL-A-37251 dated 30 December 1976.

Page 1

2.1 Applicable documents. Add the following Federal Specification: "PPP-C-186 - Containers, Packaging and Packing For Drugs, Chemicals, and Pharmaceuticals."

Page 6

3.7 Rough handling and safety mechanism. In line 6, delete "20.00 ± 0.25 lbs." and substitute "20 to 22 lbs".

3.10 Accelerated aging. In line 3, delete "$70^{o} \pm 5^{o}$ F for 24 hours" and substitute: "$72^{o} \pm 7^{o}$ F for at least one hour".

Page 7

3.12.1 Label information. In line 8, delete "(Yellow on Black)" and substitute "(Black on Brown)". Add the following sentences: "The immediate container label may bear the following: 'Caution New Drug Limited By Federal Law To Investigational Use Only'. In addition, the label may bear the trade name and patent number."

Page 8

4.2.1.3 Lot for Water for Injection. Add the following sentence: "As an alternate the water shall be filtered within eight (8) hours after removal from the heated recirculating water for injection system".

Page 9

4.2.2.2 For tests. Add the following sentence: "In addition, ten (10) extra injectors shall be included in 4.2.4.4 for 20 lb load application only."

4.2.3.1 For examination. At the end of tables III and IV, add the following sentence: "Where possible the sample shall be used for two or more tests."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:17Z
Check the source to verify that this is the current version before use.

Page 10

4.2.4 Tests. In line 2, change "70° F ± 5° F" to 72° F ± 7° F."

Page 11

4.2.4.3 Needle length after medication is dispensed. Add the following sentence: "As alternate, the gauging of the needle on limit guage for length shall be permitted."

4.2.4.4 Rough handling and safety mechanism. In lines 6 and 7, delete "20.00 ± 0.25 lb" and substitute "not less than 20 lb to not more than 22 lb.".

4.2.5.1 Benactyzine hydrochloride. Under "Reagents" delete "Sodium bicarbonate solution" and substitute "Sodium bicarbonate or sodium carbonate solution."

Page 13

4.2.5.1 Benactyzine hydrochloride. Under "Procedure" delete the second sentence entirely and substitute: "Add 1 ml of a 7 percent sodium bicarbonate or sodium carbonate solution to assure a pH of 10 in the vial."

Page 22

5.1.1 Level A. Add the following sentence: "As an alternate to the leakage test in MIL-P-116 the following test shall be employed:

1. Remove finished injector from the bag by cutting the bag along the fold which forms the bottom of the bag.
2. Pressurize the inside bag with at least 2 psi of air.
3. Hold the bag under water and observe for leakage.

Sampling for this alternate test shall be conducted in accordance with MIL-STD-105, level S-4, using an AQL of 4.0.

Page 23

5.3.3 Exterior container. Add the following statement: "NOTE: The unrefrigerated shipment time shall be not more than 12 days (288 hours). Paragraphs 3.1.1, 5.5.4.1.1, 5.5.4.1.2, 5.5.5 and 5.5.6.2 of PPP-C-186 are applicable. The injectors may be out of the storage range of 2° to 8° C when inprocess testing is necessary for production inspection procedures but the filled cartridges and final injectors are to be stored as required in the above applicable PPP-C-186 paragraphs.

Preparing activity:
Defense Logistics Agency - DM

Project No. 6505-1979

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:17Z
Check the source to verify that this is the current version before use.