MIL-A-13325A(Ord)
2 February 1960
SUPERSEDING
MIL-A-13325(Ord)
22 March 1954

MILITARY SPECIFICATION

ADAPTER, TELESCOPE: M9A1

1. SCOPE

1.1 This specification covers one type of telescope adapter hereinafter referred to as "adapter". The adapter forms a part of the Sightunit: M34 Series.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification:

SPECIFICATIONS

Military

MIL-A-12757	Adapter, Telescope M9 Series; Packaging of
MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking of U. S. Military Property

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

DRAWINGS

Ordnance Corps

F7691596	Azimuth Test Fixture
F8229250	Adapter (Test Fixture)
F8244830	Adapter, Telescope: M9A1
IEL-8244830	Index of Inspection Equipment List
LSQAP-8244830	Supplementary Quality Assurance List

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS.

3.1 Production model.- At the beginning of production one adapter, representative of production, shall be made available to the government to determine if the adapter meets all requirements of this specification.

3.2 Materials.- Materials shall be in accordance with drawings, material specifications, and general specifications forming a part of this specification.

3.3 Design and construction.- The adapter shall be manufactured in accordance with Drawing F8244830, "Adapter, Telescope: M9A1," and drawings pertaining thereto. The requirements of this specification are detailed only to the extent considered necessary to obtain the desired mechanical characteristics, performance and permanence to insure inherent quality and performance capabilities prior to final acceptance by the Government.

3.4 General specifications.- The contractor shall be responsible for adherence to and compliance with the following requirements of Specification MIL-F-13926:

(a) Order of Precedence
(b) Protective Finished Surfaces
(c) Special Accuracy
(d) Finish Painting and Protective
(e) Workmanship

3.5 Environmental.

3.5.1 Operating temperature.- The adapter shall meet the applicable requirements of 3.9 while exposed to, and thermally stabilized, at ambient temperatures of plus 150 degrees and minus 40 degrees Fahrenheit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

3.5.2 Vibration.- The adapter shall be vibrated in a vertical plane at a constant frequency of 30 cycles per second with an amplitude of 1/16 inch (1/8 inch maximum excursion) for a period of 5 minutes plus or minus 15 seconds. Subsequent to vibration there shall be no loose or damaged parts and the adapter shall meet the following performance requirements of this specification.

3.6 Accuracy.- With the mounting surface of the adapter in a horizontal plane, the following requirements shall be met.

3.6.1 Plumb travel.- The axis of the telescope holder assembly shall track a plumb line within plus or minus 0.75 mil throughout the total movement of the assembly.

3.6.2 Elevation accuracy.- With the elevation indexes of the holder assembly in coincidence, the axis of the bore of the holder assembly shall be horizontal within plus or minus 1.0 mil. Tightening the elevation wing nut shall secure the holder at any position in elevation.

3.6.3 Open sight.- The line of sight of the open sight shall be parallel to the axis of the bore of the holder assembly within 10 mils, when the elevation indexes are in coincidence.

3.6.4 Azimuth travel.- With the line of sight through the axis of the bore of the holder assembly horizontal and coincident with a horizontal target line, the line of sight shall not deviate from the target line by more than 0.7 mil (total spread of 1.4 mil) when the holder assembly is rotated through 6400 mils by rotation of the aximuth micrometer knob.

3.6.5 Backlash.- Backlash in the azimuth worm mechanism shall not exceed 0.5 mil.

3.6.6 Azimuth error.- Errors in any azimuth reading including backlash shall not exceed 1.5 mil.

3.6.7 Elevation jump.- Displacement between a line of sight through the axis of the bore of the holder assembly, and a horizontal target line shall not exceed 0.5 mil when reversing the azimuth motion of the holder assembly by rotation of the azimuth micrometer knob.

3.7 Scales and indexes.

3.7.1 Micrometer scale.- The micrometer scale shall indicate zero when any graduation of the azimuth scale is in coincidence with its index.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

3.7.2 Azimuth scale.- Release of the azimuth scale wing screw lock shall release the azimuth scale for rotation to any resetting position. Securing the wing screw lock shall secure the scale to the adapter body.

3.7.3 Resetting micrometer scale.- Depressing the button in center of the micrometer knob shall release the micrometer scale, allowing the scale to be slipped. Release of the button shall secure the scale to the micrometer knob assembly, allowing no slippage between the knob and the scale.

3.7.4 Adjustable index.- The adjustable index of the micrometer knob assembly shall not shift position during resetting of the micrometer scale.

3.8 Azimuth mechanism.- Disengagement of the azimuth worm shall allow 6400 mils free rotation of the holder assembly.

3.9 Operability.

3.9.1 Azimuth micrometer knob.- The running torque required to rotate the azimuth micrometer knob shall not exceed 5 pound inches at standard ambient temperature (plus 60 degrees to 90 degrees Fahrenheit) and shall not exceed the value obtained at standard ambient temperature by more than 2 pound inches when subjected to extreme temperatures of 3.5.1.

3.9.2 Scales and indexes.- When the locking devices of the azimuth micrometer scale, adjustable index, and azimuth scale are released, the respective scale or index shall be mechanically operable when subjected to the extreme temperatures of 3.5.1.

3.9.3 Holder assembly.- With the worm disengaged and the elevation lock released the holder assembly shall be operable in elevation and azimuth when subjected to the extreme temperatures of 3.5.1.

3.10 Identification marking.- Identification marking unless otherwise specified shall be in accordance with Standard MIL-STD-130.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.1 Contractor inspection.- Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order.

4.1.1 Contractor's quality assurance system.- The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies under this contract. A current written description of the system shall be submitted to the contracting officer prior to initiation production. The written description will be considered acceptable when it provides:

(a) The quality assurance required by the applicable drawings and specifications listed in the contract or order.
(b) Contractor's quality standards of acceptability.
(c) Procedure for continually evaluating product quality.
(d) Procedure for continually reporting evidence of actual product quality.
(e) Measures for preventing any significant departure of product quality from standards.

4.1.1.1 The contractor will not be restricted to the inspection station to or the method of inspection listed provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute as to whether or not certain procedures of the system provide equal assurance, the comparable procedure of this specification shall be used. The contractor shall notify the Government of, and obtain approval for, any change to the written procedure that might affect the degree of assurance required by this specification or other documents referenced herein.

4.1.2 Government verification.- All quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of (a) surveillance of the operations to determine whether the practices, methods, and procedures of the written inspection plan are being properly applied, and (b) Government product inspection to measure quality of product offered for acceptance. Deviation from the prescribed or agreed-upon procedures, or instances of poor practices which might have an affect upon the quality of the product, will immediately be called to the attention of the contractor. Failure of the contractor to promptly correct deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to prescribed criteria

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

has been demonstrated. To avoid interference with operations, the contractor will designate a responsible official or officials to whom the Government inspector will report such instances.

4.2 Production model.

4.2.1 Unless otherwise specified in the contract, one unit taken from the production run shall be tested by the contractor under the surveillance of the Government.

4.2.1.1 These tests shall be conducted at the contractor's facility or Government approved laboratory using test equipment designed or procured for use on the remaining items.

4.2.1.2 The model shall meet all the requirements of this specification using the inspection method prescribed herein.

4.2.1.3 Disposition of rejected production model.- Should the production model fail to pass the test for Government acceptance, the contractor shall cease those operations which are causing rejectable material and make the necessary corrections. When corrections have been made, a new production model shall be tested by the contractor under the surveillance of the Government. Operations causing rejections shall not be resumed until a production model has successfully passed all inspections specified.

4.3 Inspection provisions.

4.3.1 Inspection of components.- Inspection requirements for component parts and subassemblies are contained herein and on Supplementary Quality Assurance Provisions (SQAP) listed on Supplementary Quality Assurance Provisions List, LSQAP-8244830.

4.3.1.1 The contents of SQAP shall represent the minimum inspection requirements and shall be the basis for acceptance or rejection by lot, of those components covered by a SQAP. The Government reserves the right, however, to inspect for the requirements of all drawings and specifications, and to reject individual non-conforming items.

4.3.1.2 Contractor's inspection.- Contractor inspection for all components not covered by SQAP shall be in accordance with inspection procedures of the written inspection plan required by 4.1.1. The plan shall include procedures for checking all positional and functional characteristics shown on the drawings which indicate precision requirements that have a bearing on the functional accuracy and performance of Adapter, Telescope, M9A1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.3.2 Control of materials.- Materials shall be tested to determine conformance to contractually applicable specifications. Such tests may be conducted in the prime contractor's or subcontractor's facilities, or in other suitably equipped laboratories. The test results shall be available to the Government inspector for review. Certified test reports, identifiable with the material, may be accepted in lieu of repeated tests. The Government reserves the right, in any case, to require retests to assure that the materials are acceptable.

4.3.3 Lot formation.- Unless otherwise specified by the contracting officer, or his representative, inspection lot sizes and lot formation shall be in accordance with Standard MIL-STD-105.

4.3.3.1 Acceptance tests.- The classification of defects in Tables I and II shall constitute the minimum inspection requirements to be performed by the contractor prior to acceptance or rejection of the adapter by lot. The Government reserves the right, however, to inspect for any applicable requirement, and to reject individual non-conforming items.

4.3.3.2 Disposition of rejected lots.- Rejected lots shall be screened for all defective characteristics. After corrections have been made and the Government inspector informed of the corrective action taken, the lot shall be resubmitted for acceptance as outlined in Standard MIL-STD-105.

TABLE I - CLASSIFICATION OF DEFECTS

For Normal Inspection use Level L7, and Sampling Plan Table IV-A of Standard MIL-STD-105

AQL value is expressed in percent defective.

MAJOR: AQL 4.0%	Req't Par.	QA Par.	Test Method
1. Operating temperatures	3.5.1	4.4.1 4.4.4	Device, Special Testing (DST)
2. Vibration	3.5.2	4.4.2	DST-Standard Measuring Equipment (SME)-Visual-Tactile

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

TABLE II - CLASSIFICATION OF DEFECTS

For Normal Inspection use Level II, and Sampling Plan Table IV-A of Standard MIL-STD-105

For Reduced Inspection use Level I, and Sampling Plan Table IV-A of Standard MIL-STD-105

AQL value is expressed in percent defective.

MAJOR: AQL 2.5%	Req't Par.	QA Par.	Test Method
1. Completeness of assembly	Per dwg	4.4.5	Visual
2. Performance	3.6	4.4.3.3	(DST)
3. Plumb travel	3.6.1	4.4.3.4	DST
4. Elevation accuracy	3.6.2	4.4.3.5	DST
5. Open sight	3.6.3	4.4.3.6	Visual
6. Azimuth travel	3.6.4	4.4.3.7	DST
7. Backlash	3.6.5	4.4.3.8	Visual
8. Azimuth error	3.6.6	4.4.3.9	DST
9. Elevation jump	3.6.7	4.4.3.10	DST
10. Micrometer scale	3.7.1	4.4.3.11	Visual
11. Azimuth scale	3.7.2	4.4.3.12	Visual
12. Resetting micrometer scale	3.7.3	4.4.3.13	Tactile
13. Adjustable index	3.7.4	4.4.3.14	Visual
14. Azimuth mechanism	3.8	4.4.3.15	Tactile
15. Identification marking	3.10	4.4.6	Visual

4.3.4 Inspection equipment.

4.3.4.1 Contractor provisions.- Unless otherwise specified in the contract, the contractor shall provide and properly utilize all gaging, measuring, and testing equipment of the required accuracy for the performance of all inspection examinations and tests required to be performed by the contractor under this contract. The contractor shall be responsible for the maintenance of the equipment including surveillance, calibration, and rehabilitation, on a regularly scheduled basis, and shall have available, all calibration equipment and other instrumentation essential for calibration and certification of the inspection equipment. The contractor also shall maintain records of inspection equipment surveillance and calibration, and shall make these records available for review by the Government. The Government reserves the right to certify inspection equipment, and to use it for Government verification inspection or acceptance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.3.4.2 Government provisions.- Test equipment listed on IEL-8244830, when available, will be used for Government product inspection (reference 4.1.2(b)), and to settle disputes (reference 4.1.1). Drawing of this equipment will be furnished the contractor for informational purposes.

4.3.4.3 Accuracy requirements.- Inspection equipment which incorporates features for measuring values or sizes, established by product requirements, shall be capable of measuring these values within an accuracy of ten percent of the specified tolerance. In cases where the ten percent accuracy imposes impractical or very difficult design and fabrication problems, or results in a test equipment cost factor which is exorbitant in relation to the cost and application of the product to be inspected, the Government shall be expeditiously advised in order that necessary appropriate action can be taken.

4.4 Test methods and procedures.

4.4.1 Operating temperatures.- The test shall consist of exposing the adapter to the temperatures indicated in 3.5.1 by means of a cold chamber and an oven capable of maintaining these temperatures until the units under test are thermally stabilized. While at these temperatures, the test for the requirements of 3.9:1 shall be made by means of a commercial torque wrench and an adapter.

4.4.2 Vibration.- The adapter shall be rigidly mounted in its normal operating position on a vibrating machine capable of producing a vertical motion at the frequency and amplitude specified. The unit shall then be vibrated in accordance with the requirements specified in 3.5.2. Subsequent to vibration, the adapter shall be subjected to a visual and tactile inspection for damage, and meet all performance requirements of this specification.

4,4.3 Performance tests.- Performance tests are accomplished by means of a special testing device and adapter. These fixtures are depicted on Drawings, F7691596, Azimuth Test Fixture and F8229250, Adapter listed on IEL-8244830.

4.4.3.1 Azimuth test fixture.- The fixture provides the means for azimuth movement in a horizontal plane, and also provides the means for attaching and locating the adapter fixture.

4.4.3.2 Adapter fixture.- The fixture provides the means for locating and securing the telescope adapter in a horizontal plane.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.4.3.3 Performance tests set-up.- The set-up for performance tests shall be made by cross leveling the azimuth test fixture by means of a ten second bench level. The adapter fixture secured to the mounting plate of the azimuth fixture shall be cross leveled by means of a ten second bench level. In this position, with the telescope adapter secured in place on the test fixture, the mounting surface of the adapter will be in a horizontal plane as required in 3.6.

4.4.3.4 Plumb travel.- A target for checking the plumb travel of the telescope holder assembly shall be a plumb line placed approximately fifteen feet from the special testing device and in alinement with a collimating telescope positioned in the telescope holder. A mil block chart located at the top or bottom of the plumb line will be used to determine if the line of sight of the telescope will track plumb within the tolerance specified in 3.6.1. A peep sight with an approximate 1/16 inch aperture placed over the eyepiece of the telescope will assist the observer's eye to determine conformance with the requirements specified in 3.6.1.

4.4.3.5 Elevation accuracy.- Elevation accuracy shall be checked with the same set-up as used for the plumb travel test of 4.4.3.4. Prior to performing the test, the elevation wing nut shall be loosened to relieve the pressure on the clamping screw, then elevate and depress the holder assembly through its full movement. At various positions of the movement, the wing nut shall be tightened to determine that there is sufficient clamping action to firmly hold the holder assembly in position to comply with the specified requirement of 3.6.2. In addition to the test set-up, a horizontal zero mark shall be located on a wall chart in back of the plumb line and in a horizontal plane with the optical line of sight of the elbow telescope of the M62 series, or equivalent. A mil block located above the line and one below the line shall indicate the accuracy for this test. With the adapter located on the special testing device, and with the elevation indexes of the holder assembly in coincidence, the zero line of the telescope shall correspond with a zero mark on the wall target. Deviation shall be read on the mil blocks to determine conformance with the specified requirement of 3.6.2.

4.4.3.6 Open sight.- The open sight test shall be checked with the same set-up as used above. In addition, the wall chart shall have a ten mil radius circle the center of which shall correspond to the center of the open sight. With the telescope focused on the line of sight mark, the open sight shall read within the limits of the circle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.4.3.7 Azimuth travel.- Azimuth travel test shall be checked with set-up in 4.4.3.5. In addition, with the aid of a .7 mil block located above, and one below centrally located on the horizontal line on the wall chart in back of the plumb line, shall indicate the tolerance for this test. With the telescope secured in the holder, the intersection of the reticle crosslines shall optically be brought into coincidence with the intersecting point on the horizontal line. The test shall consist of checking the line of sight of the telescope at 6400 mils of azimuth movement in a horizontal plane while simultaneously rotating the special testing device through 6400 mils in the opposite direction. The deviation of the horizontal optical line of sight in a vertical plane shall not exceed the requirements of 3.6.4 as gaged on the mil blocks.

4.4.3.8 Backlash.- Backlash can be measured by means of the micrometer reading of the adapter being tested. Backlash shall be checked at positions at which accuracy readings are taken. At each position checked, the instrument being tested shall be brought to the setting first by a clockwise and then by a counterclockwise rotation of the azimuth micrometer knob. The difference between the readings of the micrometer at each direction shall be considered as backlash, and shall not exceed the tolerance of 3.6.5.

4.4.3.9 Azimuth error.- Azimuth error test shall be checked with the same set-up employed in the azimuth travel test of 4.4.3.7. With the scales of the instrument and azimuth fixture indicating zero and the optical line of sight level, readings shall be taken at different settings through the 6400 mil scale and the deviation shall not exceed the requirements of 3.6.6.

4.4.3.10 Elevation jump.- To check elevation jump, the same set-up as in 4.4.3.7 shall be employed, except that a .5 mil tolerance block shall be used. Optically, the horizontal line of sight shall be in coincidence with the horizontal zero mark on the wall chart. Displacement reading from zero position shall be taken by simultaneously rotating the azimuth micrometer knob in one direction and then in reverse. The deviation of the horizontal line in a vertical plane shall not exceed the requirements of 3.6.7.

4.4.3.11 Micrometer scale.- Depress the button in the micrometer knob to allow the telescope holder assembly to be manually rotated to any setting of a graduation of the azimuth scale in coincidence with its index. Releasing the button, rotate the azimuth worm knob to coincide the zero graduation of the azimuth micrometer with its index. Observe the azimuth scale to determine conformance with the requirements of 3.7.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.4.3.12 Azimuth scale.- The test shall be performed manually in accordance with the requirements specified in 3.7.2. When the wing screw lock is made secure, there shall be sufficient clamping action to firmly hold the scale at all positions.

4.4.3.13 Resetting micrometer scale.- Resetting of micrometer scale shall be tested manually in accordance with the requirements specified in 3.7.3 for operability. Sufficient pressure shall be applied to the button thereby allowing the scale to be manually rotated with a free movement, and when released, the scale shall hold firmly in position.

4.4.3.14 Adjustable index.- A mark shall be made on the housing assembly in coincidence with the adjustable index. Visually check the index which shall be in coincidence with the mark on the housing assembly to determine conformance with the requirements specified in 3.7.4.

4.4.3.15 Azimuth mechanism.- The test shall be performed manually for operability. When the azimuth worm is disengaged, the holder assembly shall be manually rotated and there shall be no undue looseness or friction throughout its full movement.

4.4.4 Operability.

4.4.4.1 Azimuth micrometer knob.- Operability shall consist of measuring the torque required to rotate the azimuth micrometer knob through a full travel at standard ambient temperature by means of a commercial torque wrench with a special adapter. These torque values shall then be compared with the operating temperature test values of 3.5.1, and the difference shall not exceed the prescribed value in 3.9.1.

4.4.4.2 Scales and indexes.- Scales and indexes shall be tested manually for operability when exposed to the temperature specified in 3.9.2. The scales and indexes, when their respective locks are released, shall have a free movement throughout their full excursion.

4.4.4.3 Holder assembly.- The holder assembly shall be tested manually for operability when exposed to the temperature specified in 3.9.3. The holder assembly, with the worm disengaged and the elevation lock released, shall have a free movement in azimuth, elevation and depression throughout their full excursion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

4.4.5 Check for completeness.- In addition to the performance and accuracy tests above, the finished unit shall be checked against the assembled view drawings to ascertain that all visible parts shown on the drawings and listed on the list of parts have been assembled, and that all locking and fastening screw, pins, nuts, etc., are in place and secured as required by the drawings and specifications.

4.4.6 Identification marking.- Marking for identification shall be visually inspected for conformance in accordance with Standard MIL-STD-130.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with Specification MIL-A-12757.

6. NOTES

6.1 Intended use.- The Adapter, Telescope: M9A1 is intended to position and secure an Elbow Telescope: M62 series. The adapter provides a coarse adjustment in elevation and a fine adjustment in azimuth and is used primarily as a component of the Sightunit: M34 series.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification
(b) Selection of an applicable level of preservation, packaging and packing
(c) Applicable stock number
(d) Provisions for production model including date of delivery (see 3.1)

6.3. Definitions.

6.3.1 Standard measuring equipment (SME). Standard measuring equipment is defined as the common hand type measuring devices which are usually stocked by commercial supply houses for ready supply (shelf items), and which are normally used by an inspector to perform dimensional inspection of items under procurement. This category also includes commercial testing equipment such as meters, optical comparators, etc.

6.3.2 Device, special testing (DST).- Special testing devices are defined as special inspection fixtures, instruments, and modified standard measuring equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.

6.3.3 Tactile.- Skillful manipulation or sensing.

6.4 SQAP (Supplementary Quality Assurance Provisions), LSQAP (List of SQAP's, and IEL (Inspection Equipment List).- Lists pertinent to each component and subassembly are identified by the Ordnance drawing number of the item prefixed by the above appropriate letter designation.

6.5 Design information.- Information regarding specific design not covered or referenced by this specification may be obtained from the procuring activity upon specific request of the contractor.

6.6 International standardization agreement.- Provisions of this specification are the subject of international standardization agreement. When amendment, revision or cancellation of this specification is proposed the departmental custodians will inform their respective Departmental Standardization Officer so that appropriate action may be taken respecting the international agreement concerned.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Custodian:

Army-Ordnance Corps

Preparing Activity

Army-Ordnance Corps

International interest (see 6.6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:24Z
Check the source to verify that this is the current version before use.