MIL-M-13348(Ord)
26 March 1954

MILITARY SPECIFICATION

MOUNTS, PERISCOPE, M89 (T177) AND M94 (T177E2)

10 ***SCOPE***

1.1 This **specification** ***covers two types of periscope mounts used*** **to support the Periscope M20 Series in medium and light tanks.**

2. ***APPLICABLE*** SPECIFICATIONS, STANDARDS, **D R A W I N G S**

2.1 The **following specification and drawings, and specifications and** drawings referenced **thereon, of the issue in offset on date of Invitation for bids,** form a part of this specification:

SPECIFICATION

Military

MIL-P-12413	***Packaging*** **of Mount, Periscopes,, M88 (T176),** (T176E1) , T176E2, **(T177) and M94 (T177E2)** ***<M93 <M89***

U. S. Army

51-7	***Instruments,*** Fire-Control; General Specification Governing the Manufacture and Inspection of

DRAWINGS

Ordinance Corps

F7652069	Mount, Perscope, M89 (T177)
F7652161	Mount, Periscope, M94 (T177E2
D7652081	**Arm**
D8246199	**Arm**
C7652089	***Arm Assembly***

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:26Z
Check the source to verify that this is the current version before use.

C765164	Arm Assembly
F7652072	Bracket Assembly
F7652162	Bracket Assembly
C7652092	Connector Assembly
C7654881	connector Assembly
B7652106	coupling

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer).

3. REQUIREMENTS

3 . 1 General requirements and associated tests comnon to all fire control instruments as specified in Specification 51-7 shall be mandatory where applicable.

3.2 MATERIALS - Materials shall be in accordance with the applicable drawings, and specifications farming a part of this specification.

3.3 Accuracy - The distance between the two extreme bore centers of the arm shall be in accordance with dimensions specified on the following drawings:

PERISCOPE MOUNT	ARM
M8 (T177)	*D7652081*
M94 (T177E2)	D8246199

3.4 Alinement- **With the vial in the level position, alinement of the arm and bracket assembly shall be in accordance with the requirements specified** on the following drawings:

PERISCOPE MOUNT	ARM ASSEMBLY	BRACKET ASSEMBLY
M89(T177)	*C7652089*	F7652072
M94 (T177E2	C7652164	F7652162

***3.5* Backlash. - With the stud of the lover connector assembly clamped rigidly the backlash shall not exceed 0.1 mil. as measured on the following coupling drawings:**

PERISCOPE MOUNT	CONNECTOR ASSEMBLY (lower)	COUPLING (See *Paragraph 6.1*)
M89 (T177)	*C7652092*	*B7652106*
M94 (T177E2)	*C765483l*	*B7652106*

3.6 Temperature requirement and test for assembled mounts shall not apply.

Source: https://assist.dla.mil - Downloaded: 2026-10-10 10:06:26Z
Check the source to verify that this is the current version before use.

3.7 Illumination - With a 24 volt d-c source applied to the receptacle assembly, the signal light assembly shall be checked for functional operation.

3.8 Workmanship - Workmanship shall be in accordance with Specification 51-7.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 Unless otherwise specified, each periscope mount shall be inspected for conformance with this specification and as specified in Specification 51-7.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking - Packaging, packing a marking shall be in accordance with Military Specification MIL-P-12413.

6. NOTES

6.1 Information data - Backlash in *Coupling* Assembly B7652105 (that is, between Coupling B7652106 and Plate B7652107) will be absorbed by the spring in the head of Periscope M20 series,

6.2 Ordering data - Invitation for bids and contracts shall specify the title, number and date of this specification, type of mount, and type of packing.

NOTICE: This specification, together with specification and drawings pertaining to it and bearing a 'NOTICE" of similar restrictions, is intended for use only in connection with procurement by the United States Government ; and shall not be reproduced either wholly or in part except when authorised in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordinance .

CUSTODIAN:

Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:26Z
Check the source to verify that this is the current version before use.