MIL-T-13364B(MU)
16 MARCH 1964
SUPERSEDING
MIL-T-13364A(ORD)
15 DECEMBER 1961

MILITARY SPECIFICATION

TELESCOPE, STRAIGHT: M97 SERIES

1. SCOPE

1.1 This specification covers straight tube telescopes of the M97 Series. These telescopes are similar except for difference in reticle patterns (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-12577 —Telescope, M97 Series; Packaging of.
MIL-O-13830 —Optical Components for Fire Control Instruments; General Specification Governing the Manufacture, Assembly, and Inspection of.
MIL-F-13926 —Fire Control Materiel: General Specification Governing the Manufacture and Inspection of.
MIL-I-45208 —Inspection System Requirements.

STANDARDS

MILITARY

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109—Quality Assurance Terms and Definitions.

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

F7660688 —Telescopes, Straight: M97 and M97C.
F8205100 —Telescopes, Straight: M97D, M97F, M97G and M97H.
LSQAP-7660688—List of Supplementary Quality Assurance Provisions for Telescopes, Straight: M97 and M97C.
LSQAP-8205100—List of Supplementary Quality Assurance Provisions for Telescopes, Straight: M97D, M97F, M97G and M97H.
IEL-7660688 —List of Inspection Equipment Numbers for Telescopes, Straight: M97 and M97C.
IEL-8205100 —List of Inspection Equipment Numbers for Telescopes, Straight: M97D, M97F, M97G and M97H.

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 **Other publications.** The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS

NBS Resolution Test Chart of 1952 (High Contrast) (Number 56)

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with drawings, material specifications, and general specifications forming a part of this specification.

3.2 Fabrication. The telescope specified in the contract or order shall be manufactured in accordance with the applicable drawing listed in Section 2 and all drawings pertaining thereto.

3.3 General specifications. The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specifications MIL–O–13830 and MIL–F–13926.

3.3.1 *MIL–F–13830.*

(a) Cleanliness.
(b) Illuminated reticles.

3.3.2 *MIL–F–13926.*

(a) Order of precedence.
(b) Dimensions and tolerances.
(c) Inorganic protective surface finishes.
(d) Part identification and marking.
(e) Workmanship.

3.4 Environmental.

3.4.1 *Storage temperatures.* The telescope shall show no evidence of physical failure and shall meet all performance requirements of this specification at a standard ambient temperature of between 60° and 90° Fahrenheit (F) after having been exposed to, and thermally stabilized at, ambient temperatures of −80° and +160° F.

3.4.2 *Operating temperatures.* The telescope shall meet the applicable requirements of 3.8 while exposed to and thermally stabilized at ambient temperatures of −40° F. and +150° F.

3.4.3 *Vibration.* The telescope shall be vibrated at a constant frequency of 30 cycles per second with an amplitude of $\frac{1}{16}$ inch ($\frac{1}{8}$ inch maximum excursion) for a period of 5 minutes ±15 seconds. Subsequent to vibration the telescope shall show no evidence of loose or damaged parts and it shall meet the following requirements of this specification.

3.5 Cleanliness. Subsequent to vibration the telescope shall meet the cleanliness requirements of Specification MIL–O–13830 and there shall be no more than two particles of dirt visible on the reticle. The area of each of the particles shall not be in excess of the area equivalent to a size five dig. There shall be no other dirt within the telescope which interferes with observation or adversely affects image quality.

3.6 Sealing. The telescope shall show no evidence of leakage when subjected to an external pressure of 5 pounds per square inch gage (psig) pressure for a minimum period of five minutes.

3.7 Accuracy.

3.7.1 *Collimation.* With the telescope mounted on the spherical surfaces of its mounting bearings, and with the telescope's locating pin in a vertical, downward position, the center of the boresight cross shall be 21.04 mils ±0.2 mil above the geometric axis and shall coincide within 0.2 mil of a plumb line passing through the geometric axis. Subsequent to vibration the line of sight shall not vary from the established positions prior to vibration by more than 0.15 mil.

3.7.2 *Reticle accuracy.* The angular value for reticle graduations between zero and max-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

imum range shall read as indicated on the applicable reticle drawing within 0.25 mil.

3.7.3 *Parallelism of reticle and image.* With the telescope locating pin in a vertical downward position, the longest horizontal reticle line shall not deviate from a horizontal target line by more than 0.5 mil at one extremity of the reticle line when the other extremity of the reticle line is in coincidence with the horizontal target line.

3.7.4 *Eyepiece focus.* The eyepiece shall be adjustable over the range of ±3 diopters as read on the eyepiece scale. The zero setting of the diopter scale shall indicate zero diopter within 0.25 diopter.

3.7.5 *Resolution.* The resolving power at the geometric axis shall be 4.5 seconds of arc or less.

3.7.6 *Parallax.* Parallax at the geometric axis shall not exceed 0.1 mil when viewing a target at 800 meters ±100 meters.

3.8 **Operability.** The running torque required to rotate the diopter adjustment shall not exceed 12 pound inches at a standard ambient temperature of between 60° and 90° F. The torque value obtained at the extreme temperatures of 3.4.2 shall not exceed the value recorded at the standard ambient temperature by more than 3 pound inches.

3.9 **Illumination.** With the reticle illuminated, the reticle markings shall appear clearly defined when observed in a darkened area.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract of purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *General provisions.* The quality assurance provisions of this specification and of other documents referenced herein form the basis for inspection to be performed by the supplier. Inspection shall be in accordance with the requirements of Specification MIL–I–45208 and the component inspection requirements of Specification MIL–F–13926. Definitions of inspection terms not otherwise defined herein shall be listed in Standard MIL–STD–109.

4.2 **Inspection provisions.**

4.2.1 *Inspection lot.* Unless otherwise specified by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with "Submission of Product" as specified in Standard MIL–STD–105.

4.2.2 *Examination and tests.* Components and subassemblies shall be inspected in accordance with the inspection provisions contained in Specification MIL–F–13926 and List of Supplementary Quality Assurance Provisions, LSQAP–7660688, and LSQAP–8205100. Examinations and tests related to Section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with Standard MIL–STD–105, and the inspection level and sampling plans specified in Table I titled "Classification of Defects." Examinations and tests for packaging, packing and marking shall be in accordance with Specification MIL–T–12577 and Section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirement and to reject individual non-conforming items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

TABLE I. *Classification of Defects*

Use Inspection Level II of Table I with Sampling Plan Table II–A of Standard MIL–STD–105

	Requirement	Test procedure
Critical: None.		
Major: AQL 0.65 Percent Defective.		
101. Vibration	3.4.3	4.5.3
102. Cleanliness	3.5	4.5.4
103. Collimation	3.7.1	4.5.6.1
104. Collimation—post vibration	3.7.1	4.5.3.1
105. Reticle accuracy	3.7.2	4.5.6.2
106. Parallelism of reticle and image	3.7.3	4.5.6.3
107. Eyepiece focus	3.7.4	4.5.6.4
108. Resolution	3.7.5	4.5.6.5
109. Parallax	3.7.6	4.5.6.6
110. Operability (60° and 90° F)	3.8	4.5.7
Minor: AQL 2.5 Percent Defective.		
201. Illumination	3.9	4.5.8

4.2.3 *Disposition of non-conforming product.* Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in Standard MIL–STD–105.

4.3 Control tests.

4.3.1 *General.* One telescope shall be selected at random from each 100 produced, or from each month's production, whichever occurs first. Control samples shall have successfully met all acceptance tests specified herein prior to conducting the following examinations and tests:

Control test	Requirement	Test procedure
Materials	3.1	Per applicable drawings and Specifications
Fabrication	3.2	Visual—Per Drawings
General Specifications	3.3	Visual—MIL–O–13830 and MIL–F–13926

4.3.2 *Environmental.* Three telescopes shall be selected at random from each 50 produced, or from each month's production, whichever occurs first. Control samples shall meet the following requirements and tests:

Control test	Requirement	Test procedure
Storage temperatures	3.4.1	4.5.1
Operability of diopter adjustment (—40° and +150° F).	3.4.2	4.5.2 and 4.5.7
Sealing	3.6	4.5.5

4.3.3 *Control test failure.* Should the control test sample fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved.

4.4 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall furnish and maintain all required measuring and testing equipment in accordance with the "Measuring and Test Equipment" requirement of Specification MIL–I–45208. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 *Government furnished inspection equipment.* Where the contact provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with "Measuring and Test Equipment" and "Government-furnished Material" requirements of Specification MIL–I–45208.

4.4.2 *Contractor furnished inspection equipment.*

4.4.2.1 *Government design.* All inspection equipment required by drawings forming a part of the contract and not provided by the Government shall be supplied by the contractor in accordance with the List of Inspection Equipment Numbers, IEL–7660688; IEL–8205100. Alternate designs may be substituted only as provided by "Inspection Provisions" of Specification MIL–I–45208.

4.4.2.2 *Contractor design.* The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5, and with the "Com-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

ponent Inspection" requirements of Specification MIL–F–13926. Concept, construction, materials, dimensions, and tolerances used in design of test equipment shall be so selected and controlled as to insure that the test equipment will permit positive rejection of a product which exceeds the prescribed tolerance limit, and will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit. Construction shall be such as to facilitate routine calibration of the equipment.

4.5 Test methods and procedures.

4.5.1 *Storage temperatures.* The telescope shall be exposed to the temperatures indicated in 3.4.1, utilizing testing equipment in accordance with the "Test Facilities" requirements of Specification MIL–F–13926. This equipment shall be capable of maintaining the specified temperatures until thermal stabilization is reached. The temperatures shall be changed gradually to avoid thermal shock. After the telescope has been exposed to the extreme temperatures and permitted to return to standard ambient temperature, the telescope shall be examined for evidence of damage or deterioration. The telescope shall then be subjected to, and comply with, the accuracy requirements of this specification.

4.5.2 *Operating temperatures.* The telescope shall be exposed to the temperatures indicated in 3.4.2, employing the test facilities used for the temperature test in 4.5.1. The temperatures shall be changed gradually to avoid thermal shock. To determine compliance with the requirements of 3.4.2 when thermal stabilization is established at each extreme temperature condition, the telescope shall be subjected to the test procedures of 4.5.7.

4.5.3 *Vibration.* Prior to the performance of this test, the inspector must know the position of the reticle with respect to the locating pin, which is obtained as described in 4.5.6. With the telescope removed from the special testing device, subject the telescope to the vibration test utilizing a type of vibrating machine capable of meeting the conditions of 3.4.3. The accuracy of the applicable test equipment and test equipment measurements shall be in accordance with the "Test Facilities" requirements of Specification MIL–F–13926. The telescope shall be secured to the vibrating table in a horizontal position by means of an adapter or holding media. The telescope shall be vibrated in a vertical plane with the motion and frequency applied for the time indicated in 3.4.3. At the conclusion of this vibration, the telescope shall be examined for evidence of damage and looseness of parts. The telescope shall then be subjected to the tests and procedures outlined herein to determine compliance with the requirements of 3.4.3.

4.5.3.1 *Postvibration collimation check.* After vibration, reinsert the telescope into the special testing device. The telescope shall again meet the collimation test outlined in 4.5.6.1 to determine compliance with the requirements of 3.7.1.

4.5.4 *Cleanliness.* Cleanliness of the optical surfaces shall be such that when the telescope is pointed toward a source of illumination and examined through the objective and eyepiece ends, respectively, with the unaided eye, the telescope shall not contain particles of dirt in excess of the amount specified in 3.5. Area inspection of the dirt particles shall be accomplished by means of a Scratch and Dig Standards Drawing C7641866 for a comparison of the area of the dirt particles with the dig size of the standard. This test shall be performed subsequent to vibration.

4.5.5 *Sealing.* The telescope shall be subjected to the external pressure indicated in 3.6. the test shall be accomplished by means of a testing device, with an adapter to receive the telescope. This device shall be capable of producing the required pressure for the time specified. The device, set-up, and operating instructions for this test shall be comparable to that depicted on Drawing F7680673, "Fixture, Pressure Testing", and "Adapter", Drawing F7680717, listed on IEL's. Leakage, as indicated on the gage of the test equipment, shall not be evident

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

within the minimum duration specified in 3.6.

4.5.6 *Accuracy.* The equipment required for the performance of the accuracy tests shall consist of a device to receive the respective telescopes of the M97 series so that the spherical mounting surfaces of the tube are positioned in a horizontal plane in such a manner as to insure immobilization of the telescope. The telescope's locating pin shall be positioned in a vertical downward position in the locating pin keyway in the locating surface of the device. Provision shall be provided, in the locating surface of the device, to permit 360° rotation of the telescope's optical line of sight to check collimation accuracy. The device shall be equipped with provisions to permit plumbing the vertical reticle line of an auxiliary telescope to a plumb line suspended in front of a target that has been alined with respect to the vertical axis of the locating pin. The device shall permit repeatability of the initial setting, using the telescope's boresight cross as a reference in coincidence with markings on the target used for measuring reticle patterns. The total allowable shift shall not exceed the specified limit when the telescope is removed and replaced in the device three consecutive times. Appropriate targets shall be provided and utilized for measuring the reticle patterns. The targets shall have acceptance and rejection limitation markings or pips marked thereon, the angular tolerance of which shall not exceed the specified tolerance. The targets shall be used for measuring the accuracy requirements. Rigidity, stability, ease of maintenance and adaptability of set-up and calibration equipment with complete provisions are also prime requirements. All special set-up and calibration equipment necessary for certification of device accuracy shall be furnished and will become part of the device.

4.5.6.1 *Collimation.* This test shall be accomplished with the testing device depicted in 4.5.6 holding the telescope positioned to view the target located 66 feet 6 inches from the telescope's objective. (This distance is selected as it represents 4.5 seconds of arc on the National Bureau of Standards Test Chart of test pattern No. 56.) Viewing through the telescope, note the related position of the boresight cross with the boresight cross or marks on the target. The intersecting point of the telescope's boresight shall coincide with the boresight cross or marks on the target representing the limits for collimation. When the collimation has been established, observe parallelism between the longest horizontal reticle line of the telescope with respect to the horizontal line on the target. They shall be parallel within 0.5 mil. A shield or peep sight of the cap type, with a centrally located $\frac{1}{16}$-inch diameter hole, placed over the eyepiece of the telescope will assist the observer's eye and reduce parallax.

4.5.6.2 *Reticle Accuracy.* With the telescope positioned in the testing device from the previous test, accuracy of angular value of the reticle shall be accomplished with the aid of a MIL target established at the proper height for the requirements of 3.7.2. Reticle accuracy shall be checked by coinciding the horizontal line of the telescope's boresight cross with the corresponding horizontal line of the scaled target. Observe the horizontal lines of the telescope's reticle with respect to the tolerance lines of the scaled target. Repeat this operation, coinciding the vertical line of the boresight crosses and checking the ends of the vertical dash lines for uniformity of spacing against the vertical lines of the scaled target and the overall spread against the tolerance lines of the target. The angular value between zero and maximum range shall not exceed the specified tolerance. A peep sight positioned over the eyepiece of the telescope will assist the observer's eye for parallax. Each reticle of the series shall conform to the tolerances specified.

4.5.6.3 *Parallelism of reticle and image.* This test shall follow the collimation test. Proceed to make the check by sighting through the ocular of the telescope, coinciding one end of the telescope's longest horizontal reticle line with that of the scaled target. Then observe coincidence at the op-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

posite end of the reticle lines. The horizontal reticle line shall not deviate from the image of the horizontal target line by more than the limit specified in 3.7.3. Each reticle shall conform to the tolerance specified.

4.5.6.4 *Eyepiece focus.* The test shall be made with the aid of a dioptometer of at least 3 power (3X). The dioptometer is employed to produce identical diopter readings when the eyepiece of the dioptometer is focused on its reticle to accommodate the observer's eye. Prior to performing the eyepiece focus test, the dioptometer shall be set as follows: Adjust the eyepiece to produce a sharp image of the reticle when viewing against an illuminated background. Set the dioptometer at infinity by sighting at a target, such as a smoke stack, edge of a building, etc., at approximately 1000 yards to remove parallax. Parallax is removed when there is no displacement between the reticle and target when the observer's head is moved from side to side or up and down. Set the diopter scale to zero. Locate the telescope to be tested with the objective facing the illuminated background, with the diopter scale set at zero. Rotate the telescope eyepiece assembly to obtain a clear, sharp image of the reticle. Note setting on the diopter scale. The diopter scale setting will indicate the error for determining the requirement of 3.7.4. Place the dioptometer behind the eyepiece assembly and observe the reticle image of the telescope under test. Obtain a clear, sharp image of the telescope reticle by rotating the dioptometer's eyepiece. Note the reading on the diopter scale. This reading shall coincide with the diopter scale setting on the telescope within the limit specified in 3.7.4.

4.5.6.5 *Resolution.* The resolution requirement can be checked with the same set-up used for the collimation test, with the aid of a dioptometer of at least 3 power. The "56" pattern of the National Bureau of Standard's Test Chart shall be attached to the central area of the target located 66 feet 6 inches from the objective of the telescope. The test chart shall be illuminated by a reflector type lamp of at least 60 watts. The target's geometric axis must be in coincidence with the telescope's optical axis. With the telescope focused on the "56" numeral, aline the dioptometer's optical axis to the eyepiece of the telescope. Focus the objective of the dioptometer until the numeral on the test chart appears sharp. The test patterns on either side of the "56" shall be resolved when viewed through the dioptometer. The test pattern shall be resolved for compliance with the limit specified in 3.7.5. The test pattern will be considered resolved when the observer can determine the direction in which the lines lay.

4.5.6.6 *Parallax.* Parallax is checked on the testing device by sighting through the telescope and observing a point on a target at the distance specified in 3.7.6 with respect to a corresponding point of the telescope's reticle in close proximity to the telescope's optical axis. Parallax shall be removed paraxially. Parallax will be recognized as any apparent displacement of the target image in relation to the reticle image when the observer's head is moved. Any movement of the observer's head shall not cause displacement of the target image to exceed the limit specified in 3.7.6.

4.5.7 *Operability.* The telescope, with the eyeshield removed, shall be secured in a holding device in a horizontal position. The test consists of measuring the torque required to rotate the diopter adjustment through full travel, while at standard ambient temperature and extreme temperatures, by means of a commercial type torque wrench, measuring in pound-inches, with an adapter. The torque wrench shall be rotated in a clockwise direction and then in a counterclockwise direction. Readings shall be taken when the diopter adjustment assembly is in continuous motion. The readings obtained on the device while at standard ambient temperature shall not exceed the value indicated in 3.8 and they shall be noted. During the performance testing at $-40°$ and $+150°$ F., the diopter adjustment shall again be rotated by means of the torque wrench with adapter, and the readings ob-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

tained shall not exceed the value indicated in 3.8.

4.5.8 *Illumination.* The illumination test for the requirement of 3.9 is a visual check, and shall be accomplished with the lighting instrument energized with a 3-volt source.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with Specification MIL–T–12577. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.

6.1.1 *Telescope M97.* Used for direct fire in tanks of the M41 Series with 76MM Gun T91. The reticle for ammunition AP–T128E6 M.V. 3200F/S is inscribed for range in yards.

6.1.2 *Telescope M97C.* Used for direct fire in tanks of the M48 Series with 90MM Gun T119. The reticle for ammunition AP–T, T33E7 M.V. 3000F/S is inscribed for range in yards.

6.1.3 *Telescope M97D.* Used for direct fire in tanks of the M48 Series with 90MM Gun M41. The reticle for ammunition AP–T, M318A1 MV–3000F/S is inscribed for range in yards.

6.1.4 *Telescope M97F.* Used for direct fire in tanks of the M48 Series with 90MM Gun M41. The reticle for ammunition AP–T, M318A1 MV3000F/S is inscribed for range in meters.

6.1.5 *Telescope M97G.* Used for direct fire in tanks of the M48 Series with 90MM Gun M41. The reticle is inscribed for range in meters for ammunition HEAT, T300E54 M.V. 4000F/S.

6.1.6 *Telescope M97H.* Used for direct fire in tanks of the M48 Series with 90MM Gun M41. The reticle is inscribed for range in yards for ammunition HEAT, T300E54 M.V. 4000F/S.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of preservation, packaging and packing.
(c) Applicable stock number.

Custodian:
Army—MU

Preparing activity:
Army—MU
Project No. 1240–A397Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
U. S. Army Munitions Command
Attn: SMUFA-5500
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:27Z
Check the source to verify that this is the current version before use.