NOT MEASUREMENT SENSITIVE

MIL-DTL-43098/14
15 November 1996

DETAIL SPECIFICATION SHEET

MEDALLION, EUGENE G. FUBINI AWARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-43098 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER: 2-1/2 inches (6.35 cm) (REF)
THICKNESS (At Thickest Point): 0.190 inch ± 0.010 inch (0.482 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:37Z
Check the source to verify that this is the current version before use.

2. A hole 3/16 inch ± 1/64 inch (0.48 cm ± 0.04 cm) in diameter shall be drilled through the lug, perpendicular to the obverse and reverse faces of the pendant. The hole shall be centered in the lug.

3. The pendant ring shall be fabricated from 0.064 inch ± 0.002 inch (0.062 cm ± 0.005 cm) diameter wire and shall have an inside diameter of 3/8 inch ± 1/64 inch (0.95 cm ± 0.04 cm). The ends shall be square cut and shall be together and in line.

4. Medallion set shall consist of a medallion and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XV, Style 1 with a Type 1, Class 1 pad.

5. The ribbon for the pendant drape shall conform to MIL-DTL-11589/495.

6. The lapel button shall conform to MIL-DTL-11484/242.

Custodian:
Army - IH

Preparing activities:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0869)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:37Z
Check the source to verify that this is the current version before use.