INCH-POUND
A-A-52524/17A
November 6, 2003
SUPERSEDING
A-A-52524/17
April 10, 1997

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

SEAL, PLAIN OR SEAL, PLAIN ENCASED: SINGLE SEALING MEMBER, EXTENDED CASE

The General Services Administration has authorized the use of this Commercial Item Description Specification Sheet (CIDSS) for all federal agencies.

The complete requirements for procuring the seals shall consist of this document and the issue in effect of A-A-52524.

1. SCOPE. This CIDSS covers seals to be used as rotary shaft seals to retain oil and other fluids.

2. SALIENT CHARACTERISTICS

2.1 Materials.

2.1.1 Class 1 sealing member material. Class 1 sealing members shall be made of polymer-impregnated leather or chrome-vegetable-retanned leather which has been mildew resistant treated and suitable for normal operating temperatures (see A-A-52524).

2.1.2 Class 2 sealing member material. Class 2 sealing members shall be made of oil resistant synthetic elastomer suitable for normal operating temperatures (see A-A-52524).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSRD-TAR-E/ASI, 6501 E. 11 Mile Road, Warren, MI 48397-5000.

AMSC N/A FSC 5330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

2.1.3 Class 3 sealing member material. Class 3 sealing members shall be made of oil resistant elastomer suitable for extreme operating temperature service (see A-A-52524).

2.2 Design and construction. The seals (classes 1, 2, and 3 of A-A-52524) shall be designed and constructed in accordance with figure 1.




FIGURE 1. Seal design, construction, and part number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

First dash No. (size)	A Shaft dia. (Nom)	B1 Seal O.D. (1)	B2 Housing bore (ref)	C Width (5)	First dash No. (size)	A Shaft dia. (Nom)	B1 Seal O.D. (1)	B2 Housing bore (ref)	C Width (5)
1	0.25	0.754	0.750	0.25	15	1.72	2.718	2.714	0.359
2	0.5	0.691	0.687	0.078	16	1.75	2.730	2.726	0.5
3	0.554	0.813	0.809	0.219	17	1.75	2.754	2.750	0.484
4	0.875	1.250	1.246	0.25	18	1.93	3.004	3.000	0.25
5	0.875	1.314	1.310	0.25	19	1.93	3.160	3.155	0.25
6	1	1.252	1.248	0.094	20	2	3.001	2.997	0.25
7	1	1.441	1.437	0.313	21	2.125	2.879	2.875	0.25
8	1	1.504	1.500	0.25	22	2.25	3.317	3.312	0.375
9	1.1875	2.002	1.998	0.25	23	2.96	4.008	4.003	0.25
10	1.25	1.504	1.500	0.094	24	3.5	4.756	4.751	0.25
11	1.25	1.756	1.752	0.25	25	4	5.378	5.373	0.75
12	1.375	1.878	1.874	0.25	26	4.68	6.005	6.000	0.25
13	1.375	2.441	2.437	0.468	27	6.18	7.508	7.502	0.25
14	1.56	2.690	2.686	0.375	28	6.46	7.257	7.251	0.25

NOTES:

1. Dimensions are in inches. Tolerances are ±0.002 for seal outside diameters (O.D.) up to and including 2 inches. Tolerances are +0.003, -0.002 for seal O.D. over 2 inches and up to and including 3 inches. Tolerances are +0.004, -0.002 for seal O.D. over 3 inches and up to 7 inches.
2. The part number consists of the CID designator, the CID number, the specification sheet number and 2 dash numbers (see paragraph 7.3 of A-A-52524). The first dash number indicates the size. The second dash number indicates the class.
   EXAMPLE: AA52524/17-11-3 indicates size number 11 with class 3 sealing member
   (elastomer for extreme operating temperature).
3. The PIN dash numbers and the former MS part number dash numbers are the same.
   EXAMPLE: AA52524/17-11-3 cross references to MS51920-11-3.
4. The CIDSS is not intended to limit construction to features other than as shown herein by dimensions, notation, or referenced documents.
5. Width tolerances for seals shall be ± 0.015 for widths up to 4.00, and ± 0.020 for widths over 4.00.

FIGURE 1. Seal design, construction, and part number - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

3. NOTES. (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

3.1 Part identification number (PIN). The PINs to be used for acquisition of seals are shown in 7.3 of A-A-52524.

3.2 Cross reference data. Seals conforming to this CIDSS are interchangeable/substitutable with seals conforming to MS51920F.

MILITARY INTERESTS:

Custodian:
Army - AT

Review Activities:
Army – AR
DLA - IS

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

Preparing Activity:
Army - AT

(Project 5330-1268)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.