[INCH-POUND]
A-A-52524/18
April 10, 1997
SUPERSEDING
MS51921
27 October 1986

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

SEAL, PLAIN OR SEAL, PLAIN ENCASED: SINGLE SEALING MEMBER, FACE TYPE

The General Services Administration has authorized the use of this Commercial Item Description Specification Sheet (CIDSS) for all federal agencies.

The complete requirements for procuring the seals shall consist of this document and the issue in effect of A-A-52524.

1. SCOPE. This CIDSS covers seals to be used as rotary shaft seals to retain oil and other fluids.

2. SALIENT CHARACTERISTICS

2.1 Materials.

2.1.1 Class 1 sealing member material. Class 1 sealing members shall be made of polymer-impregnated leather or chrome-vegetable-retanned leather which has been mildew resistant treated and suitable for normal operating temperatures (see A-A-52524).

2.1.2 Class 2 sealing member material. Class 2 sealing members shall be made of oil resistant synthetic elastomer suitable for normal operating temperatures (see A-A-52524).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000.


AMSC N/A FSC 5330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:12Z
Check the source to verify that this is the current version before use.

2.1.3 Class 3 sealing member material. Class 3 sealing members shall be made of oil resistant elastomer suitable for extreme operating temperature service (see A-A-52524).

2.2 Design and construction. The seals (classes 1, 2, and 3 of A-A-52524) shall be designed and constructed in accordance with figure 1.



First dash No. (size)	A Shaft dia. (Nom)	B_1 Seal O.D. +0.004 -0.002	B_2 Housing bore (ref)	C Width ±0.020
1	2.5	3.187	3.182	0.56

FIGURE 1. Seal design, construction, and part number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:12Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. The part number consists of the CID designator, the CID number, the specification sheet number and 2 dash numbers (see paragraph 7.3 of A-A-52524). The first dash number indicates the size. The second dash number indicates the class.
   EXAMPLE: AA52524/18-1-3 indicates size number 1 with class 3 sealing member (elastomer for extreme operating temperature).
3. The PIN dash numbers and the former MS part number dash numbers are the same.
   EXAMPLE: AA52524/18-1-3 cross references to MS51921-1-3.
4. The CIDSS is not intended to limit construction to features other than as shown herein by dimensions, notation, or referenced documents.

FIGURE 1. Seal design, construction, and part number - Continued.

3. NOTES. (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

3.1 Part identification number (PIN). The PINs to be used for acquisition of seals are shown in paragraph 7.3 of A-A-52524.

3.2 Cross reference data. Seals conforming to this CIDSS are interchangeable/substitutable with seals conforming to MS51921.

MILITARY INTERESTS:

Custodian:
Army - AT

Review Activities:
Army - AR, AL, AV, MI, GL

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

Preparing Activity:
Army - AT

(Project 5330-1059)

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:12Z
Check the source to verify that this is the current version before use.