MILITARY SPECIFICATION SHEET

FILTER, HIGH PASS, TYPE FR4SX33AG1

This amendment forms a part of Military Specification Sheet MIL-F-18327/22A, dated 13 May 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure: Delete "TERMINALS-SOLDER TYPE .250 DIA. 3 REQ'D", and substitute "TERMINALS-SOLDERABLE STUD .250 DIA, 3 REQ'D".

PAGE 2

Requirements, Terminals: Delete "Solder lug." and substitute "Solderable stud (see figure)."

Requirements: After "Terminal strength", add the following:

" Solderability: Method 208 MIL-STD-202.
All terminations, of each filter, to be tested.
Solder dip dwell time: 5 seconds +1/2 second.
Examination of terminations: At 10X magnification. "

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, AV, ME, WC
Navy - AS, CG, MC, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5915-0190-15)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:20Z
Check the source to verify that this is the current version before use.