MIL-I-14303E
7 May 1971
SUPERSEDING
MIL-I-14303D(MU)
27 October 1970

MILITARY SPECIFICATION

IGNITER, BOMB, WP, AN-M23A1; COMPONENTS FOR

This specification is mandatory for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the components for the AN-M23A1 igniter.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-15011 - Pallets, Material Handling, Wood Post Construction, 4-Way Entry.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL14-5-2164 - Igniter, Bomb, WP, AN-M23A1; Components for.

FSC 1325

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, IL 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressd to the American Trucking Associations, Inc., 1616 P Street, N. W., Washington, D. C. 20036.)

AGENT T. C. GEORGE's TARIFF

(Application for copies should be addressed to T. C. George, Agent, 2 Pennsylvania Plaza, New York, NY 10001.)

3. REQUIREMENTS

3.1 Components. All components of the igniter shall conform to the specifications and drawings listed on Drawing DL14-5-2164 and subsidiary drawings.

3.2 Assembly. The igniter components shall be assembled as shown on Drawing C14-5-2164.

3.3 Leakage. The assembled body shall not leak when subjected to an internal air pressure of 50 + 10 pounds per square inch gage (psig) when submerged in water for a period of 1 minute and tested in accordance with 4.2.4. Subsequent to test, the assembled body shall be thoroughly dried.

Source: https://assist.dla.mil -- Downloaded: 20261O-18T03:02Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. The components shall be free from damage and foreign matter that could prevent normal assembly. The interior of the assembled body shall be free of contaminants such as rust, water, oil and other foreign elements.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. A lot shall consist of the igniter components produced by one manufacturer, at one plant, from the same materials and under essentially the same manufacturing conditions.

4.2.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure.

4.2.3.1 Examination and nondestructive tests. Sample components shall be examined and tested in accordance with the classification of defects and with MIL-STD-105.

4.2.3.2 Critical defects. Each igniter body shall be inspected for its critical characteristic listed in the classification of defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:02Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects.

(a) Body, igniter-assembly (Dwg D14-5-2164).

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.2.4
Major:	AQL 0.65 percent defective	
101	Thread (1-1/2-24) minor or pitch diameter incorrect	
102	Thread (1/4-18NPT special) incorrect	
103	Rolled thread incorrect	
104	Eccentricity between 1-1/2-24 thread and burster cup inside diameter excessive	
105	Depth (fuze cavity) incorrect	
106	Workmanship (3.4)	

(b) Plug, (Dwg B14-5-777).

Categories	Defects
Major:	AQL 1.0 percent defective
101	Thread incorrect
102	Hexagon incorrect
103	Depth of hexagon incorrect
104	Length incorrect

4.2.4 Leakage test. The body shall be subjected to the required pressure for the specified period of time. Air bubbles shall be considered evidence of leakage.

5. PREPARATION FOR DELIVERY

5.1 Interplant shipment. The bomb igniter components shall be cleaned, dried, preserved as applicable and packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:02Z
Check the source to verify that this is the currentversion before use.

5.2 Interplant shipment. "A designated quantity" of items, not to exceed the weight limitations specified as follows, packaged as specified in 5.1, shall be packed in containers or special packs as applicable, together with interior packaging, constructed as to give assurance that the items being shipped will remain in prime condition and adequate to assure safe delivery to destination without damage to contents. The containers shall comply with Uniform Freight Classification, National Motor Freight Classification, or T.C. George's Tariff, as applicable, and be acceptable for shipment at the most favorable rate. The containers shall be sufficiently rigid to withstand transportation and permit storing in tiers at least 10 feet high without damage to containers or contents. The gross weight and size limitations specified therein, and the containers shall be closed or strapped as specified therein.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages and shipping container shall be marked in accordance with MIL-STD-129.

5.4 Palletization. The igniter and component packed as specified in 5.2, shall be palletized to facilitate handling. The pallet shall be 4-way entry and conform to MIL-P-15011. Pallet loads shall not exceed the gross weight and size limitations for the respective type pallet utilized with a 2000 lb weight limitation for any type pallet. The pallet load shall be secured to the pallet in a manner to restrict free movement of the load, in any direction, during routine shipping conditions. The pallet load shall also be in compliance with applicable rules and regulations for shipping of non-hazardous metal parts and components.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number and date of this specification.

6.2 Interplant shipments. Interplant shipments are shipments from a vendor to a prime contractor, sub-contractor or a supplier to a supplier to a military arsenal or plant.

Custodian:

Army - MU
Navy - AS
Air Force - 70

Preparing activity:

Army - MU(EA)

Project No. 1325-0150

Review activities:

Army - SM
Navy - AS
Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:02Z
Check the source to verify that this is the current version before use.

TO DETACH FORM – CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:02Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:02Z
Check the source to verify that this is the current version before use.