MIL-S-14268A(WC)
13 August 1971
SUPERSEDING
MIL-S-14268(ORD)
8 March 1956

MILITARY SPECIFICATION

SLING ASSEMBLY, HEAD HANDLING, 762MM ROCKET, M6

1. SCOPE

1.1 This specification covers one type of head handling sling assembly for the 762mm rocket.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

Federal		
FED-STD-751	-	Stitches, Seams, and Stitchings.
Military		
MIL-STD-105	-	Sampling Procedure and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.
MIL-STD-130	-	Identification Marking of U.S. Military Property.

DRAWINGS

U.S. Army Weapons Command		
F8407294	-	Sling Assembly, Head Handling, 762MM Rocket, M6.

PUBLICATIONS

U.S. Army Weapons Command		
F8407294	-	Packaging Data Sheet for Sling Assembly, Head Handling, 762MM, M6.

FSC 1055

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:01Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article sample. Requirements for submission of first article samples shall be as specified in the contract (see 6.1). The first article sample shall include the pilot pack (see 5.1), unless otherwise specified.

3.2 Materials, construction and design. Sling assemblies shall conform to the materials, construction and design requirements specified herein, on Drawing F8407294 and drawings applicable thereto. Sling assemblies shall fit the 762mm rocket head.

3.2.1 Welding. Welding of metal parts shall be in accordance with the applicable drawings.

3.2.2 Stitching. Stitching of straps shall be as specified on the applicable drawings and in accordance with FED-STD-751, type 301. Ends of threads shall be securely fastened and there shall be no evidence of loose or irregular stitching or ruptured seams.

3.2.3 Hardware. All metal hardware shall be as specified on the applicable drawings and all snaps and buckles shall function as intended.

3.2.4 Color. Color and finish of thread, webbing, and metal parts shall be in accordance with the applicable drawings.

3.2.5 Proof-load. The head handling strap assembly, the front stablizing strap assembly and the strap assembly shall be capable of withstanding the proof-loads specified on the applicable drawings.

3.3 Marking. The sling assemblies shall be marked in accordance with the applicable drawings and MIL-STD-130.

3.4 Workmanship. Sling assemblies shall be free of visual defects including sharp edges, burs and sharp points on metal parts.

Source: https://assist.dla.mil -- Downloaded: 20261O-18T03:01Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. Inspection of first article (see 3.1) and pilot pack (see 5.1) shall be performed at the designated testing agency. First article and pilot pack shall be subjected to the inspection specified herein and such other inspection as is necessary to determine compliance with the requirements of the contract (see 6.1).

4.5 Quality conformance inspection.

4.5.1 Inspection lot. The formation, size and presentation of inspection lots of sling assemblies, parts, and packaging shall be in accordance with MIL-STD-105. Inspection lots shall be as large as practicable, in consideration of quality history, manufacturing conditions, and contractor's delivery schedule. Sling assemblies shall be assembled from lots of component parts that have met all inspection requirements specified herein.

4.5.2 Examination. Examination of sling assemblies and packaging shall be performed in accordance with the applicable examination provisions specified herein. Sample size shall be in accordance with MIL-STD-105. Packaging sample size shall be in accordance with inspection level I of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:01Z
Check the source to verify that this is the current version before use.

4.5.2.1 Classification of defects. Classification of defects and acceptable quality levels (AQL's) for examination in accordance with MIL-STD-105 shall be as specified herein and shall include the following provisions:

a. For sling assemblies, AQL's apply to each group of defects.

b. For packaging, AQL's apply to each individual defect.

c. Where "Visual" is specified as the method of dimensional inspection, the sample shall be either scaled or compared with a specimen of known acceptable quality.

4.5.2.1.1 Sling Assembly, Head Handling, 762MM Rocket, M6 (Drawing F8407294).

Class	Characteristics	Inspection method
Critical:	None defined.	
Major:	AQL = 1.0 Percent	
101	Loose or ruptured seams in fabric (see 3.2.2).	Visual
102	Welds of fitting assembly missing or defective (see 3.2.1).	Visual
103	Incomplete assembly or mislocated parts.	Visual
Minor:	AQL = 2.5 Percent	
201	Color, nonconforming (see 3.2.4).	Visual
202	Stitching, incomplete or nonconforming with design (see 3.2.2).	Visual
203	Improper functioning or wrong type of snap (see 3.2.3).	Manual and Visual
204	Marking, incorrect or illegible (see 3.3).	Visual
205	Dimensional requirements of finished strap assemblies not met.	Scale
206	Defective workmanship (see 3.4).	Visual

4.5.2.1.2 Packaging. Unless otherwise specified in each listed defect, the packaging requirements are specified on Packaging Data Sheet P8407294 (see 5.2).

Class	Characteristic	AQL
Critical:	None defined.	
Major:		
101	Illegible or incorrect marking.	1.0
102	Improper location of marking.	1.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:01Z
Check the source to verify that this is the current version before use.

Class	Characteristic	AQL
103	Improper level of packaging and packing (see procurement documents).	1.0
104	Inadequate cleaning and drying.	1.5
105	Container not as specified.	1.0
106	Improper closure of interior package.	1.5
107	Improper closure of shipping container.	1.5

4.5.3 Testing. Unless otherwise specified, prior to submission of sling assemblies for acceptance, the contractor shall have tested each head handling strap assembly, stabilizing strap assembly and strap assembly using the proof loads and the direction of loading specified on the applicable drawing. Failure of strap assemblies to meet the proof load requirements shall be cause for rejection of the individual assembly.

5. PREPARATION FOR DELIVERY

5.1 Pilot pack. A pilot pack consisting of complete and packed unit and intermediate packages, as applicable, packaged in accordance with Packaging Data Sheet P8407294 to the level of protection specified in the contract shall be forwarded as specified in the contract.

5.2 Preservation, packaging, packing and marking. Sling assemblies shall be unit packaged, packed and marked in accordance with requirements of Packaging Data Sheet P8407294 for the level of protection specified in the contract (see 6.1).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. List of documents and specifications pertinent to the sling assembly showing applicable revision dates.
c. Requirements for submitting of sling assembly for first article sample by the contractor (see 3.1).
d. Provision for proof load testing and procedures other than specified (see 3.2.5 and 4.5.3).
e. Unit packaging and packing and levels of protection required (see 5.2).

6.2 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208, as appropriate, on the Management Control Systems Summary List, DD Form 1660.

Custodian:
Army - WC

Review activity:
Army - MI

Preparing activity:
Army - WC

Project number:
1055-A032

Source: https://assist.dla.mil -- Downloaded: 20260-18T03:01Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-S-14268A(WC) Sling Assembly, Head Handling, 762MM Rocket, M6

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)

SUBMITTED BY (Printed or typed name and activity - Optional) | DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
HEADQUARTERS
U. S. ARMY WEAPONS COMMAND
ROCK ISLAND, ILLINOIS 61201

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding General
U. S. Army Weapons Command
ATTN: AMSWE-REE-S
Rock Island, Illinois 61201

FOLD

To detach this form, cut along this line.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:01Z
Check the source to verify that this is the current version before use.