DD–C–581a
May 1, 1967
SUPERSEDING
Fed. Spec. DD–C–581
July 30, 1952, and
MIL–G–1385
September 12, 1949

FEDERAL SPECIFICATION

COVER GLASS; LANTERN SLIDE, PHOTOGRAPHIC

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers lantern-slide cover glasses as specified in 1.2.

1.2 Classification.

1.2.1 Types and sizes. Lantern-slide cover glasses shall be of the following types and sizes, as specified:

Type I —Cover glass having a cut edge.
Size 1—2 x 2 inches
Size 2—3¼ x 4 inches

Type II—Cover glass having a ground edge.
Size 1—2 x 2 inches
Size 2—3¼ x 4 inches

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

Federal Specifications:

PPP–B–636—Box, Fiberboard.
PPP–B–640—Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP–B–676—Boxes, Setup.
PPP–S–760—Strapping, Nonmetallic, (and Connectors).
PPP–T–97 —Tape; Pressure-Sensitive Adhesive, Filament Reinforced.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index which includes cumulative monthly supplements as issued is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Ft. Worth, Denver, San Francisco, Los Angeles, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL–P–116—Preservation, Methods of.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.
MIL–STD–129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The glass shall be of high quality, clear glass which shall be clean and free from defects which would impair the serviceability.

3.2 Color. Cover glass shall be clear commercial grade. It shall be colorless as judged by the unaided eye, except that when viewed edgewise, it shall possess not more than a slight greenish tint. The greenish tint shall not be of such density as to be noticeable in the projection of color slides.

3.3 Construction. Type I cover glass shall have a cut edge. Type II cover glass shall have a ground edge.

3.4 Size and thickness.

3.4.1 Size 1. Actual size of cover glass having a nominal size of 2 by 2 inches shall be $1\frac{15}{16}$ inches by $1\frac{15}{16}$ inches with a tolerance of plus or minus $\frac{1}{64}$ inch.

3.4.1.1 Thickness. The thickness of size 1 cover glass shall be as follows:

Minimum thickness—0.030 inch.
Maximum thickness—0.043 inch.

3.4.2 Size 2. Actual size of cover glass having a nominal size of $3\frac{1}{4}$ inches by 4 inches shall be $3\frac{7}{32}$ inches by $3\frac{31}{32}$ inches with a tolerance of plus or minus $\frac{1}{32}$ inch.

3.4.2.1 Thickness. The thickness of size 2 cover glass shall be as follows:

Minimum thickness—0.043 inch.
Maximum thickness—0.055 inch.

3.5 Workmanship. Uniformity of physical characteristics shall be maintained within the limits which will insure that no significant difference in any characteristic shall be noticeable.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance inspection of equipment before preparation for delivery (see 4.3).
(b) Quality conformance inspection of preparation for delivery (see 4.4).

4.3 Quality conformance inspection of equipment before preparation for delivery. The contractor shall perform the inspection specified in 4.3.2 and 4.3.3. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. The Government will review and evaluate the contractor's inspection procedures. In addition, the Government, at its discretion, may perform all or any part of the specified inspection to verify the contractor's compliance with specified requirements (see 6.3).

4.3.1 Inspection lot. A lot for inspection shall consist of all material of the same type submitted for inspection and delivery at one time. When more than one size cover glass is specified, the inspection lot

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

may consist of all sizes presented at one time. In this case, sampling shall be in proportion to the respective sizes. The acceptable quality level shall be applicable to the entire lot regardless of defects as they may occur in any one or more cover glasses.

4.3.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105. The acceptable quality level (AQL) shall be 2.5 defects per hundred units (DPHU).

4.3.3 Examination. Cover glass shall be examined for the defects listed in table I.

Table I. Examination for Defects.

Examine	Defects
Material	Not clear, colorless glass as specified.
Construction, Appearance, and Workmanship	Any striation, bubble, scratch, opaque area or other defect which affects serviceability. Corners not square and in true 90 degree alignment. Cut edge (Type I) not uniform and even. Ground edge (Type II) not uniformly and evenly ground. Any foreign matter embedded in glass. Not clean. Dimensions not within specified tolerance.

4.4 Quality conformance inspection of preparation for delivery. Preparation for delivery shall be inspection in accordance with MIL-P-116 to determine conformance to the requirements of section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging. Preservation and packaging shall be Level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. The cover glass shall be cleaned in accordance with C-1 of MIL-P-116.

5.1.1.2 Drying. The cover glass shall be dried in accordance with MIL-P-116.

5.1.1.3 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.3.1 Size 1. The cover glass, Type I or II, size 1 shall be packaged Method III. Units of 36, 50 or 100 sheets, as specified by the procuring agency, shall be adequately cushioned and placed within a close-fitting paperboard box, type I, conforming to PPP-B-676. Closure shall be made in accordance with the appendix to the box specification.

5.1.1.3.2 Size 2. The cover glass, Type I or II, size 2 shall be Method III, Units of 12 and 360 sheets shall be packaged as specified in 5.1.1.3.1. Units of 1108 sheets shall be adequately cushioned and placed within a close-fitting fiberboard box conforming to PPP-B-636, adequately cushioned and placed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class Domestic, Closure shall be in accordance with the appendix to the box specification.

5.1.1.4 Intermediate packaging. A quantity of cover glasses packaged as specified in 5.1.1.3 shall be placed in intermediate containers conforming to PPP-B-636, type CF, class weather-resistant, style RSC. Closure and waterproofing shall be made in accordance with the appendix to the box specification.

5.1.2 Level C. The cover glass shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

5.2 Packing shall be Level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Unless otherwise specified, a quantity of cover glasses, packaged as specified in 5.1, shall be packed in a close-fitting fiberboard box conforming to PPP–B–640, class 2, grade A, style E. Closure shall be in accordance with the appendix to the box specification. The shipping containers shall be reinforced by pressure-sensitive filament tape or non-metallic banding conforming to PPP–T–97 and PPP–S–760 respectively, as prescribed in the appendix of the box specification.

5.2.2 Level B. Unless otherwise specified, a quantity of cover glasses, packaged as specified in 5.1, shall be packed as specified in 5.2.1 except the fiberboard box shall be class 1.

5.2.3 Level C. The cover glass, packaged as specified in 5.1, shall be packed in shipping containers to afford adequate protection against damage to the package and its contents during shipment from the supply source to the first receiving activity. Shipping containers shall comply with the rules and regulations of the common carrier as applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL–STD–129 (see 6.2). The nomenclature shall be as follows: Cover Glass; Lantern Slide, Photographic (Type (applicable data to be entered by contractor), inches wide, inches long, inches thick, and size), Federal Specification DD–C–581.

6. NOTES

6.1 Intended use. Glass covered by this specification is intended for use in binding black and white lantern slides and clear transparencies for projection.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification and any amendment thereto.
(b) Type and size required (see 1.2).
(c) Levels of preservation, packaging, packing, and marking (see section 5).
(d) Marking and shipping of samples.
(e) Place of final inspection.
(f) Responsibility for inspection (see 4.1).

6.3 Verification inspection. Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

MILITARY INTEREST:
Custodians:
Army—EL
Navy—WP
Air Force—70
Review Activities:
Navy—WP
Air Force—85
Other—NSA
User Activities:
Navy—SH
Preparing Activity:
Army—EL

CIVILIAN AGENCIES INTEREST:
AG
JUS
VA—DMS

U.S. Government Printing Office: 1967.

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price of this specification is 5 cents each.

☆ U.S. GOVERNMENT PRINTING OFFICE : 1967 O - 302-502 (91)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

FOLD

PARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING GENERAL
U.S. ARMY ELECTRONICS COMMAND
ATTN: AMSEL-PP-E-SED
FORT MONMOUTH, N.J. 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEM PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:43Z
Check the source to verify that this is the current version before use.