DD-P-00100C(GSA-FSS)
April 30, 1970
INTERIM REVISION OF
Fed. Spec. DD-P-100b
July 9, 1963

INTERIM FEDERAL SPECIFICATION

PAPERWEIGHT, GLASS

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification DD-P-100b, dated July 9, 1963.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers glass paperweights for general office use.

1.2 Classification.

1.2.1 Types. Paperweights shall be of the following types, as specified (see 6.2).

Type I - Semi-spherical.
Type II - Rectangular.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-576 - Boxes, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes.
PPP-B-636 - Box, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

(Copies of Military Standards required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Ill. 60606.)

National Classification Board:

National Motor Freight Classification.

(Application for copies shall be addressed to the American Trucking Association, Inc., Attention: Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

3. REQUIREMENTS

3.1 Material. The glass used in the manufacture of the paperweights shall be solid and clear, and shall be of such quality and strength to insure that the paperweights will not crack or break when tested as specified in 4.4.1.

3.2 Type I, semi-spherical.

3.2.1 Design and construction. The paperweight shall conform to the material requirements as specified in 3.1. The shape of the paperweight shall be approximately the half of a sphere, and the bottom shall have a cutout. All edges shall be rounded and the surfaces shall have a smooth finish. The base shall rest firmly on any flat surface.

3.2.2 Dimensions. The bottom diameter shall be 3 inches ± 1/8 inch; the over-all height shall be 1-1/2 inches ± 1/8 inch; the bottom cutout diameter shall be 2 inches ± 1/8 inch, with a height of not less than 3/16 inch and not more than 9/16 inch. The stated dimensions shall be exlusive of rounded edges.

3.2.3 Weight. The weight of the paperweight shall be not less than 8-1/4 ounces.

3.3 Type II, rectangular.

3.3.1 Design and construction. The paperweight shall conform to the material requirements as specified in 3.1. The paperweight shall be of a rectangular shape. All edges shall be rounded and the surfaces shall have a smooth finish. The base shall rest firmly on any flat surface.

3.3.2 Dimensions. The bottom length shall be 4-1/4 inches ± 1/4 inch; the bottom width shall be 2-3/4 inches ± 1/16 inch; and the over-all height shall be 3/4 inch ± 1/8 inch. The stated dimensions shall be exclusive of rounded edges.

3.3.3 Weight. The weight of the paperweight shall be not less than 10-3/4 ounces.

3.4 Workmanship. The paperweights shall be free from foreign material, sand holes, bubbles, chips, and other defects which may affect their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. All paperweights of the same type presented for inspection at one time shall be considered a lot for the purpose of examinations and tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling for inspection. Sampling for inspections shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random sample of paperweights shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one paperweight. The paperweights shall be examined for defects listed in table I. The Inspection Level shall be S-4, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for tests. Random sample of paperweights for each test shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one paperweight. The paperweights shall be tested as specified in 4.4.1. The Inspection Level shall be S-2 and the AQL shall be 4.0 percent defective.

4.3 Examination.

4.3.1 Visual and dimensional examination for end items. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

TABLE I. Classification of defects

Examine	Defects
Material	Glass not solid and clear (see 3.1).
Design and Construction	Paperweight not type and shape specified. Edges not rounded (see 3.2.1 or 3.3.1). Surface does not have a smooth finish (see 3.2.1 or 3.3.1).
Dimensions	Dimensions not as specified (see 3.2.2 or 3.3.2).
Weight	Not as specified (see 3.2.3 or 3.3.3).
Workmanship	Not in accordance with 3.4.

4.3.2 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing and marking requirements of section 5 are complied with.

4.4 Tests.

4.4.1 End item tests. Samples selected in accordance with 4.2.4 shall be subjected to the following tests. Any paperweight failing the test shall be considered defective. If the number of defective paperweights exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected.

4.4.1.1 Drop test. The paperweight shall be dropped edgewise three times from a height of 30 inches to a wooden floor to assure compliance with the requirements stated in 3.1.

4.4.1.2 Thermal shock. The paperweights shall be heated to 140°F., and than immersed into a cold water bath of 70°F. for 30 seconds to insure compliance with the requirements stated in 3.1.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C as specified (see 6.2).

5.1.1 Level A. Twelve paperweights shall be packaged in a box conforming to PPP-B-636, type CF, class weather-resistant, V3c. The box shall be provided with dividers to form an individual cell for each paperweight. The dividers shall be made of the same material as the box.

5.1.2 Level B. Twelve paperweights shall be packaged as specified in 5.1.1 except the box shall be class domestic.

5.1.3 Level C. Paperweights shall be packaged in accordance with the manufacturer's commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Six unit packages (72 paperweights) shall be packed in a close-fitting box conforming to PPP-B-585, class 3; PPP-B-591, class II; PPP-B-601, overseas type; PPP-B-621, class 2; PPP-B-636, V3c or V3s; or PPP-B-576. Box closures and strapping shall conform to the applicable box specification and the appendix thereto.

5.2.2 Level B. Paperweights shall be packed as specified for level A, except that domestic type or class boxes shall be used and case liners and strapping shall not be required.

5.2.3 Level C. The paperweights packaged as specified in 5.1 shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification or National Motor Freight Classification.

5.3 Marking. In addition to any special marking required by the contract or order (see 6.2), the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

6. NOTES

6.1 Intended use. The paperweights covered by this specification are intended to hold down papers, maps, charts, drawings, etc.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of paperweight required (see 1.2.1).
(c) Level of packaging and packing required (see 5.1 and 5.2).
(d) Any special marking required (see 5.3).

GSA DC 70-13683

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.