MIL-STD-35-72(MI)
NOTICE 1
15 January 1975

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

ACTUATORS. ELECTROMECHANICAL, ROTARY

TO ALL HOLDERS OF MIL-STD-35-(MI)

1. The following pages of MIL-STD-35-72(MI) have been revised and supersede the pages listed:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	15 January 1975	v	22 May 1974
vi	15 January 1975	vi	22 May 1974
vii	15 January 1975	vii	22 May 1974
viii	15 January 1975	viii through X	22 May 1974
5	15 January 1975		22 May 1974
6	15 January 1975	6	22 May 1974
7	15 January 1975	7	22 May 1974
a	15 January 1975	8	22 May 1974
9		9 through 22	22 May 1974
23	15 January 1975	Reprinted without change	
24	15 January 1975	24 through 26	22 May 1974
27	15 January 1975		22 May 1974
41	22 May 1974	Reprinted without change	
42	15 January 1975	42 through 46	22 May 1974
47	15 January 1975	47	22 May 1974
48	22 May 1974	Reprinted without change	
49	22 May 1974	Reprinted without change	
50	15 January 1975	60	22 May 1974
113	22 May 1974	Reprinted without change	
114	15 January 1975	114 through 146	22 May 1974
165	15 January 1975	165 through 170	22 May 1974

2. Main this notice page and insert before the Table of Contents.

3. Holder this notice page and intnsert before the Table of Contents. additions indicated above have been entered. Tho notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-A098

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
1.0	Actuators, Electromechanical, Rotary	1
1.1	Specification Title Index	3
1.2	Specification Requirements Instructions	5
1.2.1	General	5
1.2.2	Approved Item Name Code	6
1.2.3	Figure Number	6
1.2.4	Dimensions	6
1.2.5	Tabulation	6
1.2.6	Deleted	
1.2.7	Deleted	
1.2.8	Deleted	
1.2.9	Applicable Documents	8
	NOTE: Paragraphs 1.2.10 through 1.2.19 have been deleted.	
1.2.20	Design Characteristics	9
1.2.20.1	Starting Current	9
1.2.2002	Operating Current	9
1.2.20.3	Acceleration	23
1.2.20.4	Operating Speed With Load	23
1.2.20.5	Operating Speed Without Load	23
1.2.20.6	Breakaway Torque	23
1.2.20.7	Overtravel	24

Supersedes page v of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	Text
1.2.21	Deleted	
1.2.22	Deleted	
1.2.23	Travel	24
1.2.24	operating Torque	24
1.2.25	Stall Torque	27
1.2.26	Holding Torque	27
1.2.27	Rated Load	27
1.2.28	Maximum Operating Load	27
1.2.29	Stall Load	27
1.2.30	Output Shaft Revolutions	27
1.2.31	Backlash	29
1.2.32	Coast	29
1.2.33	Repeatability	29
1.2.34	Travel Limit Stops	29
1.2.35	Brakes	30
1.2.36	Operating Speed Adjustments	31
1.2.37	Reversibility	31
1.2.38	Position Transmitters	31
1.2039	Thermal Protection	32
1.2.40	Duty Cycle	32
1.2.41	Over-Riding Loads	32

Supersedes page VI of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.42	Rated Life	32
1.2.43	clutch	33
1.2.44	Motor-to-Output Shaft Gear Ratio	33
1.2.45	Output Shaft Side Loading	33
1.2.46	Motor	33
1.2.47	Efficiency	34
1.2.48	Power Consumption	34
1.2.49	Input Power	34
1.2.50	Electrical Connectors	35
1.2.51	Electrical Wiring	35
1.2.52	Electrical Connections	35
1.2.53	Weight	35
1.2.54	Locking of Parts	35
1.2.55	Housing	36
102.56	Output Shaft	36
1.2.57	Lubrication	36
1.2.58	Retaining Rings	37
1.2.59	Spring Pins	37
1.2060	Operating Temperature	37
1.2.61	Storage Temperature	37
1.2.62	Operating Altitude Range	38

Supersedes page vii of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.63	Nameplate and Product Marking	38
1.2.64	Wiring Diagram Nameplate	38
1.2.65	Motor Data Nameplate	38
1.2.66	Lubrication Data Nameplate	39
1.2.67	Interference (Conducted)	39
1.2.67.1	Test Methods	39
1.2.67.2	Requirements	39
1.2.68	Interference (Radiated)	40
1.2.68.1	Test Methods	40
1.2.68.2	Requirements	40
1.2.69	Electrical and Environmental Test Methods and Requirements	41
1.2.69.1	Test Methods	41
1.2.69.2	Requirements	42
	Specification Requirements List (SRL)	47
1.3	Configuration and Drawings	147
1.3.1	Figure Titles vs Figure Numbers	149
1.3.2	Legend Index	151
	Figures 250-01-1 through 250-02-1	155-163
	Reproducible Foldout Specification Requirement Sheet (SRS) Form	165

Supersedes pages viii through x of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SECTION 1.2

SPECIFICATION REQUIREMENTS INSTRUCTIONS

1.2.1 General

The purpose of these Instructions Is to establish the procedures to be followed, and the format to be used, for submission of requirements to obtain a computer generated procurement document.

The requester will find it impossible to complete an SRS using only this dash numbered part of MIL-STD-35. information which is standard for all generic families has been included in the master document at the issuance of MIL-STD-35C. This Information is not repeated for each dash numbered part. The following list contains the subjects which are pertinent to every family unless otherwise excepted.

General Description of AEDPS
Part Numbering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi-Item Specification (Tabulation)
Sources
Search
General Instructions for SRL
Tables A through S

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

1.2.2 Approved Item Name Code

The item name code for an actuator, to be entered on the SRS with Code 1007, is. selected from the Item Name Code column of the following list.

Approved Item Name	Item Name Code
Actuator, Electromechanical, Rotary	11006
Unapproved Name	77777

1.2.3 Figure Number

Code 1009 must show the figure number selected from Section 1.3.

1.2.4 Dimensions

MIL-STD-35 must be used in conjunction with this dash numbered part to completely delineate the dimensions for an actuator.

The figures and corresponding legends, representing different configurations of actuators, are located in the rear of this document. The figure number (representing the selected figure) is mandatory and shall be entered on the SRS with Code 1009. The figure legends in this document (AA, AB, AC, etc.) representing dimensions shall be employed with corresponding legends in Table A of MIL-STD-35.

The remaining instructions for dimensioning actuators are in MIL-STD-35.

1.2.5 Tabulation

The explanation of, and the instructions for using tabulation-are found in MIL-STD-35. Candidates for tabulation for this part are the. dimensional codes shown in Table A of MIL-STD-35 and the following.

TABULATION CANDIDATES FOR ROTARY ACTUATORS

Characteristic Code	Title
1562	Minimum Starting Current (amperes)
1564	Maximum Starting Current (amperes)
1566	Minimum Starting Current (milliamperes)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

TABULATION CANDIDATES FOR ROTARY ACTUATORS (CONT)

Characteristic Code	Title
1568	Maximum Starting Current (milliamperes)
1570	Minimum Operating Current (amperes)
1572	Maximum Operating Current (amperes)
1574	Minimum Operating Current (milliamperes)
1576	Maximum Operating Current (milliamperes)
1588	Nominal Operating Speed Under Rated Load (RPM)
1598	Nominal Operating Speed Under Maximum Operating-Load (RPM)
1608	Nominal Operating Speed Under No-Load Condition (RPM)
1648	Holding Torque (pound-inches)
1650	Rated Load (pounds)
1652	Maximum Operating Load (pounds)
1654	Stall Load (pounds)
1768	Maximum Side Loads Output Shaft may be Subjected to (pounds)
3212	Power Consumption at Rated Load (watts)
3234	Actuator Weight (ounces)
3236	Actuator Weight (pounds)

NOTE: Paragraphs 1.2.6, 1.2.7, and 1.2.8 have been deleted.

Supersedes page 7 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

1.2.9 Applicable Documents

In addition to the documents contained in the Applicable Document List of MIL-STD-35, the documents that follow shall be entered on the SRS with appropriate codes from Table B of MIL-STD-35.

Documents	Codes or Other Conditions
MIL-STD-130	Mandatory
MIL-STD-810	When a characteristic code specifying a test method in MIL-STD-810 is entered on the SRS.
MIL-STD-461	2512 and 2514 (Conducted Interference) and 2530 (Radiated Interference)
MIL-STD-462	2504 and 2506 (Conducted Interference) and 2524 (Radiated Interference)
MIL-STD-704	3222 (Input Power)
MIL-M-7969	3204 and 3206 (Motor)
MIL-M-8609	3200 and 3202 (Motor)
MS16624	3264 (Retaining Rings)
MS16625	3264 (Retaining Rings)
MS20995	3246 (Locking of Parts)
MS33540	3246 (Locking of Parts)
633547	3272 (Spring Pin Usage)
NAS561	3268 (Spring Pins)

NOTE: Paragraphs 1.2.10 through 1.2.19 have been deleted.

Supersedes page 8 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

1.2.20 Design Characteristics

It is mandatory to specify design characteristics on the SRS with at least one of the following.

1.2.20.1 Starting Current

Starting current maybe specified in amperes or in milliamperes with one of the following:

a. Amperes. Write in the minimum value (amperes) with Code 1562, or write in the maximum value (amperes) with Code 1564, or write in both the minimum and the maximum value (amperes) with Codes 1562 and 1564, respectively.

b. Milliamperes. Write in the minimum value (milliamperes) with Code 1566, or write in the maximum value (milliamperes) with Code 1568, or write in both the minimum and the maximum values (milliamperes) with Codes 1566 and 1568, respectively.

1.2.20.2 operating Current

Operating current may be specified in amperes or in milliamperes with one of the following:

a. Amperes. Write in the minimum value (amperes) with Code 1570, or write in the maximum value (amperes) with Code 1572, or write in both the minimum and the maximum values (amperes) with Codes 1570 and 1572, respectively.

Supersedes pages 9 through 22 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

b. Milliamperes. Write in the minimum value (milliamperes) with Code 1574, or write in the maximum value (milliamperes) with Code 1576, or write in both the minimum and the maximum values (milliamperes) with Codes 1574 and 1576, respectively.

1.2.20.3 Acceleration

The time in which the actuator shall reach rated speed either under maximum operating load or under rated load may be specified by using one of the following:

a. Maximum Operating Load. Write in the time value (seconds) with Code 1580.

b. Rated Load. Write in the time value (seconds) with Code 1582.

1.2.20.4 Operating Speed With Load

The actuator operating speed either under rated load or under maximum operating load may be specified by using one of the following:

a. Rated Load. Write in both the minimum and the maximum speed values (RPM) with Codes 1584 and 1586, respectively; or write in the nominal speed value (RPM) with Code 1588; or write in the two values, time (seconds) per (degrees of arc) with Codes 1590 and 1592, respectively.

b. Maximum Operating Load. Write in both the minimum and the maximum speed values (RPM) with Codes 1594 and 1596, respectively; or write in the nominal speed value (RPM) with Code 1598; or write in the two values, time (seconds) Per (degrees of arc) with Codes 1600 and 1602, respective y.

1.2.20.5 Operating Speed Without Load

The actuator operating speed under no-load conditions may be specified by writing in both the minimum and the maximum speed values (RPM) with Codes 1604 and 1606; or by writing in the nominal speed value (RPM) with Code 1608; or by writing in the two values, time (seconds) per degrees. of arc) with Codes 1610 and 1612, respectively.

1.2.20.6 Breakaway Torque

A requirement that the actuator shall provide, at the output shaft, a breakaway torque may be specified by writing in both the minimum and the maximum torque values (pound-inches) with Codes 1614 and 1616, respectively; or by writing in the minimum torque value (pound-inches)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

with Code 1614; or by writing in the maximum torque value (pound-inches with Code 1616; or by writing in the nominal torque value (pound-inches with Code 1618.

1.2.20.7 Overtravel

The maximum allowable actuator shaft overtravel may be specified by writing in both the overtravel values (degrees or arc) and (minutes of arc) with Codes 1620 and 1622, respectively; or by writing in the over-travel value (degrees of arc) with Code 1620; or by writing in the over-travel value (minutes of arc) with Code 1622.

NOTE: Paragraphs 1.2.21 and 1.2.22 have been deleted.

1.2.23 Travel

The direction and amount of rotation that the actuator shaft shall be capable of may be specified on the SRS by writing in both the amount of clockwise rotation (degrees) with Code 1624 and the amount of counter-clockwise rotation (degress) with Code 1626; or by writing in the amount of clockwise rotation only (degrees) with Code 1628; or by writing in the amount of counterclockwise rotation only with Code 1630; or by writing in the amount of rotation in either direction (degrees) with Code 1632.

It may also be specified that clockwise and counterclockwise direction is determined when facing the output shaft end of the actuator by entering an “X” with Code 1634.

1.2.24 Operating Torque

The operating toque that the actuator shall provide at the output shaft may be specified on the SRS by writing in both the minimum and the maximum values (pound-inches) with Codes 1636 and 1638, respectively; or by writing in the minimum value (pound-inches) with Code 1636; or by writing in the maximum value (pound-inches) with Code 1638: or by writing in the nominal value (pound-inches) with Code 1640.



Supersedes pages 24 through 26 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

1.2.25 Stall Torque

The actuator stall torque may be specified on the SRS by writing in the minimum value (pound-inches) with Code 1642; or by writing in the maximum value (pound-inches) with Code 1644; or by writing in both the minimum and the maximum values (pound-inches) with Codes 1642 and 1644, respectively; or by writing in the nominal value (pound-inches) with Code 1646.

1.2.26 Holding Torque

The actuator static holding torque may be specified on the SRS by writing in the torque value (pound-inches) with Code 1648.

1.2.27 Rated Load

Rated load may be specified on the SRS by writing in the load value (pounds) with Code 1650.

1.2.28 Maximum Operating Load

Maximum operating load may be specified on the SRS by writing in the load value (pounds) with Code 1652.

1.2.29 Stall Load

Stall load may be specified on the SRS by writing in the load value (pounds) with Code 1654.

1.2.30 Output Shaft Revolutions

The number and direction of revolutions that the actuator output shaft shall be capable of may be specified on the SRS by using one *of* the following:

a. Write in both the number of revolutions in the clockwise direction with Code 1656 and the number of revolutions In the counterclockwise direction with Code 1658.

b. Write in the number of revolutions in the clockwise direction only with Code 1660.

c. Write in the number of revolutions in the counterclockwise direction only with Code 1662.

d. Enter an “X” with Code 1664 to specify that there shall be no limitation on the number of output shaft revolutions in either direction.

Supersedes pages 27 and 28 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

1.2.69 Electrical and Environmental Test Methods and Requirements

The instructions contained in this paragraph shall be followed when it is desired to make exceptions to the test methods and requirements of any of the following tests:

Altitude

High Temperature

Low Temperature

Temperature Shock

Rain

Humidity

Fungus Resistance

Salt Fog

Dust

Explosive Atmosphere

Leakage (Immersion)

Acceleration

Vibration

Acoustical Noise

Shock

Combined Temperature-Humidity-Altitude

When a code is shown for any test method, It is mandatory that a requirement code be shown. However, the first test method code and the first requirement code should not be used together, since that combination makes no exception to the specification referenced with Code 1006.

1.2.69.1 Test Methods

The test method may be specified on the SRS by using one of the following codes:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

a. If the first test method is desired, use the first test method code with an "X" to specify testing per the specification referenced with Code 1006.

b. If.the second test method is desired, use the second test method code and complete the sentence with the specified exceptions, for testing per the referenced specification with exceptions. The exceptions stated must be limited to 189 characters, including punctuation and spaces.

c. If testing is to be detailed, one or more of the test method codes should be used to specify test conditions. All codes marked with an asterisk "*" must be used.

If the specification referenced with Code 1006 specifies a MIL-STD-81O test method and exceptions are to be taken, the second test method code (see b. above) should be used if the exceptions can be stated within the 189 character limitation; the third test method (see c. above) should be used if the exceptions cannot be stated within the limitation.

1.2.69.2 Requirements

If the requirements specified in the specification shown with Code 1006 are to be used, the first requirements code should be shown, with an "X" on the SRS. If exceptions to the requirements specified in the specification shown with Code 1006 are to be made, the second require-ments code should be shown with exceptions written in on the SRS to complete the sentence. If the requirements are to be changes In parameter values as a result of the environmental test, one or more of the remaining requirements codes with the applicable fill-in values must be shown. When the third requirements code is shown, the requirements that there be no evidence of physical damage or degradation of performance will be included automatically.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Amry-MR
Amry- SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-A098

Supersedes pages 42 through 46 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	
1.2.1	Enter on SRS, requirements from MIL-STD-35.	
	NOTE: Reference paragraphs 1.2.12 through 1.2.19 have been deleted. These characteristic names and codes are now contained in MIL-STD-35.	
1.2.20	*Design Characteristics (Select one or more and enter value)	
1.2.20.1	Starting current	
	Minimum (amps)	1562
	Maximum (amps)	1564
	or	
	Minimum (milliamps)	1566
	Maximun (milliamps)	1568
1.2.20.2	Operating current	
	Minimum (amps)	1570
	Maximum (amps)	1572
	or	

*INDICATES MANDATORY REQUIREMENT
Supersedes page 47 of 22 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN,

REF, PARA,	CHARACTERISTIC NAME	CODE
1.2.20.2 Cont	Minimum (milliamps)	1574
	Maximum (milliamps)	1576
1.2.20.3	Acceleration (Select one and enter value)	
	Time required to reach rated speed with maximum operating load (seconds)	1580
	or	
	Time required to reach rated speed with rated load (seconds)	1582
1.2.20.4	Operating speed with load (Select rated load or max operating load)	
	Rated load (Select one)	
	Minimum speed (RPM)	1584
	*Maximum speed (RPM)	1586
	or	
	Nominal speed (RPM)	1588
	or	
	Time (seconds)	1590
	*Per rotational movement (deg of arc)	1592
	or	

*INDICATES MANDATORY REQUIREMENTS

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN,

REF. PARA.	CHARACTERISTIC NAME	CODE
1.2.20.4 Cont.	Maximum operating load (Select one)	
	Minimum speed (RPM)	1594
	*Maximum speed (RPM)	1596
	or	
	Nominal speed (RPM)	1598
	or	
	Time (seconds)	1600
	*Per rotational movement (deg of arc)	1602
1.2.20.5	Operating speed without load (Select one)	
	Minimum speed (RPM)	1604
	*Maximum speed (RPM)	1606
	or	
	Nominal speed (RPM)	1608
	or	
	Time (seconds)	1610
	*Per rotational movement (deg of arc)	1612

*INDICATES MANDATORY REQUIREMENTS
Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
1.2.20.6	Breakaway torque	
	Minimum torque (pound-inches)	1614
	Maximum torque (pound-inches)	1616
	or	
	Nominal torque (pound-inches)	1618
1.2.20.7	Overtravel	
	Shall not exceed	
	Deg of arc	1620
	Minutes of arc	1622
	Note: If the Requirements and Quality Assurance Provisions in the specification shown with Code 1006 meet the users requirements, Characteristic Codes without an asterisk "*" in the far left edge should not be used. The generated document will then specify all of the requirements and tests of the referenced specification.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF. PARA.	CHARACTERISTIC NAME	CODE
1.2.69.1 Cont	Operating speed with load	2462
	Operating speed without load	2466
	Breakaway torque	2468
	Overtravel	2469
	Measurements after test (Select one or more)	
	Starting current	2470
	Operating current	2472
	Acceleration	2474
	Operating speed with load	2476
	Operating speed without load	2478
	Breakaway torque	2480
	Overtravel	2481
1.2.69.2	Requirement (Select one) (Mandatory if either Code 2450, 2452, or 2454 is selected) /	
	Requirements per Specification shown with Code 1006	2482
	or	

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.69.2 Cont	Requirements per Specification shown with Code 1006 except .	2484
	or	
	Requirements as follows:	
	*No evidence of physical damage or degradation of performance	2485
	Pretest requirements per Design Characteristics	2486
	Requirements after test per Design Characteristics	2488

*INDICATES MANDATORY REQUIREMENT

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENT SHEET (SRS)

SHEET___ OF ___

TITLE CODE | REQUESTER NO.

1 2 3 4 5 6 7 8 9 10 11 12

THIS FORM IS USED TO INITIATE A REQUEST FOR AN AEDPS DOCUMENT (SEE PARAGRAPH TITLED SPECIFICATIONS REQUIREMENT SHEET, SECTION 5 OF MIL-STD-35).

MARK IF APERTURE CARDS REQUIRED ☐

MARK IF SEARCH ONLY ☐

REVISION TO AEDPS DOCUMENT NO.:

REQUESTER'S NAME _____

MAILING ADDRESS _____

_____

PHONE NO. A/C _____

ACTUATORS, ELECTROMECHANICAL, ROTARY CHARACTERISTIC NAME	CHAR CODE 13 14 15 16	CHARACTERISTIC VALUE 20 25 30 35 40 45 50 55 60 65 70 75 79	LINE NO. 80
DESIGN CHARACTERISTICS - SELECT ONE OR MORE APPROPRIATE CODE(S)			

☆U.S. GOVERNMENT PRINTING OFFICE: 1975-603-130/1299

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.