MIL-J-7398D(ASG)
2 JANUARY 1968

Superseding
MIL-J-7398C(ASG)
23 May 1957

MILITARY SPECIFICATION

JACK, HAND HYDRAULIC, FOLDING TRIPOD,
30-TON CAPACITY, TYPE B-4A

This specification has been approved by the Department of the Air Force and by the Naval Air Systems Command.

1. SCOPE

1.1 This specification covers one type of adjustable hand jack with 30-ton capacity, designated type B-4A.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	Boxes, Wood, Cleated-Plywood

Military

MIL-P-116	Preservation, Methods of
MIL-H-6083	Hydraulic Fluid, Petroleum Base, for Preservation and Testing
MIL-H-81019	Hydraulic Fluid, Petroleum Base, Ultra-Low Temperature

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-810	Environmental Test Methods
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods

/FSC 1730/

Source: https://assist.dla.mil -- Downloaded: 20260-17T08:27Z
Check the source to verify that this is the current version before use.

DRAWINGS

Air Force

53J6268 Jack Assembly Hand Hydraulic, Folding Tripod, 30-Ton Capacity Type B-4A

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Uniform Classification Committee

Uniform Freight Classification Rules

(Application for copies of the above publication should be addressed to the Uniform Classification Committee. 202 Chicago Union Station, Chicago, Ill. 60606.)

3. REQUIREMENTS

3.1 Preproduction inspection.- This specification makes provision for preproduction inspection (see 4.2).

3.2 General requirements.- The requirements specified on Drawing 53J6268 are applicable as requirements of this specification.

3.2.1 When Drawing 53J6268 and this specification conflict, this specification shall govern.

3.3 Identification of product.- Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.4 Workmanship.- The jack, including all parts and accessories, shall be fabricated and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges; accuracy of dimensions, and marking of parts and assemblies.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:27Z
Check the source to verify that this is the current version before use.

4.2 Classification of tests.- The inspection and testing of the jack shall be classified as follows:

(a) Preproduction inspection (4.3)
(b) Quality conformance inspection (4.4)

4.3 Preproduction inspection.- The preproduction inspection shall consist of the quality conformance inspection, and the tests specified in 4.3.2 through 4.3.3.2.

4.3.1 Test sample.- One jack, as specified in the contract, will be tested for design approval by the procuring activity or, when specified in the contract, at the contractor's plant under the supervision of the procuring activity.

4.3.2 Low temperature.- The jack shall be subjected to low temperature in accordance with MIL-STD-810, Method 502, Procedure I. For this test, the jack shall be serviced with hydraulic fluid conforming to MIL-H-81019. At the end of the exposure, and with the temperature maintained, the jack ram shall be raised to its maximum extension and pumped until the bypass relief valve operates. The lowering valve shall be opened, and the ram shall retract with not more than 50 pounds applied to the ram. The number of full strokes necessary to fully extend the ram shall be recorded at both +70° and -65° F. The full strokes required to fully extend the ram at -65° F shall be not more than double the strokes required at +70° F.

4.3.3 Lift test.- With the screw extension retracted, the jack shall be subjected to the tests specified in 4.3.3.1 and 4.3.3.2.

4.3.3.1 Vertical lift.- The vertical lift test shall consist of 200 cycles of raising and lowering a vertical load of 30 tons. One cycle shall consist of raising the hydraulic ram under load from the fully retracted position to the fully extended position and return to the fully retracted position. Failure of any part of the jack during this test shall be cause for rejection.

4.3.3.2 Variable side load.- The variable side load test shall consist of 60 cycles of raising a 30-ton load vertically with a graduated 4.5-ton horizontal load. Twenty cycles each shall be applied through the jack pad socket adapter in the direction of an opposite jack leg. The horizontal load on the jack adapter shall be gradually increased from zero in the fully retracted position to 4.5 tons in the fully extended position. Failure of any part of the jack during this test shall be cause for rejection.

4.4 Quality conformance inspection.- The quality conformance inspection shall consist of the following:

(a) Individual tests (4.4.1)
(b) Sampling tests (4.4.2)

4.4.1 Individual tests.- Each jack shall be subjected to the tests specified in 4.4.1.1 through 4.4.1.3.

4.4.1.1 Examination of product.- Each jack shall be inspected to determine compliance with the requirements specified herein with respect to workmanship, marking, and compliance with Drawing 53J6268.

Source: https://assist.dla.mil -- Downloaded: 20260-17T08:27Z
Check the source to verify that this is the current version before use.

4.4.1.2 Each ram of the assembled jack shall be tested by applying a minimum hydraulic pressure of 3,000 psi. Any leaking of hydraulic fluid shall be cause for rejection.

4.4.1.3 Each pump shall be tested by sealing the pump outlet and operating the pump until the bypass valve opens. The bypass valve shall be adjusted as specified on Drawing 53J6268.

4.4.2 Sampling tests.- Five jacks shall be selected at random from every 50 or fraction thereof on the order and subjected to the static proof test (see 4.4.2.1).

4.4.2.1 Static proof test.- After the bypass relief valve has been adjusted for overload, the jack shall be tested with the screw extension in the fully extended position by raising a 45-ton load vertically from the lowest position of the hydraulic ram to the fully extended position. While in the extended position, the vertical load shall be reduced to 30 tons and maintained during application of a 4.5-ton horizontal load applied to the top of the extended screw extension. To complete the cycle, the horizontal and vertical loads shall be removed and the jack ram allowed to free fall to its original position. Failure of any part of the jack during this test shall be cause for rejection.

4.4.3 Rejection and retest.- When sampling tests are specified on a number of jacks that are selected from a production run, and one or more of this number fails to meet the specified tests, acceptance of all jacks still on hand and subsequent production will be withheld until the extent and cause of failure is determined. For operational reasons, individual tests may be continued pending investigation of a sampling test failure. However, final acceptance of the jacks on hand and subsequent production is contingent upon the procuring activity's decision regarding the overall conformance of the jacks to specification requirements. When corrective action has been accomplished, all necessary tests shall be repeated. If investigation indicates that the defects may exist in jacks previously accepted, full particulars concerning the defects, including recommendations for correction, shall be furnished to the procuring activity.

4.5 Preservation, packaging, packing, and marking.- Preparation for delivery shall be examined for conformance to section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Disassembly.- Jacks shall be disassembled to accomplish reduction in cubage. Disassembly shall be limited to the extent that reassembly can be performed without requiring the use of special tools. Removed bolts, nuts, washers, and pins shall be placed in one of the mating parts and secured to prevent loss.

5.1.1.2 Cleaning.- Jacks shall be cleaned in accordance with MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:27Z
Check the source to verify that this is the current version before use.

5.1.1.3 Preservation.- Exposed, unpainted metal surfaces of the jacks subject to corrosion shall be preserved in accordance with Method I of MIL-P-116. The hydraulic system shall be filled with fluid conforming to MIL-H-6083.

5.1.2 Level C.- Jacks shall be preserved and packaged in accordance with the supplier's commercial practice.

5.2 Packing.- Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.- Each jack, preserved and packaged as specified in 5.1, shall be packed in a container conforming to PPP-B-601, style A, type II, class 2. Each container shall be provided with four nominal 2-inch by 4-inch skids and shall be equal in length to the width of the container. The ends of each skid shall be beveled on a 45-degree angle to one-half thickness, from the broad face to the center of the end-grain surface.

5.2.2 Level B.- Packing shall be the same as for level A, except the containers shall be type II, class 1.

5.2.3 Level C.- Jacks, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules, and rules of other carriers applicable to the mode of transportation.

5.3 Physical protection.- Shipping containers shall be anchored, cushioned, blocked, and braced in accordance with MIL-STD-1186. Cornerwise drop tests shall be in accordance with MIL-STD-1186. The tests are not required when level C packing is specified.

5.4 Marking.- In addition to any special marking specified in the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The type B-4A jack covered by this specification is intended for use as an aircraft wing jack.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Where the preproduction test shample should be sent, the activity responsible for testing, and instructions concerning the submittal of the test reports (see 4.3.1).
(c) Selection of applicable levels of preservation, packaging, and packing requirements (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:27Z
Check the source to verify that this is the current version before use.

6.3 International standardization.- Certain provisions of this specification are the subject of international standardization agreement ASCC AIR STD 11/7A. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

Custodians:
Navy - AS
Air Force - 82

Reviewer activities:
Navy - AS
Air Force - 82

International interest (see 6.3)

Preparing activity:
Air Force - 82

Project No. 1730-0048

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:27Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget
Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION
MIL-J-7398D(ASG) Jack, Hand Hydraulic, etc., Type B-4A

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A
( ) Direct Government Contract ( ) Subcontract

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID.

3. IS THE SPECIFICATION RESTRICTIVE?
   ( ) YES ( ) NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)

SUBMITTED BY (Printed or typed name and activity) DATE

DD Form 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:27Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY

OFFICIAL BUSINESS

Aeronautical Standards Group (ASG)

8719 Colesville Rd.

Silver Spring, Md. 20910

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:27Z
Check the source to verify that this is the current version before use.