MILITARY SPECIFICATION

MAINTENANCE PLATFORM, AIRCRAFT, TYPE B-5A

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 scope. This specification covers one type of aircraft maintenance platform, designated type B-5A,

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-N-95	Naphtha; Aliphatic.
UU-T-81	Tags, Shipping and Stock.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-636	Box, Shipping, Fiberboard.

MILITARY

MIL-P-116	Preservation, Methods of.
MIL-E-5272	Environmental Testing, Aeronautical and Associated Equipment, General Specification for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: The Engineering Division, San Antonio ALC/MMEDO, Kelly AFB, TX 78241 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.

MIL-C-5501	Cap, Protective, Dust and Moisture Seal for Resistoflex Dynatube Fittings.
MIL-H-5606	Hydraulic Fluid, Petroleum Base; Aircraft; Missile, and Ordnance.
MIL-H-6083	Hydraulic Fluid, Petroleum Base, for Preservation and Testing.

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of US Military Property.
MIL-STD-162	Materials Handling Equipment, Preparation for Shipment, Storage, Cyclic Maintenance, Routine Testing and Processing.
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods.

* (Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this Specification to the extent specified herein.

DRAWING

AIR FORCE

54J6279	Maintenance Platform Assembly, Aircraft Type B-5A Assembly of.

* (Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence . In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

2.2 Other publications . The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernmental standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

3. REQUIREMENTS

* 3.1 First article. This specification makes provisions for first article testing. First article testing shall be in accordance with paragraph 4.4. Testing shall be performed at the contractor's plant.

3.2 General requirements. The requirements of drawing 54J6279 apply as requirements of this specification with the exceptions and additions specified herein, When the drawing and this specification conflict, this specification shall govern.

3.3 Commercial parts. Commercial parts having suitable properties may be used where, on the date of invitation for bids, there are no suitable standard parts. In any case, commercial utility parts such as screws, bolts, nuts, and cotterpins, having suitable properties may be used provided:

a. They can be replaced by the standard parts (MS or AN) without alteration.

b. The corresponding standard parts are referenced in the parts list and, if practical, on the contractor's drawings.

3.4 Performance. Unless otherwise specified, the maintenance platform shall be capable of operating satisfactorily immediately following subjection to temperature ranging from -65° to +160° Fahrenheit.

3.4.1 Mobility. The maintenance platform shall be capable of being towed over equal distance of sod, brick pavement, rough concrete, and rough macadam for a distance of 50 miles at an average speed of 15 miles per hour.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.

3.5 Wheel locks. With all wheel locks fully engaged, no damage to the locks or slipping of wheels shall result when the maintenance platform is moved a distance of 5 feet on smooth, dry concrete.

3.6 Hydraulic system. The hydraulic system shall be equipped with a reservoir and filler opening located on the top, A drain plug shall be provided. An air vent shall be incorporated in the filler cap. Means shall be provided in the reservoir tank to prevent oil from splashing out when the maintenance platform is moved. An oil strainer shall be installed in the filler opening. The hydraulic system and reservoir shall be filled with oil conforming to MIL-H-6083 for shipment and storage.

3.6.1 Actuating pump. The actuating pump used in height adjustment of the maintenance platform shall be designed for ease of maintenance, operation, and for resistance to the temperatures specified herein. The force required at the end of the handle of the pump to raise the platform from the low level shall not exceed 15 pounds with 150 pounds on the platform. A maximum of one hundred strokes shall be required to accomplish the first 4 feet of adjustment.

3.6.2 Hydraulic cylinder. Whenever practical, the hydraulic components shall conform to AN standards. A seal shall be installed to prevent the entrance of moisture into the cylinder. All hydraulic fittings and lines (rubber and metal) shall be suitable for operation in temperatures ranging from -65° to +160°F. Low-temperature, synthetic rubber-packing shall be used. The plunger or piston shall be chromium plated.

3.7 Bolts, nuts and pins. All bolts, nuts and pins used in the construction of the maintenance platform shall be cadmium or zinc plated. Unless otherwise specified, self-locking nuts shall be used in the construction of the maintenance platform.

3.8 Identification of product. Equipment, assemblies and parts shall be marked for identification in accordance with MIL-STD-130.

3.9 Workmanship.

3.9.1 General, The maintenance platform, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness and thoroughness of welding and brazing, painting, riveting, and freedom of parts from burrs and sharp edges.

3.9.2 Riveting. Riveting operations shall be carefully performed to insure that the rivets are tight and satisfactorily headed.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:28Z
Check the source to verify that this is the current version before use.

3.9.3 Welding. All welded joints shall be inspected to insure freedom from cracks, oxide inclusions, or injurious porosity.

3.9.4 Cleaning. The maintenance platform shall be thoroughly cleaned of loose, spattered, or excess weld, metal chips, and other foreign material during and after final assembly. Burrs and sharp edges, as well as resin flash that may crumble, shall be removed.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of tests. The inspection and testing of the maintenance platform shall be classified as follows:

a. First article (see 4.4).

b. Acceptance tests (see 4.5).

4.3 Test conditions. The test conditions are described under the tests to which they apply.

4.4 First article testing.

4.4.1 Test sample. The first article test sample shall consist of one model representative of the production equipment. It shall be tested at a laboratory designated by the procuring activity or, when so stated in the contract, at the contractor's plant under the supervision of the procuring activity.

4.4.2 First article tests. The first article tests shall consist of all the tests described under 4.6.

4.5 Acceptance tests. Acceptance test shall consist of:

a. Individual tests.

b. Sampling tests.

4.5.1 Individual tests. Each maintenance platform shall be subjected to the following test as specified under 4.6:

Examination of product (see 4.6.1).

4.5.2 Sampling plan and tests.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:28Z
Check the source to verify that this is the current version before use.

4.5.2.1 Sampling plan. One maintenance platform shall be selected at random from every fifty or fraction thereof produced and subjected to the following tests as specified under 4.6:

a. Static load (see 4.6.2),

b. Ten percent of the endurance test. The hydraulic system shall be filled with hydraulic fluid conforming to MTL-H-5606 for this test (see 4.6.3).

c. Setting (see 4.6.4).

4.5.2.1.1 Rejection and retest. When one or more maintenance platforms selected from a production run fail to meet the specification, maintenance platforms still on hand or later produced shall not be accepted until the extent and cause of failure are determined.

4.5.2.1.2 Individual tests may continue. For operational reasons, individual tests may be continued pending the investigation of a sampling test failure. Final acceptance of maintenance platforms on hand or produced later shall not be made until it is determined that the lot meets all the requirements of the specification.

4.5.2.1.3 Defects in maintenance platforms already accepted. The investigation of a test failure could indicate that defects may exist in maintenance platforms already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.6 Test methods.

4.6.1 Examination of product. The maintenance platform shall be inspected to determine compliance with the requirements specified herein with respect to material, workmanship, dimensions, marking and finish.

4.6.2 Static load. The maintenance platform shall be tested at all heights throughout its range in increments not to exceed 12 inches. At each of these increments, a uniformly distributed load of 1,000 pounds shall be placed on the maintenance platform. No member of the maintenance platform shall be depressed or deflected more than 1 1/2 inches under this load nor shall any permanent defamation or deflection of any member of the maintenance platform be evident after completion of these tests. Safety pins shall not be installed for this test.

4.6.2.1 No point on the expanded metal deck shall be depressed or deflected more than 1/4 inch when subjected to a concentrated vertical load of 300 pounds distributed over an area of 25 square inches.

4.6.2.2 Steps or rungs shall be individually tested by applying a load of 400 pounds at or near the center of the step. No evidence of damage or permanent deformation of the steps shall be apparent at the conclusion of these tests.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:28Z
Check the source to verify that this is the current version before use.

4.6.2.3 Upon completion of the tests specified in 4.6.2, 4.6.2.1. and 4.6.2.2, the maintenance platform shall be visually inspected. There shall be no leakage of hydraulic fluid, elongation of boltholes, or failure of welding, materials, or workmanship.

4,6,3 Endurance. The maintenance platform shall operate satisfactorily after it has been subjected to a hundred cycles of raising a 500-pound load to maximum height and lowering the load to minimum height,

4.6.4 Settling. With the platform raised 20 percent above the minimum height and with a platform load of 1,000 pounds, the rate of settling of the hydraulic ram shall not exceed 0.020 inch per hour. Safety pins shall not be installed for this test.

4.6.5 Temperature tests. The maintenance platform shall be subjected to the following tests conducted in accordance with the specified procedures of MIL-E-5272. Upon completion of each exposure period, the maintenance platform shall be subjected to 10 cycles of operation with a 500-pound load on the platform.

4.6.5.1 Low temperature. The low temperature test shall be in accordance with procedure I. For this test, hydraulic systems shall be filled with a mixture by volume of 60 percent hydraulic fluid conforming to MIL-H-5606 and 40 percent fuel conforming to TT-N-95.

4.6.5.2 High temperature, The high temperature test shall be in accordance with procedure I, except that the temperature shall be reduced to 49° Centigrade for 12 hours prior to operation and test.

4.6.6 Tow test. The maintenance platform shall be towed for a distance of 50 miles at an average speed of 15 mph. The tow tests shall be conducted, as nearly as available conditions will permit, over equal distances of sod, brick pavement, rough concrete, and rough macadam. No appreciable shimmying of casters shall occur during these conditions. No damage or appreciable wear shall occur to the casters, platforms, or any components thereof as a result of this test. All components of platforms and casters, including immobilizing features, shall function properly after the tow test and shall show no evidence of failure.

4.6.6.1 The maintenance platform shall be inspected for misalignment, distortions, or other defects that may have developed or have been aggravated during this test. Following the tow test and without intervening reconditioning, the maintenance platform shall be subjected to the test specified in 4.6.2.

4.6.7 Wheel locks. With all wheel locks fully engaged, the maintenance platform shall be subjected to a drawbar pull sufficient to move the unloaded maintenance platform a distance of 5 feet on smooth, dry concrete. There shall be no indication of retraction, deformation, or damage to the locks or slipping of the wheels.

4.7 Inspection of the preservation, packaging and marking for shipment and storage. Sample items or packs and the inspection of the Preservation. packaging, packing and marking for shipment and storage shall be in accordance with the requirements of section 5, or the documents specified therein.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:28Z
Check the source to verify that this is the currentversion before use.

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A or C or commercial as specified (see 6.2).

5.1.1 Disassembly and matchmarking. Disassembly shall be the minimum necessary to safeguard parts known to be subject to damage, loss or breakage in transit and to accomplish reduction in cube. Bolts, nuts and pins, and other attaching parts removed shall be reinstalled in one of the mating parts and secured to prevent their loss. When necessary to facilitate reassembly, parts removed and mating parts shall be matchmarked. Matchmaking shall be printed on shipping tags conforming to UU-T-81, type A. The printed tags shall be waterproofed in accordance with MIL-STD-129.

5.1.2 Level A. The maintenance platform shall be preserved in accordance with MIL-P-116, method 1. All bare unpainted metal surfaces subject to rust or corrosion shall be coated with type P1 preservative in accordance with MIL-P-116. The hydraulic system shall be preserved in accordance with MIL-STD-162. All openings shall be capped or plugged with MIL-C-5501 closures.

5.1.3 Level C. The level C preservation for maintenance platforms shall conform to the MIL-STD-794 requirements for this level.

5.1.4 Commercial. The maintenance platform shall be preserved in accordance with ASTM-D-3951.

5.2 Packing. Packing shall be level A, B, C or Commercial, as specified (see 6.2).

5.2.1 Level A. The maintenance platform preserved and packaged as specified in 5.1 shall be packed in a container conforming to PPP-B-601, style A, type II, class 2. Containers shall be provided with three 4 by 4 skids and shall extend the full exterior width of the box and shall meet the requirements of PPP-B-601. All loose parts shall be packed in a domestic type container conforming to PPP-B-636 and secured within the PPP-B-601 container. Containers shall be closed and strapped in accordance with the appendix of the applicable specification.

5.2.2 Level B. Same requirements as for level A, except the container shall be type III, class 1.

5.2.3 Level C. The level C packing for maintenance platforms shall conform to the MIL-STD-794 requirements for this level.

5.2.4 Commercial. Maintenance platforms preserved as specified in 5.1 shall be packed in accordance with ASTM-D-3951.

5.3 Physical protection. All cushioning, blocking, bracing and bolting shall be in accordance with MIL-STD-1186.

5.4 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129, or ASTM-D-3951 as applicable.

Source: https://assist.dla.mil -- Downloaded: 20260-17T08:28Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Intended use. The type B-5A maintenance platform is intended for use in facilitating maintenance on all aircraft within its height range.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Required levels of preservation, packaging and packing.

c. Point of inspection for first article tests.

6.2.1 Commercial products proposed as equal to and interchangeable with those specified will be subject to approval by the procuring activity.

* 6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made, This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue .

Custodian:
Air Force - 99

Preparing activity:
Air Force - 82

(Project 1730-F287)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 73236 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

SA-ALC/MMEDO
Kelly AFB, TX 78241-5990

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2 DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording.

b Recommended Wording

c Reason/Rationale for Recommendation

6. REMARKS

7a NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:28Z
Check the source to verify that this is the current version before use.