INCH-POUND


MIL-DTL-28748/14A
w/Amendment 1
5 August 2021
SUPERSEDING
MIL-DTL-28748/14A
27 February 2019

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, RACK AND PANEL, CRIMP TYPE REMOVABLE SOCKET CONTACTS, SIZE 22

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-DTL-28748.




Configuration A. Connector.

FIGURE 1. Connector with guide pins, jackscrews, and shields.


AMSC N/A
FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.




Configuration B. Connector with guide pins.




Configuration C. Connector with fixed jackscrews.

FIGURE 1. Connector with guide pins, jackscrews, and shields – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.



Configuration D. Connector with short turnable jackscrews.



Configuration E. Connector with long turnable jackscrews and shield.

FIGURE 1. Connector with guide pins, jackscrews, and shields – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.


Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	.13	.086	2.18	.187	4.75	.600	15.24
.007	.18	.090	2.29	.195	4.95	.620	15.75
.015	.38	.093	2.36	.200	5.08	.625	15.88
.020	.51	.110	2.79	.210	5.33	.700	17.78
.046	1.17	.125	3.18	.255	6.48	.920	23.37
.055	1.40	.132	3.35	.500	12.70	.960	24.38
.078	1.98	.150	3.81	.585	14.86		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± .003 (0.08 mm).
4. .730 (18.54 mm) maximum for 14 contact connector with side opening shield.
   .630 (16.00 mm) maximum for 50 contact connector.
5. 1.20 (30.48 mm) maximum for 44 contact arrangements.
   1.52 (38.61 mm) maximum for 50 contact arrangements.
6.


Number of contacts	Minimum cable openings
4	.07 (1.8 mm) sq. inch
7	.07 (1.8 mm) sq. inch
14	.19 (4.8 mm) sq. inch
20	.22 (5.6 mm) sq. inch
26	.26 (6.6 mm) sq. inch
34	.34 (8.6 mm) sq. inch
44	.34 (8.6 mm) sq. inch
50	.34 (8.6 mm) sq. inch

FIGURE 1. Connector with guide pins, jackscrews, and shields – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.




Configuration A. Insert with four contacts.




Configuration B. Insert with seven contacts.

FIGURE 2. Insert arrangements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.




Configuration C. Insert with 14 contacts.




Configuration D. Insert with 20 contacts.

FIGURE 2. Insert arrangements – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.




Configuration E. Insert with 26 contacts.




Configuration F. Insert with 34 contacts.

FIGURE 2. Insert arrangements – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.



Configuration G. Insert with 44 contacts.



Configuration H. Insert with 50 contacts.

FIGURE 2. Insert arrangements – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.


Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.003	.08	.090	2.29	.23	5.8	.625	15.88	1.100	27.94
.004	.10	.091	2.31	.270	6.86	.695	17.65	1.128	28.65
.005	.13	.105	2.67	.28	7.1	.752	19.10	1.230	31.24
.008	.20	.109	2.77	.282	7.16	.78	19.8	1.25	31.8
.010	.25	.125	3.18	.376	9.55	.814	20.68	1.281	32.54
.031	.79	.130	3.30	.382	9.70	.862	21.89	1.408	35.76
.0405	1.029	.140	3.56	.39	9.9	.88	22.4	1.50	38.1
.045	1.14	.146	3.71	.50	12.7	.987	25.07	1.62	41.1
.047	1.19	.171	4.34	.505	12.83	1.000	25.40		
.062	1.57	.195	4.95	.562	14.27	1.032	26.21		
.081	2.06	.21	5.3	.564	14.33	1.06	26.9		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Unless otherwise specified, tolerances are ± .02 (.51 mm) for two place decimals and ± .015 (.38 mm) for three place decimals.
4. Tolerance between any two adjacent contact centers shall be ± .004 (.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ± .006 (.15 mm).
5. Contact letter identification may be located on either side of the contact hole. All letters shall appear on the front and rear face of each insert.
6. Inserts shall be used with guide pin assemblies or jackscrew assemblies.
7. Insert material: Shall be in accordance with MIL-DTL-28748.
8. Installing and removal tools: M81969/18-02 and /20-02 per SAE AS81969/18 and /20.
9. Crimp tool: M25520/2-01. Positioner: Astro 640092, Daniels K280, or equivalent.
10. Shape of .008 pads optional.
11. Mating face of socket insert shown; pin insert is reverse image.
12. Contacts: SAE-AS39029/35.

FIGURE 2. Insert arrangements – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.



Inches	mm
.059	1.50
.062	1.57
.073	1.85
.075	1.91
.077	1.96
.080	2.03
.305	7.75
.315	8.00
.490	12.45

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.

FIGURE 3. Insert hole configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1, 2 and 3.

Mating connectors: See MIL-DTL-28748/7 and MIL-DTL-28748/13.

Resistance to text probe damage .145 ± .015 depth of insertion.

Part number: As shown in the following example:

EXAMPLE OF PART NUMBER:

(See part number code)

M28748/14	A	0	0	F	1A
Basic number of specification sheet	Insert arrangement (Fig. 2)	Shield and shield clamp location or retaining plate (Fig. 1)	Shell type	Jackscrews or guide pins (Fig.1)	Contacts

PART NUMBER CODE

Insert arrangement figure 2 configuration	Number of contacts	Shield and shield clamp location or retaining plate	Shell type
		Shield	
A-	4	1 – Top opening per	0 – None included
B-	7	configuration E	
C-	14	of figure 1	
D-	20	2 – Side opening per	
E-	26	configuration E	
F-	34	of figure 1	
G-	44	0 – None included	
H-	50		

Jackscrews
or
guide pins

L – Long jackscrews: Configuration E, figure 1
F – Fixed jackscrews: Configuration C, figure 1
S – Short jackscrews: Configuration D, figure 1
G – Guide pins: Configuration B, figure 1

Jack and guide location: The jackscrew (turning or fixed) or guidepin shall be located by the “A” socket contact.

Contacts: M39029/35-441
1A – 100 percent size 22

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Reference documents. In addition to MIL-DTL-28748, this document references the following:

MIL-DTL-28748/7
MIL-DTL-28748/13
SAE-AS39029/35
SAE-AS81969/18
SAE-AS81969/20

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, SH

(Project 5935-2021-083)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:18Z
Check the source to verify that this is the current version before use.