INCH-POUND


MIL-DTL-28748/21
11 March 2005

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, RACK AND PANEL, PRINTED WIRING BOARD (PWB) MOUNT, RIGHT ANGLE, SOCKET CONTACTS, SIZE 22

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28748.




Connector with mounting bracket and jackscrews or guidepins

FIGURE 1. Connector.

AMSC/NA

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.




CONNECTOR WITH GUIDEPINS

CONFIGURATION A

FIGURE 1. Connector with jackscrews and guidepins - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.




CONNECTOR WITH JACKSCREWS

CONFIGURATION B

FIGURE 1. Connector with jackscrews and guidepins - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



DETAIL A

FIGURE 1. Connector with jackscrews and guidepins - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.003	0.08	.086	2.18
.004	0.10	.090	2.29
.005	0.13	.110	2.79
.008	0.20	.125	3.18
.010	0.25	.150	3.81
.015	0.38	.244	6.20
.020	0.51	.585	14.86
.078	1.98	.625	15.88

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general only.
3. Unless otherwise specified tolerances is ± .020 inch (0.50 mm).
4. Materials for guidepins and jackscrews: Corrosion resistant steel in accordance with ASTM A276 class 304, 316, or ASTM A582, class 302, 303, 303Se.
5. Washer .020 inch (0.51 mm) may be either aluminum or corrosion resistant steel.
6. Finish for washers shall be either passivated or anodized.
7. Locknut: Mounting hardware shall include stainless steel locknuts. The nuts may be all metal or designed with nylon inserts.
8. Washer .020 inch (0.51 mm) thick supplied with all sizes.

FIGURE 1. Connector with jackscrews and guidepins - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



MOUNTING BRACKET


Inches	mm
.031	0.79
.086	2.18
.088	2.24
.175	4.45
.185	4.70
.296	7.52

Dash number	Dimension A	Dimension B (Max)	Insert size
1 (see note 5)	.105 ±.007 (2.67)	.210 (5.33)	4 and 7
2	.140 (3.56)	.255 (6.48)	14, 20, and 26
3	.195 (4.95)	.295 (7.49)	34, 44, and 50


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for l information only.
3. Unless otherwise specified tolerance is ± .005 inch (0.13 mm).
4. Material: Aluminum alloy in accordance with SAE-AMS-QQ-A-250/8.
5. Dash 1 only material thickness dimension may be .024 inch (0.61 mm) minimum.
6. Bracket design optional, design shall fall within drawing parameters.

FIGURE 2. Mounting bracket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (4 CONTACTS)




RECOMMENDED MOUNTING PATTERN (4 CONTACTS)


CONFIGURATION A

FIGURE 3. Insert arrangements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (7 CONTACTS)




RECOMMENDED MOUNTING PATTERN (7 CONTACTS)


CONFIGURATION B

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (14 CONTACTS)




RECOMMENDED MOUNTING PATTERN (14 CONTACTS)


CONFIGURATION C

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (20 CONTACTS)




RECOMMENDED MOUNTING PATTERN (20 CONTACTS)


CONFIGURATION D

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (26 CONTACTS)




RECOMMENDED MOUNTING PATTERN (26 CONTACTS)


CONFIGURATION E

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (34 CONTACTS)




RECOMMENDED MOUNTING PATTERN (34 CONTACTS)


CONFIGURATION F

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (44 CONTACTS)




RECOMMENDED MOUNTING PATTERN (44 CONTACTS)


CONFIGURATION G

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



INSERT ARRANGEMENT (50 CONTACTS)




RECOMMENDED MOUNTING PATTERN (50 CONTACTS)


CONFIGURATION H

FIGURE 3. Insert arrangements - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.



END VIEW TYPICAL OF INSERT SIZES 4 AND 7



END VIEW TYPICAL OF INSERT SIZES 14, 20 AND 26



END VIEW TYPICAL OF INSERT SIZES 34, 44 AND 50

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.002	0.05	.270	6.8
.005	0.13	.28	7.1
.010	0.25	.281	7.13
.02	0.5	.282	7.16
.020	0.51	.312	7.92
.024	0.61	.370	9.40
.028	0.71	.376	9.55
.040	1.01	.39	9.91
.0405	1.029	.407	10.33
.045	1.14	.500	12.70
.047	1.19	.516	13.11
.070	1.78	.520	13.21
.071	1.80	.562	14.27
.081	2.06	.564	14.33
.090	2.29	.625	15.87
.094	2.39	.640	16.26
.105	2.67	.704	17.88
.109	2.76	.752	19.10
.125	3.18	.78	19.8
.135	3.43	.814	20.68
.14	3.5	.88	22.4
.140	3.56	.987	25.06
.141	3.58	1.000	25.40
.146	3.71	1.032	26.21
.147	3.73	1.06	26.9
.15	3.81	1.25	31.8
.175	4.44	1.128	28.65
.195	4.95	1.281	32.54
.21	5.3	1.408	35.76
.220	5.59	1.50	38.1
		1.62	41.15

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerance is ±.015 inch (0.38 mm).
4. Tolerance between any two adjacent contact centers shall be ±.004 inch (0.10 mm). Tolerance between any two contact centers, other than adjacent centers, shall be ±.006 inch (0.15 mm).
5. Solder tail nonfunctional areas need not be plated, provided they do not cause degradation in performance.
6. Contact identification may be located on either side of the contact hole but shall appear on the front and rear of each insert.
7. Hardware hole configuration optional, design shall incorporate an anti-rotation feature on either front or rear face of insulator.
8. Manufacturer may include an optional .035 ±.010 inch (0.89 ±0.25 mm) plastic alignment bar of nylon or polyphenylene sulfide in order to ensure the proper alignment or terminals.

FIGURE 3. Insert arrangements - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figures 1, 2, and 3.

Mating connector: See MIL-DTL-28748/7.

Contacts: Contacts shall be in accordance with MIL-DTL-28748.


Solder tail: "B" length (see permissible PINS).

Solder tail finish:

a. Tin/lead in accordance with SAE-AMS-P-81728, 50 to 97 percent tin, 100 micro inches (2.54µm) minimum or hot solder dip in accordance with J-STD-006, 63 percent tin, 100 micro inches (2.54µm) minimum over 50 to 100 microinches (1.27 to 2.54µm) of nickel in accordance with SAE-AMS-QQ-N-290, class 1.
b. Gold in accordance with ASTM B488 type II, code C, class 0.76 (30 microinches) min of gold over 50 to 100 microinches (1.27 to 2.54µm) of nickel in accordance with SAE-AMS-QQ-N-290, class 1.

Contact sealants: Sealants used to back seal contact cavities to prevent entry of cleaning solutions, conformal coatings, etc.

Part or Identifying Number (PIN): As shown in the following example: The number zero (0) is used to indicate which parts are not included (see table I permissible PINS).



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.

Insert designator		Number of contact positions
A	-	4
B	-	7
C	-	14
D	-	20
E	-	26
F	-	34
G	-	44
H	-	50

Mounting bracket (see figure 2):

Mounting bracket Designator		Insert size
1	-	4 and 7
2	-	14, 20, and 26
3	-	34, 44, and 50
-0	-	None

Jackscrews or guidepins

F - fixed jackscrews, configuration B, figure 1.
G - guidepins, configuration A figure 1.
0 - none included.

Jack and guide location: The jackscrew male (turning or fixed) or guide pin shall be located by the A socket contact.

Seal: Manufacturer may supply sealed terminals when no seal is specified.

S - sealed
0 – No seal

Termination tail "B" length (see figure 3):

1A - Right angle - solder tails .093 inch (2.76 mm).
1B - Right angle - solder tails .125 inch (3.18 mm).
1C - Right angle - solder tails .156 inch (3.96 mm).

Tail plating:

T - Tin/lead
G - Gold

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.

Permissible PINs are specified in table I.

TABLE I. Permissible PINs. 1/ 2/

M prefix and specification number	Insert designator	Mounting bracket designator	Jackscrews or guide pins	Sealed Terminals 2/	Solder tail plating	Solder tail length
M28748/21	A	1 or 0	F - fixed G - Guide pin 0 - none	S - sealed 0 - no seal	T - tin/lead G - gold	1A 1B 1C
	B	1 or 0				
	C	2 or 0				
	D	2 or 0				
	E	2 or 0				
	F	3 or 0				
	G	3 or 0				
	H	3 or 0				

1/ The number zero (0) is used to indicate which parts are not included.
2/ To order mounting brackets see MIL-DTL-28748/20.

Referenced documents: In addition to MIL-DTL-28748, this document references the following:

MIL-DTL-28748/7
MIL-DTL-28748/20
ASTM A582
ASTM A276
ASTM B488
J-STD-006
SAE-AMS-P-81728
SAE-AMS-QQ-A-250/8
SAE-AMS-QQ-N-290

CONCLUDING MATERIAL

Custodians:
Army- CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4674-000)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:22Z
Check the source to verify that this is the current version before use.