[METRIC]
A-A-52152A
June 28, 1996
SUPERSEDING
A-A-52152
28 March 1990
MIL-I-13042A(AT)
15 March 1968

COMMERCIAL ITEM DESCRIPTION

INSULATION SLEEVING, THERMAL, TUBULAR (METRIC)

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE. This CID covers requirements for tubular, thermal, insulation sleeving, hereinafter called "insulation sleeving". The insulation sleeving is intended for covering heater exhaust ducts, heater ducts or tubes and pipes carrying fluids at elevated temperatures.

2. CLASSIFICATION. Insulation temperature range shall be as follows (see 7.2):

Range 1 - Up to 538 degrees Celsius (°C) (1000 degrees Fahrenheit (°F))
Range 2 - Up to 399 °C (750 °F)
Range 3 - Up to 177 °C (350 °F)

3. SALIENT CHARACTERISTICS.

3.1 Materials. The material shall conform to ASTM C 1086, specifying 100 percent (%) glass fiber, and ASTM D 581, specifying glass fiber with organic content to be at least 1 % and no greater than 4 %. Insulation hygroscopic moisture content shall not exceed 1 %. The use of recovered material made in compliance with regulatory requirements is acceptable providing that all requirements of this CID are met (see 4.1).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000.

AMSC N/A FSC 5640

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3.2 Design and construction. The insulation sleeving shall be designed and constructed in accordance with manufacturer's specifications. Size shall be as specified in the contract or order (see 7.2).

4. REGULATORY REQUIREMENTS.

4.1 Recovered material. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Responsibility for inspection. The contractor is responsible for the performance of all inspections (examinations and tests).

5.2 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this CID and that the product conforms to the producer's own drawings, specifications, workmanship standards, and quality assurance practices. Items with known defects shall not be submitted for Government acceptance. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order (see 7.2).

7. NOTES.

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents.

7.1.1 Government publications. The Code of Federal Regulations (CFR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

7.1.2 Non-Government publications. Copies of ASTM C 1086 "Standard Specification for Glass Fiber Felt Thermal Insulation" and ASTM D 581 "Standard Specification for Glass Fiber Greige Braided Tubular Sleeving" are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

7.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this CID.
b. Issue of the DoDISS to be cited in the solicitation, and if required, the specified issue of individual documents referenced.
c. Temperature range and size required.
d. Packaging requirements.

7.3 Cross-reference data. Insulation sleeving conforming to this CID are interchangeable/substitutable with insulation sleeving conforming to A-A-52152 and MIL-I-13042A(AT).

MILITARY INTERESTS:

Custodian:
Army - AT

Review Activity:
Army - SM

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

Preparing Activity:
Army - AT

(Project 5640-0587)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.