A-A-52156
23 March 1990

COMMERCIAL ITEMS DESCRIPTION
FILTER ELEMENT, INTAKE AIR CLEANER
DRY TYPE

This Commercial Item Description replaces the Military Specification MIL-F-46736(AT)

SCOPE. This Commercial Item Description covers air cleaner elements of the dry type for single stage air cleaners from 40 cubic feet per minute (cfm) to 1,000 (CFM) rated air flow.

SALIENT CHARACTERISTICS.

All testing to verify performance should be in accordance with SAE J726.

Flame Resistance. The air cleaner element shall not continue to burn or smolder when flame is removed.

Efficiency. The air cleaner element shall have an efficiency of not less than 99.5 percent as rated therein.

Dust Capacity. Coarse dust capacity of the element shall permit operation for a period of four hours without exceeding a restriction equal to 20 inches of water.

Restriction After Cleaning. After the element has been subjected to the dust capacity test and after subsequent cleaning, the increase in air flow restriction shall not exceed the equivalent of 1 inch of water, compared to the initial value obtained at rated air flow.

Beneficial comments, recommendations, additionals, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, U.S. Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, Michigan 48397-5000

FSC 2940

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

STRUCTURAL DESIGN AND PHYSICAL PROPERTIES.

Crush Resistance. Unless otherwise specified, the element shall withstand, without damage, a compressive stress (end-to-end) consisting of a static load of 150 pounds. Deflection under the specified load shall be not less than 0.040, nor more than 0.060 inch.

Vibration Resistance. Filter element shall show no structural or assembly damage.

Efficiency After Vibration. Filter element shall have an efficiency of not less than 99.5 percent.

Ozone Resistance. The element end cap seals shall be ozone resistant and shall evidence no cracks when tested.

PACKAGING.

Preservation, Packaging, Packing and Marking. Preservation, packaging, packing and marking for the desired protection shall be in accordance with the applicable packaging standard or packaging data sheet specified by the procuring activity.

Intended Use. Elements covered by this CID are intended for use in intake air cleaners used with internal combustion engines for automotive, tank, and industrial applications.

MILITARY INTERESTS:

CUSTODIAN:
Army - AT

PREPARING ACTIVITY
Army - AT

PROJECT NO. 2940-0134

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.