METRIC
DoD-C-70513 (AR)
AMENDMENT 1
21 NOVEMBER 1986

MILITARY SPECIFICATION SHEET

(U) CARTRIDGE, 120MM, KE SLUG

(U) This Amendment forms a part of Military Specification DoD-C-70513 (AR), dated 23 August 1985, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

(U) The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
2	2
4	4
30	30

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1315-A883)

FSC-1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

	DOD-C-63485	Case Base and Seal Assembly
*	DOD-P-70639	Propellant, JA-2, For Use in Cartridge, 120mm, KE Cannon Proof Slug
	DOD-P-64009	Projectile, 120mm TPCSDS-T, M865 Metal Parts for

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment
MIL-STD-1167	Ammunition Data Card
MIL-STD-1235	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings, and publications. - The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

* U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12524865	Cartridge, Slug 120mm, Cannon Proof
12525027	Cartridge, 120mm, Slug, Case Base Test

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

CODE OF FEDERAL REGULATIONS

Title 49	Transportation, Parts 100-199, Paragraph 173.54

ARMY REGULATIONS

AR 700-15	Packing of material

Supersedes page 2 dated 23 August 1985.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

3.4 Performance. - The cartridge shall comply with the following requirements.

3.4.1 Chamber pressure.

* 3.4.1.1 Cannon proof cartridge. - The chamber pressure, for the Cannon Proof Slug, P/N 12524865, as delivered shall be within the range of 6700 to 7070 bars when fired at +63°C as measured 8.89 +1.3 cm forward of the breech.

* 3.4.1.2 Case base test cartridge. - The chamber pressure for the Case Base Test Slug, P/N 12525027, shall be as defined in Dod-C-63485.

* 3.4.1.3 Primer test cartridge. - The chamber pressure for the primer test slug shall be defined in DoD-P-70451.

3.4.4 Misfire. - The cartridge shall not fail to fire from the weapon.

3.4.5 Metal parts security. - There shall be no indication of parts failure in the gun bore.

3.5 Adhesive bond. - The test sample cartridge case/cap case shall separate at other than the glue joint interface under a minimum tensile load as defined on the cartridge drawing.

3.6 Primer electrical resistance. - The primer electrical resistance shall not exceed the following:

* Primer electrode to primer body	1.8 ohms maximum, 0.8 ohms min.
Primer body to case base	0.1 ohms maximum

3.7 Primer deterioration. - See Paragraph 6.6.

3.8 Workmanship. - The cartridge and all components shall comply with the provision of MIL-A-2550. The cleaning method shall not be injurious to any of the parts; nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detailed specification.

4.2 Classification of inspections. - The inspection requirements specified herein are classified as follows:

a) Quality conformance inspection

4.3 Quality conformance inspection.

Supersedes page 4 dated 23 August 1985.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.

Government expense without cost to the contractor who loaded the assemblies or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

* 6.7 Propellant weight determination. - The required weight of propellant for the cannon proof slug, the cannon proof slug for the primer test, and the case base test slug shall be established per the procedures as described in DoD-P-70639.

* 6.7.1 Deleted.

* 6.7.2 Deleted.

6.8 Definitions of packaging levels

6.8.1 Level A. - Full military protection for unrestricted (OCONUS) shipment and storage.

6.8.2 Level B. - Limited military protection for limited (OCONUS) shipment and storage.

6.8.3 Level C. - For interplant (CONUS) shipment and very limited storage.

6.8.4 For more detailed interpretation of the various military packaging levels, see AR-700-15.

* 6.9 Keywords. -
Ammunition
Cartridge
Cannon
Slug
Tank

Supersedes page 30 dated 23 August 1985.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:36Z
Check the source to verify that this is the current version before use.