MILITARY SPECIFICATION

BOMB, SMOKE, BLU-17/B

This amendment forms a part of Military Specification MIL-B-60304(MU), 16 May 1967.

Page 2

2.1: Delete the following:

"PUBLICATIONS

EDGEWOOD ARSENAL INSPECTION STANDARD

R8-1 - Grenade, Hand and Rifle, Smoke, WP, M34."

3.2: Delete last sentence and substitute the following:

"When examined in accordance with 4.2.4.1, a 3 to 5 percent void, of total volume shall exist above the surface of the water over the WP in the filled and closed bomb. The bomb shall be in the base-down position and the WP at a temperature of 130° ± 10°F. The depth of water remaining on the surface of the WP shall not exceed 1/8 inch."

Page 3

4.2.2.2: Delete last sentence in its entirety.

Page 4

4.2.3.4(a): Add the following under "Minor":

"203 Rust inhibitor missing."

Page 5

4.2.4.1: Delete and substitute the following:

"4.2.4.1 Filling. With the WP in a molten condition, the filling height and depth of water remaining on the surface of the WP in the filled bomb shall be radiographed with the bomb in the base-down position."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.

6.3: Delete in its entirety and substitute the following:

"6.3 Refuzing. If failure of the bomb is caused by the fuze, refuzing is permitted. The delay time for the fuze shall be between 4.0 and 5.0 seconds."

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 1325-A305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.