MILITARY SPECIFICATION

CHARGER, BATTERY: 10541243

This amendment forms a part of Military Specification MIL-C-60299A(MU), dated 18 June 1970.

Paragraph 1.1: Delete and substitute:

"1.1 This specification covers an electronic battery charger which is operated from a direct current source. The charger is a system component for the Range Finder, LASER, AN/GVS-3 (see 6.1)."

Paragraphs 3.5.1 and 3.5.1a: Delete and substitute:

"3.5.1 Charger and Power Supply.- With 18 to 32 VDC applied to J4 the Battery Charger assembly shall:

a. Indicate by "POWER ON" lamp when the power switch is set to the "ON" position."

Paragraph 4.6.2: Delete and substitute:

"4.6.2 Performance.- Conduct the tests of 4.6.2.1 through 4.6.2.4 with the environmental conditions specified in 3.5 with the input voltages specified in 3.5.1 applied to J4 (Pin A (+) and Pin B (-)."

Paragraph 4.6.2.1: Delete and substitute:

"4.6.2.1 Power On Indicator.- Set the power switch to the "ON" position. The indicator lamp located behind the switch shall light. Set the switch to the off position. The lamp shall not be lighted."

Paragraph 4.6.2.2, second sentence: Delete "DC" and substitute "ON"; delete last sentence.

Paragraph 4.6.2.3, third sentence: Delete and substitute "Set the Power switch to the ON position"; delete last sentence.

Paragraph 4.6.2.4, fourth sentence: Delete and substitute "Set the power switch to the ON position."

Paragraph 4.6.5: Delete subparagraphs "b" and "c" and substitute:

"b. Ranging Mode: Supply power to range finder for ranging operations (a dummy load simulating a rangefinder may be substituted, and operated continuously) for 10 hours.

"c. Combined charging and ranging mode 30 hours."

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1240-A290

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.