INCH-POUND

MIL-T-52953/6A
27 October 1989
SUPERSEDING
MIL-T-52953/6
8 December 1986

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, PNEUMATIC, 4000-POUND CAPACITY, 144-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-52953.

REQUIREMENTS

1. Capacity: 4000 pounds at 24 inches load center.
2. Tire Type: Pneumatic.
3. Collapsed mast height: 83 inches maximum.
4. Maximum fork height: 144 inches minimum.
5. Free lift height: 56 inches minimum.
6. Fork mounting: MS16955.
7. Fork size: 1-13/16 inch thick (maximum).
   5-1/16 inch wide (maximum).
   42 inch long to +0 inch -0.5 inch.
   32 inch spread (minimum).
8. Overhead guard height: 83 inches maximum.
9. Right-angle turn dimensions: 138 inches maximum (Add 4 inches when side shifter attachment is used).
10. Travel speed: 5 mph minimum.
11. Upright tilt: Tilt shall be 5 degrees forward, 10 degrees rearward ±0.5 degree.
12. Underclearance: 4 inch minimum.
13. Overall truck width: 42.5 inches maximum.
14. Battery: 925 AH @ 6 hr. rate (minimum).
15. Lifting Speed (loaded): 43 feet per minute (minimum).

Custodian:
Army - ME
Navy - SA
Air Force - 99

Preparing activity:
Army - ME

Project 3930-0636-6

Review activities:
Army - AT, SM, MT
Navy - MC
DLA - CS
Air Force - 84

FSC 3930

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.