MIL-T-60637(MU)
AMENDMENT 2
10 June 1968

SUPERSEDING
AMENDMENT 1
9 May 1967

MILITARY SPECIFICATION
THRUSTER, CARTRIDGE ACTUATED, M6, ASSEMBLY

This amendment forms a part of Military Specification MIL-T-60637(MU) dated 24 March 1967.

Paragraph 3.4.6, delete and substitute:

"3.4.6 Functioning time.- The time elapsed between the energizing of the thruster to end of stroke, shall not exceed 50 milliseconds."

* Paragraph 4.2.3.3.1, line 1: delete "Thirty two units" and substitute "Twenty one units".

* Table III: delete and substitute:

TABLE III

Sample Size	Method	Temperature
6	Load (See 3.4.4.1)	-65° to -70°F
6	Load (See 3.4.4.1)	+65° to +75°F
6	Load (See 3.4.4.1)	+160° to +165°F
1	No Load (See 3.4.3)	-65° to -70°F
1	No Load (See 3.4.3)	+65° to +75°F
1	No Load (See 3.4.3)	+160° to +165°F

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A285

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:51Z
Check the source to verify that this is the current version before use.