NOT MEASUREMENT SENSITIVE

MIL-T-62087E
5 March 1990
SUPERSEDING
MIL-T-62087D
28 September 1984

MILITARY SPECIFICATION

TRUCK: COMPACT FORWARD CONTROL VAN, RECRUITER 5,400 POUNDS GVW, 4x2, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a forward control, gasoline engine driven, four-wheel, two-rear wheel drive, commercial integral cab-van-body compact type truck (recruiter) having a minimum gross vehicle weight (GVW) of 5,400 pounds. The vehicle is equipped with an elevating or stationary raised roof section. Vehicles procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Starting.

MILITARY

MIL-B-46176 - Brake Fluid, Silicone.

STANDARDS

FED-STD-297 - Rustproofing, Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.

* (Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE

Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DRAWINGS

MILITARY

7722352 - Receptacle Assy, Size 22, Wall type.

DEPARTMENT OF TRANSPORTATION (DOT)

Federal Motor Carrier Safety Regulations.

Federal Motor Vehicle Safety Standards.

(Application for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington. D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of the ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann. 1060 Brussels, Belgium.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)
No. 70 - National Electrical Code.

(Application for copies of NFPA publications should be addressed to National Fire Protection Association International, Batterymarch Park, Quincy, MA 02269).

SAE, INC.
SAE Standards and Recommended Practices.

J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

STATE OF CALIFORNIA
Vehicle Code of California

(Application for copies of State of California publications should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95809.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

(Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.4, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items, which meet or exceed the requirements of this specification. Except as specified in 3.1.1 through 3.1.1.4, no removal, substitution or alteration of the chassis manufacturer's standard or optional chassis model components shall be made. All chassis items shall be as represented in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2).

3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.1.1.3 Silicone brake fluid. When specified (see 6.2), and if available as the manufacturer's standard or optional brake fluid, brake fluid conforming to MIL-B-46176 shall be provided in the brake system. A tag shall be placed near the master cylinder stating "CAUTION: USE SILICONE BRAKE FLUID ONLY, MIL-B-46176."

* 3.1.1.4 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

3.2.2 Curb weight. The curb weight shall include the weight of the chassis with all attachments, accessories, and equipment; body; and full complement of fuel, lubricants, and coolant.

3.2.3 Gross vehicle weight. The GVW shall consist of curb weight, operator (weight computed at 175 pounds), and a payload, distributed evenly over the vehicle load area, to provide not less than the specified GVW. Minimum payload shall be 700 pounds.

* 3.2.4 Air pollution control. The vehicle shall comply with EPA regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacturing.

3.2.5 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall not exceed the noise limits established by the California Vehicle Code, Section 27200.

3.2.6 Ratings. Vehicle and component ratings shall be the manufacturer's published ratings. Vehicle and component ratings shall not not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.2.7 Wheelbase. The wheelbase shall be not less than 105 inches.

* 3.2.8 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.9 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

3.3 Performance.

* 3.3.1 Speeds and gradeability. The vehicle shall maintain a high speed of not less than 58 miles per hour (mph) on smooth, approximately level, hard surface roads. The vehicle shall be capable of ascending grades of at least 20 percent in low-speed range. Speed and gradeability requirements shall be met with vehicle loaded to specified GVW.

* 3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its specified GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded the specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

* 3.4.1 Engine. The engine shall be a liquid cooled, internal combustion, four-stroke cycle, gasoline type, with not less than six cylinders. The engine shall develop not less than 100 net brake horsepower at manufacturer's recommended governed speed and shall have a net torque rating of not less than 170 pound-feet. Engine net torque and net horsepower ratings shal1 be in accordance with SAE J1349. The engine shall develop the specified torque and horsepower when operated on unleaded fuel with a research octane rating of 91 or motor method rating of 83. The engine shall be capable of warranted operation on unleaded fuel when used in accordance with the operator's manual. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

* 3.4.1.1 Cooling system. The cooling system shall maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient temperature of not less than 125 degrees Fahrenheit (°F). A coolant level indicator consisting of an unbreakable translucent reservoir shall be provided in a position readily visible for checking the coolant level. The translucent reservoir shall be part of the coolant recovery system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

* 3.4.1.2 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling. The fan clutch shall be asbestos free.

3.4.1.3 Power plant heaters. When specified (see 6.2), a coolant heater and an engine oil heater shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. The heaters shall operate on 120 volts alternating current (ac) and shall be wired through a junction block, including a fuse or circuit breaker, to a single three-pronged (male), weatherproof, slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard, three-pronged (two power plus one ground) male connector at the opposite end. All electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation, and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) A coolant heater, 1000-watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. An engine thermostat with an operating range of 170°F to 195°F shall be installed.
(b) An immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening.
(c) The battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.

3.4.2 Electrical system.

3.4.2.1 Alternator. An alternator of not less than 50 amperes rated capacity and which provides not less than 16 amperes dc at normal engine idle speed shall be furnished.

3.4.2.2 Battery. The battery reserve capacity rating, measured in accordance with SAE J537, shall be not less than 100 minutes. The cold cranking rating at 0°F, measured in accordance with SAE J537, shall be not less than 450 amperes. The battery shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

* 3.4.2.3 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83 as specified for buses.

3.4.4 Transmission.

* 3.4.4.1 Automatic transmission. Unless otherwise specified (see 3.4.4.2), an automatic transmission shall be furnished.

3.4.4.2 Manual transmission. When specified (see 6.2), a manually shifted transmission shall be provided. The transmission shall have not less than three forward speeds and one reverse speed. The transmission shall provide for maximum ease of shifting with synchronized shift in all gear ranges.

* 3.4.4.3 Clutch. The clutch shall be the largest capacity clutch offered for the type vehicle and engine furnished with torque capacity exceeding maximum delivered engine torque. The clutch lining shall be asbestos free.

3.4.5 Suspension. The vehicle shall be equipped with a suspension system having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to specified GVW. When the suspension is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with a hydraulic double-acting shock absorber at each wheel.

3.4.6 Axles. Axle ratings shall be at least equal to the load imposed on each axle measured at the ground, with vehicle loaded to specified GVW. A single reduction rear axle shall be furnished.

3.4.6.1 Positive-traction differential. When specified (see 6.2), a rear axle with a positive-traction, limited-slip, or automatic locking differential shall be furnished.

* 3.4.7 Tires. Steel belted radial or, when specified (see 6.2), bias ply tires shall be furnished. Tires shall be tubeless type with highway tread. Tires shall have a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to specified GVW. Tires and tire size designation systems shall conform to the Tire and Rim Association or to the European Tyre and Rim Technical Organisation recommendations.

* 3.4.7.1 Carrier for spare tire assembly. A carrier for a spare tire assembly shall be installed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

* 3.4.7.2 Spare tire assembly. A spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on a spare wheel or rim.

* 3.4.8 Brakes. Power brakes shall be furnished. Brake linings shall be of nonasbestos material.

3.4.9 Steering. Power steering shall be furnished.

* 3.4.10 Tools. Tools required for exchanging a mounted tire assembly with the spare assembly, including at least a jack, jack handle, and wheel nut wrench, shall be provided.

* 3.4.11 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Inside rearview mirror
(b) Two padded sunvisors
(c) Front door mounted armrest on driver's side
(d) Driver's compartment ventilator other than window
(e) Domelight switch operable from driver's seat.

3.4.12 Rearview mirrors. An outside rearview mirror shall be provided on both sides. The outside rearview mirrors shall be of the Junior West Coast or low mount type incorporating a wide angle viewing system. The upper mirror shall have a flat reflective area of not less than 35 square inches. The lower mirror shall have a convex reflective area of not less than 20 square inches. The mirror assembly heads shall be adjustable and mounted to minimize obstruction of forward lines of vision.

3.5 Body. The body shall be a forward control integral cab and body with steel side panels and safety glass windows all around. Street and curbside doors, with roll-up type windows and grab handles in addition to the door operating handles, shall be provided for the driver and assistant driver. Split type double doors or a sliding door, with windows capable of being opened, shall be furnished on the curbside of the cargo space. Split type double doors, with windows capable of being opened, shall be furnished at the rear of the cargo space. The windows on the street side corresponding to curbside door windows shall be capable of being opened. Full length drip moldings shall be provided above the doors and windows that open. Curbside double doors or the sliding door shall be capable of being opened from the inside. All doors shall incorporate manufacturer's standard key locking arrangement. An assistant driver's seat shall be furnished. Two pairs of lap type seat belts shall be installed. Cargo space, immediately to the rear of the driver's seat, shall be not less than 100 inches in length, 53 inches in width (exclusive of wheelhousings), and 52 inches in height.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.5.1 Roof. The roof shall be a raised type to provide additional headroom and shall be of either the elevating type with vinylized canvas sidewalls or of the stationary type. The raised portion of the roof shall extend the length and width of the load space and shall provide inside headroom of not less than 73 inches plus or minus 1/2 inch. An elevating type roof shall be provided with spring assisted raising mechanisms. Stationary roof shall be of reinforced fiberglass with approximately 80 percent of the top of the raised roof having a green tinted translucent section to light the cargo area. The roof shall be styled to provide smooth lines for efficient air flow, rigidity, and good appearance. The roof shall be white except for the translucent section. The roof material shall withstand solar heat with no evidence of deformation. The roof shall be attached with corrosion-resistant fasteners and with a leakproof weather seal. The top shall be provided with fiber board molding on side roof sills as a protective border. The interior surface of the top shall be painted. An air vent shall be furnished at or near the ceiling. The vent shall he capable of being manually closed from the interior. The vent shall be louvered to shed water and moisture. The vent shall be retained with removable corrosion-resistant fasteners and shall be sealed inside and outside.

* 3.5.2 Interior trim. Anti-slip vinyl tile flooring, harmonizing with interior color, with aluminum bead border shall be furnished in the cargo space. Manufacturer's standard harmonizing color board paneling shall be installed on all interior surfaces except on the curbside loading doors.

3.5.3 Bench. A wooden frame bench, covered with a harmonizing vinyl upholstered cushion, shall be furnished across the rear of the cargo space. Seat belts and seat belt anchors are not required for the bench. The bench and seat back shall be securely attached to prevent movement when the vehicle is in transit.

3.5.4 Desk and chair. A light weight, table-top type desk and a castered, upholstered secretarial stool with back rest shall be furnished. The desk shall be approximately 54 inches long by 24 inches wide by 30 inches high, and shall be equipped with two drawers on the right hand side. The top drawer shall be approximately 13 inches wide by 6 inches high and full desk width in length. The bottom drawer shall be approximately 13 inches wide by 12 inches high and full desk width in length. The desk drawers shall be equipped with devices that automatically hold the drawers in a closed position when closed. Key-operated locks are not acceptable. The top of the desk shall be Formica or equal hard surface material, and shall be of harmonizing color. The desk shall be installed against the street side of the vehicle interior in such a position that a person seated at the desk will face the street side, and the left side of the desk shall be approximately 12 inches from the rear bench. The desk shall be secured to the vehicle interior in a manner which will permit easy removal and shall be locked in place with positive fasteners. Fasteners relying only on frictional forces are not acceptable. The chair shall be capable of being secured under the desk during transit. Chair upholstery shall be of a harmonizing color.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

3.5.5 Auxiliary 120-volt ac power sources. An inverter capable of converting the 12-volt dc vehicle power to not less than 200-watt, 120-volt ac, single phase, 60 hertz power shall be provided. In addition, a three-pronged (male) weatherproof slave receptacle for receiving external 120-volt ac power and grounding the vehicle shall be installed outside the vehicle on the curbside. A switch for operator selection of the inverter output or external power through the slave receptacle to energize the 120-volt ac interior receptacle and fluorescent lights (see 3.5.5.1 and 3.5.5.2) shall be provided. When specified (see 6.2), the inverter shall be of the capacity required to operate the audio-visual aids specified, in lieu of 200 watts. All electrical installations and methods shall conform to the applicable sections and articles of the National Electrical Code.

3.5.5.1 Interior electrical receptacle. A standard 120-volt ac grounded duplex receptacle shall be installed inside the vehicle, below the street side windows, approximately midway in the cargo space.

3.5.5.2 Fluorescent lights. Three 120-volt ac, 20-watt fluorescent lights shall be provided. The fixtures shall be alined parallel to the sides of the vehicle. One unit shall be located on each side of the vehicle, mounted to the side of center, and spaced to give even illumination. One unit shall be located near the desk. A light switch shall be provided, operable from the driver's seat. Lights and fixtures shall not project more than 4 inches below the original vehicle roof.

3.5.6 Auxiliary 24-volt system with radio outlet. When specified (see 6.2), an auxiliary 24-volt system with a shielded wiring harness and radio outlet shall be furnished. The receptacle shall conform to Drawing 7722352, and shall be marked with pressure sensitive tape: “24 VOLT RADIO OUTLET.” The receptacle shall be located on the side opposite the driver on the instrument panel in the cab. The shielded wiring harness shall be connected to the receptacle and the 24-volt system. The auxiliary 24-volt system output capacity shall be not less than 20 amperes. A converter type power supply, operable from the vehicle electrical system, shall be furnished.

3.5.7 Joint Optical Information Network (JOIN). When specified (see 6.2), the recruiting van shall be designed and constructed to accept the Joint Optical Information Network (JOIN) and a mobile telephone communication system. Storage space of not less than 75 cubic feet and of adequate dimensions to allow for the storage of the components of the JOIN system when the system is not in use shall be provided. Positive fasteners shall be provided within the storage areas to lock equipment in place and protect the equipment from undue stress and vibration while in transit. A collapsible work table of not less than 26 inches in height, 35.5 inches deep, and 54 inches long shall be provided. The work table surface shall withstand a load of not less than 300 pounds without evidence of deformation, warpage, or breakage. A space of 26 inches above the work table shall be free of encumberances and shall accommodate space for a printer, video

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

disc player, video monitor, keyboard, telephone and modem. Storage space and workspace shall be located in the rear of the van, shall provide for efficient set-up and shall not inhibit the flow of personnel to all van areas. A car phone and two 120 volt ac receptacles dedicated to the JOIN system shall be located at the work table.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust the vehicle for operational use including at least the following: alinement of lights; adjustment of engine and brake systems; filling and charging of battery; alinement of front wheels; inflation of all tires; complete lubrication of chassis, engine and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for conformance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on the front and rear axles. The total imposed loading on the front and rear axles shall be computed by the contractor and verified by the Government. using the curb weight, the operator weight at 175 pounds, and the payload required to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle shall be examined and road tested (less payload) by the contractor to assure that the vehicle will operate in accordance with the contractual requirements. The Government reserves the right to perform inspection requirements on first production vehicle with payload where such inspections are deemed necessary to assure the vehicle will operate in accordance with the contractual requirements.

4.3.3 Radio frequency suppression verification. The vehicle manufacturer shall indicate on the military questionnaire (commercial vehicle engineering data) if the vehicle will be suppressed to limit electromagnetic radiation in accordance with SAE J551.

4.3.4 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.5 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicle covered by this specification is intended for general nontactical use by the Government as a mobile recruiting facility.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(c) Identification of appropriate service for painting and marking (see 3.1.1.1).
(d) Rustproofing, if required (see 3.1.1.2).
(e) Tropical rustproofing, if required (see 3.1.1.2).
(f) Silicone brake fluid, if required (see 3.1.1.3).
(g) Power plant heaters, if required (see 3.4.1.3).
(h) If a battery heater is not required (see 3.4.1.3).
(i) Manually shifted transmission, if required (see 3.4.4.2).
(j) Positive-traction, limited-slip, or automatic locking differential, if required (see 3.4.6.1).
(k) Bias ply tires, if required (see 3.4.7).
(1) Inverter capacity to operate audio-visual aids, if required (see 3.5.5).
(m) Auxiliary 24-volt system with radio outlet, if required (see 3.5.6).
(n) Provisions for a JOIN system, if required (see 3.5.7).

* 6.3 Subject term (key word) listing.

Joint Optical Information Network
Mobile telephone communication system
Truck, compact
Truck, forward control van
Truck, recruiter
4x2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.

6.4 Identification of changes. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Air Force - 99

Review Activities:
Air Force - 84

User Activity:
Navy - MC

Preparing Activity:
Army - AT
Project No. 2320-0438

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15Z
Check the source to verify that this is the current version before use.